

SPECS

POLICE ROAD KING®



feedback

ENGINE

ENGINE ¹

Milwaukee-Eight® 114

BORE

4.016 in.

STROKE	4.5 in.
DISPLACEMENT	1,868 cc (114 cu in)
COMPRESSION RATIO	10.5:1
FUEL SYSTEM ³	Electronic Sequential Port Fuel Injection (ESPFI)
EXHAUST	Chrome, 2-1-2 dual exhaust with tapered mufflers

DIMENSIONS

LENGTH	96.5 in.
SEAT HEIGHT, LADEN ⁷	27.3 in.
SEAT HEIGHT, UNLADEN	31.1 in.
GROUND CLEARANCE	5.3 in.
RAKE (STEERING HEAD) (DEG)	26
TRAIL	6.7 in.
WHEELBASE	64 in.
TIRES, FRONT SPECIFICATION	BW 130/80B17 65H

feedback

TIRES, REAR SPECIFICATION	BW 180/65B16 81H
FUEL CAPACITY	6 gal.
OIL CAPACITY (W/FILTER)	5.2 qt.
WEIGHT, AS SHIPPED	805 lb.
WEIGHT, IN RUNNING ORDER	842 lb.
LUGGAGE CAPACITY -VOLUME	2.3 cu ft

PERFORMANCE

ENGINE TORQUE TESTING METHOD	J1349
ENGINE TORQUE ²	123 ft-lb
ENGINE TORQUE (RPM)	3,000
LEAN ANGLE, RIGHT (DEG.)	32
LEAN ANGLE, LEFT (DEG.)	32
FUEL ECONOMY TESTING METHOD ⁵	Estimated City/Hwy
FUEL ECONOMY	43 mpg

feedback

DRIVETRAIN

PRIMARY DRIVE	Chain, 34/46 ratio
GEAR RATIOS (OVERALL) 1ST	9.593
GEAR RATIOS (OVERALL) 2ND	6.65
GEAR RATIOS (OVERALL) 3RD	4.938
GEAR RATIOS (OVERALL) 4TH	4
GEAR RATIOS (OVERALL) 5TH	3.407
GEAR RATIOS (OVERALL) 6TH	2.875

CHASSIS

WHEELS, FRONT TYPE ³	Impeller Cast Aluminum
WHEELS, REAR TYPE	Impeller Cast Aluminum
BRAKES, CALIPER TYPE	32 mm, 4-piston fixed front and rear

ELECTRIC

feedback

**LIGHTS (AS PER COUNTRY REGULATION),
INDICATOR LAMPS ***

High beam, turn signals, neutral, low oil pressure, engine diagnostics, low fuel, neutral, battery, directional lights, digital speed display, speed capture, police emergency light activation, gear indication, ABS, miles to empty display

GAUGES

Easy to read and more functions; Speedometer is on top of the Tachometer for a better "heads up" view of speed

1. Recommended 91 octane or higher fuel (R+M)/2.
2. Values shown are nominal. Performance may vary by country and region.
3. Standard and optional fuel systems may vary by country.
4. See motorcycle owner's manual for complete details.
5. Estimated from fuel economy tests on a sample motorcycle from the corresponding family conducted by Harley Davidson under ideal laboratory conditions. Not all motorcycle models undergo fuel economy testing. Fuel economy and mileage may vary among motorcycle models within a family. Your mileage may vary depending on your personal riding habits, weather conditions, trip length, vehicle condition and vehicle configuration and other conditions. Break-in mileage may vary.
6. Prices listed are the Manufacturer's Suggested Retail Prices for base models. Options such as color are available at additional cost. Prices exclude tax, title, licensing, registration fees, destination charges, added accessories, and additional dealer charges, if any, and are subject to change. Harley-Davidson reimburses dealers for performing manufacturer-specified pre-delivery inspection and setup tasks. Dealer prices may vary.
7. Measurement reflects 180 lb. (81.7 kg) operator weight.
8. North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.
9. Standard and optional wheels may vary by country and region.

feedback