

|    | A   | B               | C   | D   | E  |
|----|---|-----------------|---|---|--|
| 1  | <b>CATEGORY 7: DISASTER MITIGATION</b>  |                 |   |   |  |
| 2  | Category Minimum 5 / Category Maximum 30  |                 |   |   |  |
| 3  |   | Points Achieved | Points Possible                               | Criteria  |  |
| 4  | <b>DM1 Hurricane (wind, rain, storm surge)</b>  |                 |   |   |  |
| 5  | DM1.01  |                 | 2   | Safe room   |  |
| 6  | DM1.02  |                 | 2   | Unvented attic or No attic  |  |
| 7  | DM1.03  |                 | 2   | Window, door, and skylight protection or impact resistant type  |  |
| 8  | DM1.04  |                 | 1   | Attached garage and exterior door protection  |  |
| 9  | DM1.05  |                 | 1   | Exterior structures and equipment properly anchored   |  |
| 10 | DM1.06  |                 | 2   | Secondary water protection installed on roof  |  |
| 11 | DM1.07  |                 | 2   | Adhesive applied to roof sheathing  |  |
| 12 | DM1.08  |                 | 2   | Roof Shingles   |  |
| 13 | DM1.09  |                 | 2   | Raised Slab or Pier Foundation  |  |
| 14 | DM1.10  |                 | 5   | Comply with Fortified For Safer Living Standards  |  |
| 15 |   |                 |   |   |  |
| 16 | <b>DM2 Flood (must incorporate all three)</b>   |                 |   |   |  |
| 17 | DM2.01  | 0               | 3   | Finished floor level at least 12" above 100 yr flood plain  |  |
| 18 |   |                 |   | Bottom of slab at least 8" above the top of backfilled dirt, graded for proper drainage               |  |
| 19 |   |                 |   | Garage floor & driveway sloped to drain out. Garage floor at least 4" lower than living floor         |  |
| 20 |   |                 |   |   |  |
| 21 | <b>DM3 Fire (must incorporate all three for 3.1)</b>  |                 |   |   |  |
| 22 | DM3.01  | 0               | 3   | Fire resistant exterior wall cladding   |  |
| 23 |   |                 |   | Fire resistant roof covering or sub-roof  |  |
| 24 |   |                 |   | Fire resistant soffit and vent material   |  |
| 25 | DM3.02  | 0               | 3   | Fire Sprinklers installed to cover 100% of living area of home  |  |
| 26 |   |                 |   |   |  |
| 27 | <b>DM4 Lightning &amp; Electronics Protection</b>   |                 |   |   |  |
| 28 | DM4.01  |                 | 1 - 2   | Installed Surge Suppression or Lightning Protection System  |  |
| 29 |   |                 |   |   |  |
| 30 | <b>DM5 Termites (must comply w/required credits listed below AND EITHER DM 5.1 OR DM 5.2 OR DM 5.3 to receive points)</b> |                 |   |   |  |
| 31 |   |                 | required                                      | Yes   | Seal slab penetrations (Health: H2.04)   |
| 32 |   |                 | required                                      | Yes   | Vegetation > 2 ft. from foundation (Materials: M3.06)  |
| 33 |   |                 | required                                      | Yes   | Sprinklers & emitters are 2 feet from house (Materials: M3.07) OR no installed irrigation (Water: W6.01) |
| 34 | DM 5.01   | 0               | 10  | <b>DM 5.01: Chemical Soil Treatment Used</b>  |  |
| 35 |   |                 |   | Exterior cladding installed to prohibit intrusion   |  |
| 36 |   |                 |   | Rain gutters installed (downspouts discharge a minimum of 3' from home) OR meet large overhangs (≥2') |  |
| 37 |   |                 |   | Condensate line(s) discharge a min of 2' from home & are located 5' or more from dryer vent           |  |
| 38 |   |                 |   | Irrigation/sprinkler water does not hit building  |  |
| 39 |   |                 |   | Damage replacement warranty issued and available for annual renewal                                   |  |
| 40 |   |                 |   | <b>OR</b>   |  |
| 41 | DM 5.02   |                 | 10  | <b>DM 5.02: Chemical Soil Treatment Avoided</b>   |  |
| 42 |   |                 |   | Chemical soil treatment avoided   |  |
| 43 |   |                 |   | Alternative Florida Building Code approved method of foundation protection employed                   |  |
| 44 |   |                 |   | <b>OR</b>   |  |
| 45 | DM 5.03   |                 | 12  | <b>DM 5.3: Treated wood products</b>  |  |
| 46 |   |                 |   | All wood products serving structural or exterior finish purposes are borate or ACQ treated            |  |
| 47 | DM5.04  |                 | 1   | 80% of Cellulose insulation used is Borate treated  |  |
| 48 |   |                 |   |   |  |
| 49 | <b>DM6 Mold Prevention</b>  |                 |   |   |  |
| 50 | DM6.01  |                 | 2   | Mold Prevention - ASTM D3273  |  |
| 51 |   |                 |   |   |  |
| 52 |   | 0               | 47  | Total Possible Points   |  |
| 53 |   |                 |   |   |  |
| 54 |   | 0               | Total points for Category 7 ( 5 min / 30 max) |   |  |
| 55 |   |                 |   |   |  |
| 56 | Certifying Agent Category 7:  |                 |   |   |  |