

65 Gallon Universal Roll Out Cart Specifications

Meets and/or exceeds all ANSI Standards

Manufacturing Process:	Injection Molding
Material:	High-density polyethylene resin (HDPE) Manufacturer: Exxon Type: HD-6605 Color pigment and ultraviolet inhibitor compounded together at 2% by weight
Wall Thickness:	Cart Minimum: 0.175 inches Critical Wear Points: 0.185 inches (Cart Bottom, handle & lift mechanisms) Lid Minimum: 0.140 inches
Cart Dimensions:	Height (includes lid): 40.5 inches Width: 26.7 inches Depth: 28.11 inches Resin weight: 27.5 pounds Assembled weight: 36 pounds Capacity: 66.25 gallons Load Rating: 227.5 pounds
Imprinting:	Hot stamp process permanently imprints logos and other information including serial numbers and user instruction
Lid Opening:	270 degrees
Lid Assembly:	Carts are shipped with the lids already attached
Catch Bar:	Integrally molded plastic catch bar or 1" corrosion resistant zinc plated steel catch bar which is easily installed
Axle:	High strength, low alloy steel 3/4 inches x 23.8 inches, zinc plated or powder coated equivalent" for corrosion protection
Wheel:	10" x 1.75" blow-molded plastic, snap-on, with integrated spacer
Handle:	Handle attachments are integrally molded part of the container body with a gripping area of 12 inches. Clearance between the cart body and the inside edge of the handle has been maximized to provide optimum control of a fully loaded cart
Lift System Compatibility:	Compatible with American semi-automated bar-locking lifters and fully automated arm lifters.
Truckload Quantity:	648, stacked 9 high



65 Gallon Nestable Bar Roll Out Cart Specifications

Meets and/or exceeds all ANSI Standards

Manufacturing Process:	Injection Molding
Material:	High-density polyethylene resin (HDPE) Manufacturer: Exxon Type: HD-6605 Color pigment and ultraviolet inhibitor compounded together at 2% by weight
Wall Thickness:	Cart Minimum: 0.175 inches Critical Wear Points: 0.185 inches (Cart Bottom, handle & lift mechanisms) Lid Minimum: 0.150 inches
Cart Dimensions:	Height (includes lid): 40.5 inches Width: 26.7 inches Depth: 28.11 inches Resin weight: 27.5 pounds Assembled weight: 36 pounds Capacity: 67.2 gallons Load Rating: 227.5 pounds
Imprinting:	Hot stamp process permanently imprints logos with serial numbers
Lid Opening:	270 degrees
Lid Assembly:	Carts are shipped with the lids already attached
Catch Bar:	Factory installed 1" corrosion resistant zinc plated steel or can be configured without a catch bar.
Axle:	High strength, low alloy steel 3/4 inches x 23.8 inches, zinc plated or powder coated equivalent" for corrosion protection
Wheel:	10" x 1.75" blow-molded plastic, snap-on, with integrated spacer
Handle:	Handle attachments are integrally molded part of the container body with a gripping area of 12 inches. Clearance between the cart body and the inside edge of the handle has been maximized to provide optimum control of a fully loaded cart
Lift System Compatibility:	Compatible with American semi-automated bar-locking lifters and fully automated arm lifters.
Truckload Quantity:	648, stacked 9 high

