

# NC.

S 20°56'47" E, a distance of 448.89 feet to the said Northerly Right-of-Way Line of South Rochaving for its elements a radius of 2839.93 feet to a point of tangency; thence S 72°10'56" We bearing of S 85°52'25" W, and a chord lengt

bearing of S DULL N 80°26'05" W, a distance of 692.80 N 69°09'25" W, a distance of 948.97 for respectively, of the Public Records of N

Said lands lying

and

situate

3

Monroe

County,

Florida,

containing

11,083,953

(254.452

acres),

9

AVIROM & ... 50 S.W. 2ND AVENUE, SUITE 102, BOCA TEL. (561) 392-2594, FAX (561) 394-7125 www.AVIROM-SURVEY.com YING ASSOCIATES, I G & MAPPING RATON, FLORIDA 33432

## Latitude (North) Longitude (West) Northing (US Feet) Easting (US Feet) Elevation (US Feet) 24\*33'23.53010" 081\*45'34.42350" 81,802.70 403,713.94 0.89 24\*33'23.53002" 81\*45'34.42314" 81802.69 403,713.97 0.71 EYW ARP 2 (PID AA0043) Latitude (North) | Longitude (West)

The following NGS horizontal stations were utilized:

EYW ARP 2 (PID AA0043)

Latitude (North) | Longitude (West) 

 Latitude (North)
 Longitude (West)
 Northing
 Easting

 24\*33'23.28023"
 081\*46'00.39025"
 81,790.75
 401,316.35

 24\*33'23.28034"
 81\*46'00.39016"
 81790.76
 401316.36

 Elevation Remarks
(US Feet)
1.21 Published
1.15 Observed

Northerly Boundary se of 2523.94 feet;

This map is intended to be displayed at a scale of 1:3600 (1"=300'). Units of measurement are in U.S. Survey Feet and decimal parts thereof. Well identified features in this survey were field measured to a horizontal positional accuracy of 0.10'. The intended use of the of this Survey is to graphically depict the boundary and calculate the area of the property described hereon. Abbreviation Legend:  $\Delta = \text{Central Angle}$ ; CB = Chord Bearing; CH = Chord Length; C.M. = Concrete Monument; D = Per Deed; F.B. = Field Book; F.D. = Found; F.D.O.T. = Florida Department of Transportation; D. = Identification; D. = Iron Pipe; I.R. = Iron Rod; L = Arc Length; L.B. = Licensed Business; M.C.R. = Monroe County Records; Ms = Measured; NAD = North American Datum; NGS = National Geodetic Survey; O.R.B. = Official Records Book; O/S = Offset; P.B. = Plat Book; PG(S) = Page(S); PID = Point Identifier; P.L.S. = Professional Land Surveyor; P.O.B. = Point of Beginning; P.R.M. = Permanent Reference Monument; R = Radius; R/W = Right-of-Way; RTN = Real-time REAL = North Months; R/W = Right-of-Way; RTN = Real-time REAL = North Months; R/W = Right-of-Way; RTN = Real-time REAL = North Months; R/W = Right-of-Way; RTN = Real-time REAL = North Months; R/W = Right-of-Way; RTN = Real-time REAL = North Months; R/W = Right-of-Way; RTN = Real-time REAL = North Months; R/W = Right-of-Way; RTN = Real-time REAL = North Months; R/W = Right-of-Way; RTN = Real-time REAL = North Months; R/W = Right-of-Way; RTN = Real-time REAL = North Months; R/W = Right-of-Way; RTN = Real-time REAL = North Months; R/W = Right-of-Way; RTN = Right-of-Way;  $RTN = \text{Righ$ 

### CERTIFICATION:

FEE SIMPLE
FEE SIMPLE
FEE SIMPLE
FEE SIMPLE
FEE SIMPLE

1952 1952 1980 1952 2000 1974

SURPLUS PROPERTY
SURPLUS PROPERTY
VIA WILL
SURPLUS PROPERTY
SURPLUS PROPERTY
SURPLUS PROPERTY

ACQUIRED

ACQUIRED

I HEREBY CERTIFY that the attached Boundary Survey of the hereon described property is true and correct to the best of my knowledge and belief as surveyed in the field under my direction. I FURTHER CERTIFY that this Boundary Survey meets the Standards of Practice set forth in Chapter 5J-17, Florida Administrative Code, pursuant to Section 472.027, Florida Statutes.

KEITH M. CHEE-A-TOW, P.L.S. Florida Registration No. 5328 AVIROM & ASSOCIATES, INC. L.B. No. 3300 EMAIL: keith@aviromsurvey.com

KEY WEST INTERNATIONAL AIRPORT PORTIONS OF SECTIONS 3 & 4 TOWNSHIP 68 SOUTH, RANGE 25 EAST JOB#

9133-6

**BOUNDARY SURVEY** 

KEY WEST MONROE COUNTY, FLORIDA

F.B.	CHECKED:	BY:	DATE:	SCALE:
1803	ŒD:			
PG.	K.M.C	SAM	06/23/2016	1" = 300'
_				