



CITY OF KEY WEST

Prepared for:	Contract Holder	10/31/24
CITY OF KEY WEST RICHARD SARVER 305-304-2397 richardsarver@cityofkeywest.fl.gov	Duval Ford Bambi Darr (Work) 904-381-6596 Bambi.Darr@duvalford.com 405 Lane Ave N Jacksonville, FL 32254	

Pricing through Bradford County Sheriff's Contract BCSO 22-27-1.0. Please note any items in red as they may require additional customer information or clarification. When submitting purchase order, please note billing address, delivery address, and any titling instructions. Thank you!

Code	Equipment	OEM Price Level:	BCSO Contract Price
2023 F5G	2023 FORD F-550 REGULAR CAB 169" WB DUAL REAR WHEELS 4X2 XL	\$ 48,469.00	\$ 45,543.74
OEM freight	Factory Destination	\$ 1,995.00	\$ 2,027.92
Z1	INTERIOR: Oxford White	\$ -	\$ -
AS	EXTERIOR: Medium Earth Gray vinyl; 40/20/40	\$ -	\$ -
660A	EQUIPMENT: XL	\$ -	\$ -
99T.44G	6.7L POWER STROKE DIESEL	\$ 9,096.00	\$ 9,246.08
90L	POWER WINDOWS & DOOR LOCKS	\$ -	\$ -
X4L	4.30 LIMITED SLIP AXLE	\$ 360.00	\$ 365.94
68M	PAYLOAD PLUS 19500# GVWR	\$ 1,051.00	\$ 1,068.34
535	HIGH CAPACITY TRAILER TOW PACKAGE (REQ 68M)	\$ 528.00	\$ 536.71
67P	EXTRA HEAVY DUTY FRONT END SUSPENSION	\$ 260.00	\$ 264.29
TGM	TIRES 225/70R19.5G BSW TRACTION	\$ 173.00	\$ 175.85
63C	AFT-AXLE FRAME EXTENSION	\$ 104.00	\$ 105.72
41H	ENGINE BLOCK HEATER	\$ 91.00	\$ 92.50
18Y	FORD PRO UPPFIT INTEGRATION SYSTEM	\$ (364.00)	\$ (364.00)
86M	DUAL 68 AH/65 AGM BATTERY	\$ -	\$ -
87Z	FACTORY BACKUP CAMERA	\$ 377.00	\$ 383.22
		\$ -	\$ -
Discount	Government Concession reflected in Base Vehicle Price		
Ceiling Markup	Primary Awardee Ceiling Markup	1.65%	
Discount	Net invoice discounts for Account reflected in Base vehicle Price	\$ (3,725.00)	
Ceiling Percentage Markup: Accessories		2.0%	
Ceiling Percentage Markup: AERIAL		2.0%	
ALTEC	Altec Model AT48S Articulating Telescopic Aerial Device, non-insulating with proportional joystick upper controls. Built in accordance to ALTEC's standard specifications and to include the following features: SEE FULL SPECS ATTACHED	\$ 118,466.00	\$ 158,744.44
Final Delivery			
0 Labor	Total Labor Hours for installation of parts	\$ -	\$ -
Freight	Freight on Parts	\$ -	\$ -
33040	Destination & Fuel to end user zip code (calculated from 32210 to EU zip Code)	\$ 2.00	\$ 1,012.00
		\$ -	\$ -
NOTE	TIMELINE FROM ALTEC IS 30 DAYS		
UNIT COST			\$ 219,202.76
TOTAL QUANTITY	1	TOTAL PURCHASE	\$ 219,202.76

CNGP530 VEHICLE ORDER CONFIRMATION 10/31/24 13:47:36
 ==> Dealer: F24081
 2023 F-SERIES SD Page: 1 of 2
 Order No: 9009 Priority: K2 Ord FIN: QE065 Order Type: SB Price Level: 350
 Ord PEP: 660A Cust/Flt Name: ME PO Number:
 RETAIL DLR INV RETAIL DLR INV
 F5G F550 4X2 CHAS/C \$51020 \$48469.00 FLEET SPCL ADJ NC \$(692.00)
 169" WHEELBASE 18Y UPPFIT INTER RMW (400) (364.00)
 Z1 OXFORD WHITE 19500# GVWR PKG
 A VNYL 40/20/40 41H ENG BLK HEATER 100 91.00
 S MED DARK SLATE 425 50 STATE EMISS NC NC
 660A PREF EQUIP PKG 535 HI CAP TRLR TOW 580 528.00
 .XL TRIM 63C AFT-AXL FRME EX 115 104.00
 57Z .AIR CONDITIONER NC NC 65Z AFT AXLE TANK NC NC
 .AMFM/MP3/CLK
 99T 6.7L V8 DIESEL 9995 9096.00 TOTAL BASE AND OPTIONS 65845 58461.30
 44G 10-SPD AUTOMATIC NC NC TOTAL 65845 58461.30
 TGM 225 TRACTION 190 173.00 *THIS IS NOT AN INVOICE*
 X4L 4.30 LTD SLIP 395 360.00
 68M PAYLD PLUS UPGR 1155 1051.00 * MORE ORDER INFO NEXT PAGE *
 67P XTR HD SUS FRNT \$285 \$260.00
 86M DUAL BATTERY NC NC
 87Z RR CAM & PREP K 415 377.00
 SP DLR ACCT ADJ (1277.00)
 SP FLT ACCT CR (1756.00)
 FUEL CHARGE 39.30
 B4A NET INV FLT OPT NC 7.00
 DEST AND DELIV 1995 1995.00
 TOTAL BASE AND OPTIONS 65845 58461.30
 TOTAL 65845 58461.30
 THIS IS NOT AN INVOICE

Street-Side View (Compartments Closed)



Street-Side Rear Corner View





October 18, 2024
Our 95th Year

Ship To:

Bill To:

Altec Sales Order: 7679483
Altec Quotation Number: 1491230 - 1
Run Number: 1398303
Account Manager: Cain Poynor
Technical Sales Rep: James Rizer
Reference WO: New Spec-
Customer Inspection:
Customer Truck Number:

X7 Discrete Job: 1020516641
X7 Configured Item: 000000000-34689024
Quantity: 1
X4 Discrete Job:
X4 Configured Item:
System Engineer: Josh Mull
Structural Engineer: Josh Mull
Line Set Date: 10/02/2023

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
	<u>Unit</u>		
1.	Altec Model AT48S Articulating Telescopic Aerial Device, non-insulating with proportional joystick upper controls. Built in accordance to ALTEC's standard specifications and to include the following features:	1	
2.	Pedestal	1	
3.	Single 2-Man Platform, Aluminum (Non-Insulated), 60" x 36" x 45", End Mount, 180 Degree Rotation.	1	
4.	Platform Mounted Single Handle Controls	1	
5.	Material Handling Jib/Winch, Hydraulically Articulating, Top Mounted, Round (ARM Jib)	1	
6.	Rubber Floor Liner With Drainage For 60 x 36 x 45 inch (1524 x 914 x 1143 mm) aluminum platform	1	
7.	Hydraulic Tool Circuit at Platform: Control easily accessible to the operator activates the tool circuit. One set of hydraulic tool outlets at the boom tip; they consist of one set of quick disconnect couplings at the platform, a valve assembly inside the control cover, and detented control handle. Operates open center tools	1	
8.	Engine Start/Stop & Secondary Stowage System: 12 VDC powered motor and pump assembly for temporary operation of the unit in a situation wherein the primary hydraulic source fails. Electric motor is powered by the chassis battery. This feature allows the operator to completely stow the booms, platform, and outriggers. Secondary Stowage & Start/Stop is activated with an air plunger at the platform or momentary switch at the lower control station and outriggers.	1	
9.	120 Volt Receptacle Installed At Platform	1	
10.	Jib Stick, 52" L, Extension Dependent, Non-Certified, grey in color	1	

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
11.	Platform Mounted Extendible Supports for Holding Signs	1	
12.	Slip Ring: Required for engine start/stop, secondary stowage system, and throttle control options	1	
13.	Outriggers, Primary, Modified A-Frame, 30"-34" Chassis Height, Electric Interlock, No Valves On Legs, 112" Spread, Fixed Shoe (AT48M/ME/P/PE/S/SE)	1	
14.	Auxiliary Vertical H Frame Outriggers with fixed shoe. For installation on a 30 to 34 inch chassis frame height. <ul style="list-style-type: none"> A. Maximum Spread: 87 inches B. Outrigger Motion Alarms C. Outrigger Interlocks: will not allow the unit to be operated until the outriggers have been at least partially deployed 	1	
15.	Lifting Eye - lifting eye on underside of lower boom. Rated at 1,000lbs (454kg) lifting capacity.	1	
16.	Winch load line swivel hook	1	
17.	Altec Unit Powder Painted White	1	
<u>Unit and Hydraulic Acc.</u>			
18.	Subbase	1	
19.	Electric Outrigger Controls for two (2) sets of outriggers, drive hydraulic outrigger control valves. Durable weather proof sealed electronic switches mounted in aluminum boxes located at the rear of the unit unless otherwise specified.	1	
20.	Steel Reservoir, 15 gallon capacity, rectangular, 26" L x 8.5" W x 20" H, and includes breather caps and dipsticks	1	
21.	Temperature Sight Gauge	1	
22.	HVI-22 Hydraulic Oil (Standard).	25	
23.	Standard Pump For PTO	1	
24.	Electric Shifted PTO	1	
25.	Standard PTO/Transmission Functionality for Small Ford and Dodge Chassis	1	
<u>Body</u>			
26.	132 inch Universal Aerial Body with outrigger housings, suitable for installing on any chassis with an approximate CA dimension of 84 inches, built in accordance with the following specifications: <ul style="list-style-type: none"> A. Basic body fabricated from A40 grade 100% zinc alloy coated steel. B. All doors are full, double paneled, self-sealed with built-in drainage. C. Stainless steel hinge rods extend full length of door. D. Door hinges are zinc alloy material attached with rivets. E. All doors contain stainless steel, flush mounted, paddle activated rotary style latches with two-stage locking, including keyed locks and adjustable strikers. F. Heavy-gauge welded steel frame construction with structural channel 	1	

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
	crossmembers and treadplate floor.		
G.	All edges are either rolled or folded for strength and safety.		
H.	Door header drip rail at top for maximum weather protection.		
I.	Neoprene or rolled fenders on wheel fender panels.		
J.	Steel treated for improved primer bond and rust resistance.		
K.	Automotive underseal applied to body.		
L.	Automotive type non-porous door seals mechanically fastened to the door facing.		
M.	132 Inch Body Length		
N.	40 Inch Body Height (Standard)		
O.	94 Inch Body Width (Standard)		
P.	20 Inch Body Compartment Depth (Standard)		
Q.	Body Color - White (Standard)		
R.	Finish Paint Body At Body Manufacturer (Standard)		
S.	6 Inch Tall Wooden Tailboard Installed At The Rear of Body Cargo Area		
T.	Stainless Steel Rotary Paddle Latch With Lock (Standard)		
U.	Master Body Locking System (Standard)		
V.	One Chock Holder On Each Side of Body With Retaining Lip In Fender Panel (Standard)		
W.	Gas Shock Type Rigid Door Holders For Vertical Doors (Standard)		
X.	Chains On Horizontal Doors		
Y.	Hotstick Shelf Extending From Rear Of First Vertical To Rear Of Body On Curbside, With Standard Sized Drop-Down Door		
Z.	Hotstick Shelf Extending Full Length Of Body On Streetside, With Standard Sized Drop-Down Door		
AA.	1st Vertical Street Side (LH) - Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers		
AB.	1st Vertical Street Side (LH) - Outrigger Housing, With Outrigger Pin Access As Needed		
AC.	2nd Vertical Street Side (LH) - Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers		
AD.	1st Horizontal Street Side (LH) - One (1) Fixed Shelf With Removable Dividers On 4 Inch Centers Installed On Bottom of Compartment		
AE.	Rear Vertical Street Side (LH) - Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers		
AF.	1st Vertical Curb Side (RH) - Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers		
AG.	1st Vertical Curb Side (RH) - Inverter Storage Inside Of Body Compartment With Guard And Provisions For Remote GFCI Receptacle		
AH.	1st Vertical Curb Side (RH) - Outrigger Housing, With Outrigger Pin Access As Needed		
AI.	2nd Vertical Curb Side (RH) - Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers		
AJ.	1st Horizontal Curb Side (RH) - One (1) Fixed Shelf With Removable Dividers On 4 Inch Centers Installed On Bottom of Compartment		
AK.	Rear Vertical Curb Side (RH) - Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers		
AL.	48 Tailshelf with Integrated Side Access Steps And One (1) Post-Style Grab Handle Installed To The Rear Of Access Steps		
AM.	One (1) Grab Handle Installed On Rear Of Curbside Sidepack.		
AN.	Two (2) Compartment Top Hotstick Bins, One (1) Installed Each Side. 122 Inch Long x 21 Inch Wide x 16 Inch High, With Drop-Down Door At Rear, And Bolt-On Panel At Front For Clean Out.		

Body and Chassis Accessories

27.	Underride Protection Bumper Installed At Rear	1
-----	---	---



<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
28.	Receiver Hitch, 2", Class 3	1	
29.	Set Of Eye Bolts for Trailer Safety Chain, installed one each side of towing device mount.	1	
30.	SuperSpring Installed at Streetside Rear Leaf Spring to Level Chassis	1	
31.	Rigid Step Mounted Beneath Side Access Steps (Installed To Extend Approx. 2" Outward)	1	
32.	Platform Rest, Rigid with Rubber Tube	1	
33.	Articulating Arm Rest for a Telescopic Unit	1	
34.	Boom Rest for a Telescopic Unit	1	
35.	Wood Outrigger Pad, 19" x 19" x 2.5", With Rope Handle	4	
36.	Outrigger Pad Holder, 20" L x 20" W x 7" H, Fits 19.5" x 19.5" And Smaller Pads, Bolt-On, Bottom Washout Holes, 3/4" Lip Retainer	2	
37.	Pendulum Retainers For Outrigger Pad Holders	2	
38.	Mud Flaps With Altec Logo (Pair)	1	
39.	Wheel Chocks, Rubber, 9.75" L x 7.75" W x 5.00" H, with 4" L Metal Hairpin Style Handle (Pair)	1	
40.	Slope Indicator Assembly (Pair) For Machine With Outriggers	1	
41.	Safety Harness & 4.5 FT Lanyard (Medium To X-large)	2	
42.	Driveaway Safety Kit	1	
43.	Vinyl manual pouch for storage of all operator and parts manuals	1	
<u>Electrical Accessories</u>			
44.	Lights and reflectors in accordance with FMVSS #108 lighting package. (Complete LED, including LED reverse lights)	1	
45.	4-Corner Strobes, Amber, LED, Two (2) Surface Mounted Lights In Grille, Two (2) Round Lights At Rear	1	
46.	Strobe Beacons, Amber LED, with Brush Guard, Installed on Post at Front of Body, One (1) Each Side (Standard) (Tecniq #K10-AAAD-1)	1	
47.	Dual Tone Back-Up With Outrigger Motion Alarm	1	
48.	PTO Hour Meter, Digital, with 10,000 Hour Display	1	
49.	7-Way Trailer Receptacle (Blade Type) Installed At Rear	1	
50.	Ford Upfitter Switches (Supplied with Chassis)	1	
51.	Inverter with Minimum 2000W 120V @ 16A Pure Sine Wave Output, Hardwired to Outlets and 12VDC Input. Features Include Surge Ratings at 300 Percent for 1 ms, 200	1	



<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
	Percent for 100 ms and 4/0 AWG 12V Wiring.		
52.	Inverter Wired Battery Hot To Switch Mounted In Chassis Cab	1	
53.	Install inverter inside 1st vertical compartment on curbside.	1	
54.	120 Volt GFCI Receptacle, Includes Weather-Resistant Enclosure, Installed In Curbside 1st Vertical Near Inverter	1	
55.	GFCI Receptacle Hardwired To Protect Additional Non-GFCI Duplex Receptacles.	1	
56.	Install Wiring for Additional Non-GFCI Receptacle Located at Platform (15 Amps Maximum)	1	
57.	Power Distribution Module Is A Compact Self-Contained Electronic System That Provides A Standardized Interface With The Chassis Electrical System. (Includes Operator's Manual)	1	
58.	Install Chassis (OEM) Supplied Backup Camera in Final Assembly	1	
59.	Install secondary stowage system.	1	
60.	Install Remote Start/Stop system in Final Assembly.	1	
61.	Install Outrigger Interlock System	1	
62.	Heavy Duty Secondary Stowage Pump	1	
63.	PTO Indicator Light Installed In Cab	1	
<u>Finishing Details</u>			
64.	Powder Coat Unit Altec White	1	
65.	Finish Paint Body Accessories Above Body Floor Altec White	1	
66.	Altec Standard; Components mounted below frame rail shall be coated black by Altec. i.e. step bumpers, steps, frame extension, pintle hook mount, dock bumper mounts, D-rings, receiver tubes, accessory mounts, light brackets, under-ride protection, etc. Components mounted to under side of body shall be coated black by Altec. i.e. Wheel chock holders, mud flap brackets, pad carriers, boxes, lighting brackets, steps, and ladders.	1	
67.	Apply Non-Skid Coating to all walking surfaces	1	
68.	English Safety And Instructional Decals	1	
69.	Vehicle Height Placard - Installed In Cab	1	
70.	Placard, HVI-22 Hydraulic Oil	1	
71.	Stability test unit according to ANSI requirements.	1	
72.	Focus Factory Build	1	
73.	Delivery Of Completed Unit	1	
74.	Inbound Freight	1	



<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
75.	As Built Electrical And Hydraulic Schematics To Be Included In The Manual Pouch	1	
76.	Altec Stock/Global Spec, AT48S, ARM Jib, LGSS Body, Ford F550 4x2	1	
77.	Stock Unit	1	
78.	Stock Unit Sold To Customer	1	
<u>Chassis</u>			
79.	Altec Supplied Chassis	1	
80.	Altec Stock Chassis	1	

Sales Text: Details:

-EC chassis config# 000000222-970825469

Last Updated By: James Rizer on 27-OCT-2023 11:02

- A. 2024 Model Year
- B. Ford F550
- C. Chassis Cab
- D. Regular Cab
- E. 4x2 Drivetrain
- F. Chassis Color - White
- G. Ford 6.7L Power Stroke Diesel
- H. Diesel
- I. 330 HP Engine Rating
- J. Ford Torqshift 10-Speed Automatic Transmission (w/PTO Provision)
- K. Clear Cab to Axle Length - 84 inches
- L. Wheelbase Length - 169 inches
- M. 19,500 LBS Gross Vehicle Weight Rating (GVWR)
- N. 7,500 LBS Front Axle Weight Rating (FAWR)
- O. 14,706 LBS Rear Axle Weight Rating (RAWR)
- P. Spring Suspension
- Q. Ford E/F250-550 Single Horizontal Right Side Exhaust
- R. Hydraulic Brakes
- S. Park Brake In Rear Wheels
- T. Ford 40 Gallon Fuel Tank (Rear)
- U. Ford 7.2 Gallon DEF Tank (Mid Mount)
- V. Dual Rear Wheels
- W. 225/70R19.5 Front Tire (Traction)
- X. 225/70R19.5 Rear Tire (Traction)
- Y. 98R - Operator Commanded Regeneration (OCR)
- Z. 63C - Aft Axle Frame Extension
- AA. No Idle Engine Shut-Down Required
- AB. 50-State Emissions
- AC. CARB Compliant
- AD. Clean Idle Certification
- AE. AM/FM Radio
- AF. Air Conditioning
- AG. Backup Camera, OEM Supplied
- AH. Block Heater
- AI. Bluetooth
- AJ. Cruise Control
- AK. Ford SYNC
- AL. Keyless Entry



<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
AM.	Limited Slip Rear Axle		
AN.	Power Door Locks		
AO.	Power Windows		
AP.	872 - Rear View Camera and Prep Kit		
AQ.	Side Mirrors, Power Adjusting, Manual Folding, Manual Telescoping with Heated Glass		
AR.	Skid Plate		
AS.	Tachometer		
AT.	Tilt Steering Wheel		
AU.	Trailer Brake Controller (Factory Installed)		
AV.	Vinyl Split Bench Seat		

Additional Pricing

81.	Standard Altec Warranty: One (1) year parts warranty, one (1) year labor warranty, ninety (90) days warranty for travel charges, limited lifetime structural warranty	1	
-----	---	---	--

Altec Industries, Inc.

BY _____
James Rizer , Technical Sales Representative

Unselected Items

<u>Item Number</u>	<u>Description</u>
970815712-	Chassis, Altec Stock/Global, 2023 Ford F550 4x2, Altec White, Ford 6.7L Power Stroke Diesel (330 HP), Ford Torqshift 10-Speed Automatic, Hydraulic Brakes, 84" Clear CA, 19500 LB GVWR, 7500 LB FAWR, 14706 LB RAWR, Curbside Horizontal Exhaust

Unselected By:James Rizer on 27-OCT-2023 11:02

New Selected Items

<u>Item Number</u>	<u>Description</u>
970825469-	Chassis, Altec Stock/Global, 2024 Ford F550 4x2, Altec White, Ford 6.7L Power Stroke Diesel (330 HP), Ford Torqshift 10-Speed Automatic, Hydraulic Brakes, 84 Clear CA, 19500 LB GVWR, 7500 LB FAWR, 14706 LB RAWR, Curbside Horizontal Exhaust

Details:
-EC chassis config# 000000222-970825469
Created By:James Rizer on 27-OCT-2023 11:02