



SBL Freightliner, LLC

2840 Center Port Circle
Pompano Beach, Florida 33064
Florida Sheriff Assoc.

Purchaser: KEY WEST CITY OF Date: 10/21/2019

Address: _____ Phone: _____

City: KEY WEST FL. Attn: RICHARD

Base Model FSA 18-VEH 16.0 FREIGHTLINER **Price** _____

Option # SPEC 15 BASE PRICE Price \$57,750

Option # DLR-58GVW 58,000GVW Price \$26,750

Option # DLR-12YD 12 YD DUMP BODY Price \$22,500

Option # TOW PACK SEE DLR-12YD ABOVE Price \$3,960

Option # BACKUP CAMERA SEE DLR-12YD Price \$1,650

Option # _____ Price _____

Option # EXTRA KEYS INCLUDED Price _____

Option # _____ Price _____

Option # ALL ITEMS PER ATTACHED FREIGHTLINER PRINT OUT Price _____

Option # _____ Price _____

Option # _____ Price _____

Option # _____ Price _____

Option # _____ Price _____

Option # _____ Price _____

Option # _____ Price _____

Option # _____ Price _____

Option # _____ Price _____

Option # _____ Price _____

Option # _____ Price _____

Option # _____ Price _____

Total Price \$112,610 EACH

KEY WEST CITY OF
 12 YD DUMP BODY
 QUOTATION

114SD CONVENTIONAL CHASSIS

SET BACK AXLE - TRUCK	18,000# FLAT LEAF FRONT SUSPENSION
CUM L9 350 HP @ 2000 RPM, 2200 GOV RPM, 1000 LB/FT @ 1400 RPM	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB
ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	4600MM (181 INCH) WHEELBASE
MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE	7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI
HENDRICKSON RTE403 @40,000# REAR SUSPENSION	1900MM (75 INCH) REAR FRAME OVERHANG
DETROIT DA-F-18.0-5 18,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE	1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT

	TOTAL # OF UNITS (1)	PER UNIT	TOTAL
VEHICLE PRICE	\$	\$	
EXTENDED WARRANTY	\$	\$	
DEALER INSTALLED OPTIONS	\$	\$	
CUSTOMER PRICE BEFORE TAX	\$	\$	

TAXES AND FEES

FEDERAL EXCISE TAX (FET)	\$	\$
TAXES AND FEES	\$	\$
OTHER CHARGES	\$	\$

TRADE-IN

TRADE-IN ALLOWANCE	\$	(0)	\$	(0)
---------------------------	----	-----	----	-----

BALANCE DUE	(LOCAL CURRENCY)	\$	112,610	\$	112,610
--------------------	-------------------------	-----------	----------------	-----------	----------------

COMMENTS: Projected delivery on ___ / ___ / ___ provided the order is received before ___ / ___ / ___.

APPROVAL: Please indicate your acceptance of this quotation by signing below: Customer:

X _____ Date: ___ / ___ / ___.

Daimler Truck Financial

Financing that works for you.

See your local dealer for a competitive quote from Daimler Truck Financial, or contact us at Information@dtoffers.com.

Daimler Truck Financial offers a variety of finance, lease and insurance solutions to fit your business needs. For more information about our products and services, visit our website at www.daimler-truckfinancial.com.



SPECIFICATION PROPOSAL

	Description
Price Level	SD PRL-20D (EFF:04/30/19)
Data Version	SPECPRO21 DATA RELEASE VER 022
Vehicle Configuration	114SD CONVENTIONAL CHASSIS 2020 MODEL YEAR SPECIFIED SET BACK AXLE - TRUCK TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK LH PRIMARY STEERING LOCATION
General Service	TRUCK/TRAILER CONFIGURATION DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES) UTILITY/REPAIR/MAINTENANCE SERVICE GOVERNMENT BUSINESS SEGMENT DIRT/SAND/ROCK COMMODITY TERRAIN/DUTY: 10% (SOME) OF THE TIME, IN TRANSIT, IS SPENT ON NON-PAVED ROADS MAXIMUM 8% EXPECTED GRADE MAINTAINED GRAVEL OR CRUSHED ROCK - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE FREIGHTLINER LEVEL II WARRANTY EXPECTED FRONT AXLE(S) LOAD : 18000.0 lbs EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 58000.0 lbs



	Description
	EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs
Truck Service	END DUMP BODY 3-V DISTRIBUTING INC
Tractor Service	FLATBED TRAILER SINGLE (1) TRAILER
Engine	CUM L9 350 HP @ 2000 RPM, 2200 GOV RPM, 1000 LB/FT @ 1400 RPM
Electronic Parameters	75 MPH ROAD SPEED LIMIT CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT PTO MODE ENGINE RPM LIMIT - 1100 RPM PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED PTO RPM WITH CRUISE SET SWITCH - 700 RPM PTO RPM WITH CRUISE RESUME SWITCH - 800 RPM PTO MODE CANCEL VEHICLE SPEED - 5 MPH PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND PTO MINIMUM RPM - 700 REGEN INHIBIT SPEED THRESHOLD - 5 MPH
Engine Equipment	2016-2019 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION NO 2008 CARB EMISSION CERTIFICATION STANDARD OIL PAN ENGINE MOUNTED OIL CHECK AND FILL SIDE OF HOOD AIR INTAKE WITH DONALDSON HIGH CAPACITY AIR CLEANER WITH SAFETY ELEMENT, FIREWALL MOUNTED DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE

Description

(3) DTNA GENUINE, FLOODED STARTING, MIN
3000CCA, 555RC, THREADED STUD BATTERIES
BATTERY BOX FRAME MOUNTED
STANDARD BATTERY JUMPERS
SINGLE BATTERY BOX FRAME MOUNTED LH
SIDE BACK OF CAB
WIRE GROUND RETURN FOR BATTERY CABLES
WITH ADDITIONAL FRAME GROUND RETURN
NON-POLISHED BATTERY BOX COVER
CAB AUXILIARY POWER CABLE
CUMMINS TURBOCHARGED 18.7 CFM AIR
COMPRESSOR WITH INTERNAL SAFETY VALVE
ELECTRONIC ENGINE INTEGRAL SHUTDOWN
PROTECTION SYSTEM
NO RETARDER
RH OUTBOARD UNDER STEP MOUNTED
HORIZONTAL AFTERTREATMENT SYSTEM
ASSEMBLY WITH RH B-PILLAR MOUNTED
VERTICAL TAILPIPE
ENGINE AFTERTREATMENT DEVICE,
AUTOMATIC OVER THE ROAD REGENERATION
AND DASH MOUNTED REGENERATION
REQUEST SWITCH
09 FOOT 06 INCH (114 INCH+0/-5.9 INCH)
EXHAUST SYSTEM HEIGHT
RH CURVED VERTICAL TAILPIPE B-PILLAR
MOUNTED ROUTED FROM STEP
6 GALLON DIESEL EXHAUST FLUID TANK
100 PERCENT DIESEL EXHAUST FLUID FILL
STANDARD DIESEL EXHAUST FLUID PUMP
MOUNTING
LH MEDIUM DUTY STANDARD DIESEL EXHAUST
FLUID TANK LOCATION
STANDARD DIESEL EXHAUST FLUID TANK CAP
ALUMINUM AFTERTREATMENT
DEVICE/MUFFLER/TAILPIPE SHIELD(S)
HORTON DRIVEMASTER ADVANTAGE ON/OFF
FAN DRIVE
AUTOMATIC FAN CONTROL WITHOUT DASH
SWITCH, NON ENGINE MOUNTED
CUMMINS SPIN ON FUEL FILTER
COMBINATION FULL FLOW/BYPASS OIL FILTER
FLEETGUARD PLAIN COOLANT FILTER

Description

1300 SQUARE INCH ALUMINUM RADIATOR
ANTIFREEZE TO -34F, ETHYLENE GLYCOL PRE-
CHARGED SCA HEAVY DUTY COOLANT
GATES BLUE STRIPE COOLANT HOSES OR
EQUIVALENT
CONSTANT TENSION HOSE CLAMPS FOR
COOLANT HOSES
RADIATOR DRAIN VALVE
ELECTRIC GRID AIR INTAKE WARMER
DELCO 12V 38MT HD STARTER WITH
INTEGRATED MAGNETIC SWITCH

Transmission

ALLISON 3000 RDS AUTOMATIC TRANSMISSION
WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -
AVAILABLE ON 3000/4000 PRODUCT FAMILIES
WITH VOCATIONAL MODELS RDS, HS, MH AND
TRV
ALLISON VOCATIONAL RATING FOR ON/OFF
HIGHWAY APPLICATIONS AVAILABLE WITH ALL
PRODUCT FAMILIES
PRIMARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
SECONDARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
PRIMARY SHIFT SCHEDULE RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SCHEDULE
RECOMMENDED BY DTNA AND ALLISON, THIS
DEFINED BY ENGINE AND VOCATIONAL USAGE
PRIMARY SHIFT SPEED RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SPEED RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
FUEL SENSE 2.0 DISABLED - PERFORMANCE -
TABLE BASED
DRIVER SWITCH INPUT - DEFAULT - NO
SWITCHES

Description

MAGNETIC PLUGS, ENGINE DRAIN,
TRANSMISSION DRAIN, AXLE(S) FILL AND
DRAIN
PUSH BUTTON ELECTRONIC SHIFT CONTROL,
DASH MOUNTED
TRANSMISSION PROGNOSTICS - ENABLED 2013
WATER TO OIL TRANSMISSION COOLER, IN
RADIATOR END TANK
TRANSMISSION OIL CHECK AND FILL WITH
ELECTRONIC OIL LEVEL CHECK
SYNTHETIC TRANSMISSION FLUID (TES-295
COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-18.0-5 18,000# FL1 71.0 KPI/3.74
DROP SINGLE FRONT AXLE
MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT
BRAKES, DOUBLE ANCHOR, FABRICATED
SHOES
NON-ASBESTOS FRONT BRAKE LINING
CONMET CAST IRON FRONT BRAKE DRUMS
FRONT BRAKE DUST SHIELDS
FRONT OIL SEALS
VENTED FRONT HUB CAPS WITH WINDOW,
CENTER AND SIDE PLUGS - OIL
STANDARD SPINDLE NUTS FOR ALL AXLES
MERITOR AUTOMATIC FRONT SLACK
ADJUSTERS
STANDARD KING PIN BUSHINGS
TRW TAS-85 POWER STEERING
POWER STEERING PUMP
2 QUART SEE THROUGH POWER STEERING
RESERVOIR
SYNTHETIC 75W-90 FRONT AXLE LUBE

Front Suspension

18,000# FLAT LEAF FRONT SUSPENSION
GRAPHITE BRONZE BUSHINGS WITH SEALS -
FRONT SUSPENSION
NO FRONT SUSPENSION OPTIONS
FRONT SHOCK ABSORBERS

Rear Axle and Equipment

Description

MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE
5.29 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING
MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES
MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES
(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE
BLINKING LAMP WITH EACH INTERAXLE LOCK SWITCH, INTERAXLE UNLOCK DEFAULT WITH IGNITION OFF
BLINKING LAMP WITH EACH MODE SWITCH, DIFFERENTIAL UNLOCK WITH IGNITION OFF, ACTIVE <5 MPH
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
NON-ASBESTOS REAR BRAKE LINING
ASPHALT SPREADER CLEARANCE REAR BRAKE GEOMETRY
CAST IRON OUTBOARD REAR BRAKE DRUMS
REAR BRAKE DUST SHIELDS
REAR OIL SEALS
WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS
HALDEX AUTOMATIC REAR SLACK ADJUSTERS
SYNTHETIC 75W-90 REAR AXLE LUBE
STANDARD REAR AXLE BREATHER(S)

Rear Suspension

HENDRICKSON RTE403 @40,000# REAR SUSPENSION
HENDRICKSON RT/RTE - 7.19" SADDLE
STANDARD AXLE SEATS IN AXLE CLAMP GROUP
52 INCH AXLE SPACING

Description

STEEL BEAMS AND RUBBER CENTER
BUSHINGS WITH BAR PIN ADJUSTABLE END
CONNECTIONS
FORE/AFT CONTROL RODS

Brake System

WABCO 4S/4M ABS
REINFORCED NYLON, FABRIC BRAID AND WIRE
BRAID CHASSIS AIR LINES
FIBER BRAID PARKING BRAKE HOSE
STANDARD BRAKE SYSTEM VALVES
STANDARD AIR SYSTEM PRESSURE
PROTECTION SYSTEM
STD U.S. FRONT BRAKE VALVE
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE,
NO REAR PROPORTIONING VALVE
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER
AIR DRYER FRAME MOUNTED
STEEL AIR BRAKE RESERVOIRS
CLEAR FRAME RAILS FROM BACK OF CAB TO
FRONT REAR SUSPENSION BRACKET, BOTH
RAILS OUTBOARD
BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER
ON ALL TANK(S)

Trailer Connections

AIR CONNECTIONS TO END OF FRAME WITH
GLAD HANDS FOR TRUCK AND NO DUST
COVERS
PRIMARY CONNECTOR/RECEPTACLE WIRED
FOR SEPARATE STOP/TURN, ABS CENTER PIN
POWERED THROUGH IGNITION
SAE J560 7-WAY PRIMARY TRAILER CABLE
RECEPTACLE MOUNTED END OF FRAME
UPGRADED CHASSIS MULTIPLEXING UNIT

Wheelbase & Frame

4600MM (181 INCH) WHEELBASE
7/16X3-9/16X11-1/8 INCH STEEL FRAME
(11.11MMX282.6MM/0.437X11.13 INCH) 120KSI
1/4 INCH (6.35MM) C-CHANNEL INNER FRAME
REINFORCEMENT
1900MM (75 INCH) REAR FRAME OVERHANG

Description

FRAME OVERHANG RANGE: 71 INCH TO 80 INCH
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 115.55 in
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 112.55 in
CALC'D FRAME LENGTH - OVERALL : 286.02
CALCULATED FRAME SPACE LH SIDE : 31.65 in
CALCULATED FRAME SPACE RH SIDE : 170.29 in
CALC'D SPACE AVAILABLE FOR DECKPLATE : 115.45 in
SQUARE END OF FRAME
FRONT CLOSING CROSSMEMBER
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD MIDSHIP #1 CROSSMEMBER(S)
STANDARD REARMOST CROSSMEMBER
STANDARD SUSPENSION CROSSMEMBER

Chassis Equipment

14 INCH PAINTED STEEL BUMPER
BUMPER MOUNTING FOR SINGLE LICENSE PLATE
BETTS B-35 PAINTED MUDFLAP BRACKETS
GRADE 8 THREADED HEX HEADED FRAME FASTENERS

Fuel Tanks

80 GALLON/302 LITER ALUMINUM FUEL TANK - LH
25 INCH DIAMETER FUEL TANK(S)
PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS
FUEL TANK(S) FORWARD
PLAIN STEP FINISH
FUEL TANK CAP(S)
DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR
EQUIFLO INBOARD FUEL SYSTEM
NO NATURAL GAS VEHICLE FUEL TANK VENT LINE/STACK

Description

HIGH TEMPERATURE REINFORCED NYLON
 FUEL LINE

Tires

MICHELIN XZY-3 385/65R22.5 18 PLY RADIAL
 FRONT TIRES
 MICHELIN X MULTI D 11R22.5 14 PLY RADIAL
 REAR TIRES

Hubs

CONMET PRESET PLUS PREMIUM IRON FRONT
 HUBS
 CONMET PRESET PLUS PREMIUM IRON REAR
 HUBS

Wheels

MAXION WHEELS 10035 22.5X12.25 10-HUB
 PILOT 4.75 INSET 5-HAND STEEL DISC FRONT
 WHEELS
 ACCURIDE 42644 ACCU-LITE 22.5X8.25 10-HP
 ALUMINUM DISC REAR WHEELS
 NO FRONT HUB COVERS

Cab Exterior

114 INCH BBC FLAT ROOF ALUMINUM
 CONVENTIONAL CAB
 AIR CAB MOUNTING
 NONREMOVABLE BUGSCREEN MOUNTED
 BEHIND GRILLE
 FRONT FENDERS SET-BACK AXLE
 BOLT-ON MOLDED FLEXIBLE FENDER
 EXTENSIONS
 LH AND RH GRAB HANDLES
 STATIONARY BLACK GRILLE
 BLACK HOOD MOUNTED AIR INTAKE GRILLE
 FIBERGLASS HOOD
 SINGLE 14 INCH ROUND HADLEY AIR HORN
 UNDER LH DECK
 SINGLE ELECTRIC HORN
 SINGLE HORN SHIELD
 DOOR LOCKS AND IGNITION SWITCH KEYED
 THE SAME WITH (4) KEYS
 REAR LICENSE PLATE MOUNT END OF FRAME



Description

HALOGEN COMPOSITE HEADLAMPS WITH
BLACK BEZELS
(5) AMBER MARKER LIGHTS
INTEGRAL STOP/TAIL/BACKUP LIGHTS
STANDARD FRONT TURN SIGNAL LAMPS
NO WORK LIGHT
DUAL WEST COAST BRIGHT FINISH MIRRORS
DOOR MOUNTED MIRRORS
102 INCH EQUIPMENT WIDTH
LH AND RH 8 INCH BRIGHT FINISH CONVEX
MIRRORS MOUNTED UNDER PRIMARY
MIRRORS
STANDARD SIDE/REAR REFLECTORS
63X14 INCH TINTED REAR WINDOW
TINTED DOOR GLASS LH AND RH WITH TINTED
NON-OPERATING WING WINDOWS
MANUAL DOOR WINDOW REGULATORS
TINTED WINDSHIELD
2 GALLON WINDSHIELD WASHER RESERVOIR
WITHOUT FLUID LEVEL INDICATOR, FRAME
MOUNTED

Cab Interior

OPAL GRAY VINYL INTERIOR
MOLDED PLASTIC DOOR PANEL
MOLDED PLASTIC DOOR PANEL
BLACK MATS WITH SINGLE INSULATION
NO DASH MOUNTED ASH TRAYS AND LIGHTER
FORWARD ROOF MOUNTED CONSOLE WITH
UPPER STORAGE COMPARTMENTS WITHOUT
NETTING
IN DASH STORAGE BIN
(2) CUP HOLDERS LH AND RH DASH
GRAY/CHARCOAL FLAT DASH
HEATER, DEFROSTER AND AIR CONDITIONER
STANDARD HVAC DUCTING
MAIN HVAC CONTROLS WITH RECIRCULATION
SWITCH
STANDARD HEATER PLUMBING
VALEO HEAVY DUTY A/C REFRIGERANT
COMPRESSOR

Description

BINARY CONTROL, R-134A
STANDARD INSULATION
SOLID-STATE CIRCUIT PROTECTION AND
FUSES
12V NEGATIVE GROUND ELECTRICAL SYSTEM
DOME LIGHT WITH 3-WAY SWITCH ACTIVATED
BY LH AND RH DOORS
CAB DOOR LATCHES WITH MANUAL DOOR
LOCKS
(1) 12 VOLT POWER SUPPLY IN DASH
BASIC HIGH BACK AIR SUSPENSION DRIVER
SEAT WITH MECHANICAL LUMBAR AND
INTEGRATED CUSHION EXTENSION
BASIC HIGH BACK NON SUSPENSION
PASSENGER SEAT
LH AND RH INTEGRAL DOOR PANEL ARMRESTS
VINYL WITH VINYL INSERT DRIVER SEAT
VINYL WITH VINYL INSERT PASSENGER SEAT
BLACK SEAT BELTS
ADJUSTABLE TILT AND TELESCOPING
STEERING COLUMN
4-SPOKE 18 INCH (450MM) STEERING WHEEL
DRIVER AND PASSENGER INTERIOR SUN
VISORS
NO ENTRY/ACCESS/STEP WIRING

Instruments & Controls

GRAY DRIVER INSTRUMENT PANEL
GRAY CENTER INSTRUMENT PANEL
BLACK GAUGE BEZELS
LOW AIR PRESSURE INDICATOR LIGHT AND
AUDIBLE ALARM
2 INCH PRIMARY AND SECONDARY AIR
PRESSURE GAUGES
INTAKE MOUNTED AIR RESTRICTION
INDICATOR WITHOUT GRADUATIONS
PRECO MODEL 360, CONSTANT 107 DB BACKUP
ALARM
ELECTRONIC CRUISE CONTROL WITH
SWITCHES IN LH SWITCH PANEL

Description

KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY

ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED

HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH

2 INCH ELECTRIC FUEL GAUGE

PROGRAMMABLE RPM CONTROL - ELECTRONIC ENGINE

ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE

2 INCH TRANSMISSION OIL TEMPERATURE GAUGE

ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY

ELECTRIC ENGINE OIL PRESSURE GAUGE

AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH AND USB AND AUXILIARY INPUTS, J1939

DASH MOUNTED RADIO

(2) RADIO SPEAKERS IN CAB

AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF

ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER

STANDARD VEHICLE SPEED SENSOR

ELECTRONIC 3000 RPM TACHOMETER

NO VEHICLE PERFORMANCE MONITOR

IGNITION SWITCH CONTROLLED ENGINE STOP

BW TRACTOR PROTECTION VALVE

TRAILER HAND CONTROL BRAKE VALVE

DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY

SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY

MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH

TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR

Description

SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE
 INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: N0006EA WHITE ELITE SS
 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT
 POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
 BUMPER PAINT: FP24812 ARGENT SILVER DUPONT FLEX
 STANDARD E COAT/UNDERCOATING

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

Secondary Factory Options

CORPORATE PDI CENTER IN-SERVICE ONLY

Raw Performance Data

CALC'D FRAME LENGTH - OVERALL : 286.02
 CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 112.55 in
 CALC'D SPACE AVAILABLE FOR DECKPLATE : 115.45 in

Dealer Installed Options

	Weight Front	Weight Rear
12 TO 14 YD DUMP BODY WITH CAB SHIELD ELECTRIC TARP AIR TAILGATE PER ATTACHED SPECS.	0	0
TOW PACK AND PINTLE HITCH BACKUP ALARM AND CAMERA	0	0



FLORIDA SHERIFFS CONTRACT
SPEC 15 FSA 18 VEH 16.0
LOU BACHRODT/SBL FREIGHTLINER
LOW BID ON THIS SPEC

Prepared by:
Drew Ellison
LOU BACHRODT FREIGHTLINER
2840 CENTER PORT CIRCLE
POMPANO BEACH, FL 33064
Phone: 407-886-6704

Total Dealer Installed Options 0 lbs 0 lbs

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

