



2840 Center Port Circle
Pompano, Bch, FL. 33064



Freightliner
SPRINTER



PURCHASER: KEY WEST CITY OF

DATE: 10/4/2018

ADDRESS:

PHONE:

CITY: KEY WEST FL

ATTN: RICHARD SARVER

BASE MODEL:	FLORIDA SHERIFFS CONTRACT SPEC 15 FSA18-VEH16 SPEC 15	PRICE:	\$57,750
OPTION #	DLR-64GVW 64000# GVW PACKAGE WITH ALLISON TRANS	PRICE:	\$32,750
OPTION #	456-006 DIFF LOCK BOTH REAR AXLES	PRICE:	\$1,290
OPTION #	DLR-4000 4000 GALLON WATER TANKER	PRICE:	\$72,500
OPTION #	STAINLESS STEEL TANK OPTION SEE ABOVE DLR-4000	PRICE:	\$19,700
OPTION #	AMBER STROBES SEE DLR-4000 ABOVE	PRICE:	\$1,200
OPTION #	SELF LOAD SYSTEM SEE ABOVE DLR-4000	PRICE:	\$2,300
OPTION #	TOOL BOX SEE ABOVE OPTIONS DLR-4000	PRICE:	\$980
OPTION #		PRICE:	
OPTION #	INCLUDES ALL OPTION IN FREIGHTLINER PRINTOUT..	PRICE:	
OPTION #		PRICE:	
OPTION #		PRICE:	
OPTION #		PRICE:	
OPTION #		PRICE:	
OPTION #	TOTAL PRICE	PRICE:	\$188,470

TOTAL PRICE: \$0.00

Budget Challenges?

Daimler Truck Financial offers special municipal financing programs to help fund the purchase of needed vehicles and other equipment.

***MTHLY PAYMENT: \$0.00**

- Monthly, annual, semi-annual or quarterly payment options
- Flexible repayment terms (tied to your budget)

*Actual rate, terms, down payment, and program eligibility will be determined by DTF credit team based upon credit worthiness and experience of customer.

KEY WEST CITY OF
4000 GALLON STAINLESS STEEL TANKER
QUOTATION

M2 112 CONVENTIONAL CHASSIS

SET BACK AXLE - TRUCK	20,000# FLAT LEAF FRONT SUSPENSION
CUM L9 370 HP @ 2000 RPM, 2100 GOV RPM, 1250 LB/FT @ 1400 RPM	112 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB
ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	5200MM (205 INCH) WHEELBASE
RT-46-160 46,000# R-SERIES TANDEM REAR AXLE	7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI
HENDRICKSON PRIMAAX EX 46,000# REAR AIR SUSPENSION	2450MM (96 INCH) REAR FRAME OVERHANG
DETROIT DA-F-20.0-5 20,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE	1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT

	TOTAL # OF UNITS (1)	PER UNIT	TOTAL
VEHICLE PRICE	\$	\$	
EXTENDED WARRANTY	\$	\$	
DEALER INSTALLED OPTIONS	\$	\$	
CUSTOMER PRICE BEFORE TAX	\$	\$	

TAXES AND FEES

FEDERAL EXCISE TAX (FET)	\$	\$	
TAXES AND FEES	\$	\$	
OTHER CHARGES	\$	0 \$	0

TRADE-IN

TRADE-IN ALLOWANCE	\$	(0) \$	(0)
---------------------------	----	--------	-----

BALANCE DUE	(LOCAL CURRENCY) \$	188,470 \$	188,470
--------------------	----------------------------	-------------------	----------------

COMMENTS: Projected delivery on ___ / ___ / ___ provided the order is received before ___ / ___ / ___.

APPROVAL: Please indicate your acceptance of this quotation by signing below: Customer:

X _____ Date: ___ / ___ / ___.

Daimler Truck Financial

Financing that works for you.

See your local dealer for a competitive quote from Daimler Truck Financial, or contact us at Information@dtffoffers.com.

Daimler Truck Financial offers a variety of finance, lease and insurance solutions to fit your business needs. For more information about our products and services, visit our website at www.daimler-truckfinancial.com.



2018/19 FLORIDA SHERIFFS
CONTRACT SPEC 15
LOU BACHRODT /SBL FREIGHTLINER
LOW BID ON THIS SPEC.

Prepared by:
Drew Ellison
LOU BACHRODT FREIGHTLINER
2840 CENTER PORT CIRCLE
POMPANO BEACH, FL 33064
Phone: 407-886-6704



SPECIFICATION PROPOSAL

Description
Price Level
M2 PRL-18M (EFF:04/17/18)
Data Version
SPECPRO21 DATA RELEASE VER 023
Vehicle Configuration
M2 112 CONVENTIONAL CHASSIS 2020 MODEL YEAR SPECIFIED SET BACK AXLE - TRUCK STRAIGHT TRUCK PROVISION LH PRIMARY STEERING LOCATION
General Service
TRUCK CONFIGURATION DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES) UTILITY/REPAIR/MAINTENANCE SERVICE GOVERNMENT BUSINESS SEGMENT DIRT/SAND/ROCK COMMODITY TERRAIN/DUTY: 10% (SOME) OF THE TIME, IN TRANSIT, IS SPENT ON NON-PAVED ROADS MAXIMUM 8% EXPECTED GRADE MAINTAINED GRAVEL OR CRUSHED ROCK - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE FREIGHTLINER LEVEL II WARRANTY EXPECTED FRONT AXLE(S) LOAD : 20000.0 lbs EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs EXPECTED PUSHER AXLE(S) LOAD : 0.0 lbs EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 66000.0 lbs

Description

Truck Service

END DUMP BODY
3-V DISTRIBUTING INC
EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE
FRAME "XX" INCHES : 32.0 in

Engine

CUM L9 370 HP @ 2000 RPM, 2100 GOV RPM,
1250 LB/FT @ 1400 RPM

Electronic Parameters

75 MPH ROAD SPEED LIMIT
CRUISE CONTROL SPEED LIMIT SAME AS ROAD
SPEED LIMIT
PTO MODE ENGINE RPM LIMIT - 1100 RPM
PTO MODE BRAKE OVERRIDE - SERVICE
BRAKE APPLIED
PTO RPM WITH CRUISE SET SWITCH - 700 RPM
PTO RPM WITH CRUISE RESUME SWITCH - 800
RPM
PTO MODE CANCEL VEHICLE SPEED - 5 MPH
PTO GOVERNOR RAMP RATE - 250 RPM PER
SECOND
PTO MINIMUM RPM - 700
REGEN INHIBIT SPEED THRESHOLD - 5 MPH

Engine Equipment

2016 ONBOARD DIAGNOSTICS/2010
EPA/CARB/FINAL GHG17 CONFIGURATION
NO 2008 CARB EMISSION CERTIFICATION
STANDARD OIL PAN
ENGINE MOUNTED OIL CHECK AND FILL
ONE PIECE VALVE COVER
SIDE OF HOOD AIR INTAKE WITH FIREWALL
MOUNTED DONALDSON AIR CLEANER
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD
ALTERNATOR WITH REMOTE BATTERY VOLT
SENSE
(3) DTNA GENUINE, FLOODED STARTING, MIN
3375CCA, 585RC, THREADED STUD BATTERIES
BATTERY BOX FRAME MOUNTED
STANDARD BATTERY JUMPERS

Description

SINGLE BATTERY BOX FRAME MOUNTED LH
SIDE BACK OF CAB
WIRE GROUND RETURN FOR BATTERY CABLES
WITH ADDITIONAL FRAME GROUND RETURN
NON-POLISHED BATTERY BOX COVER
CAB AUXILIARY POWER CABLE
CUMMINS TURBOCHARGED 18.7 CFM AIR
COMPRESSOR WITH INTERNAL SAFETY VALVE
STANDARD MECHANICAL AIR COMPRESSOR
GOVERNOR
AIR COMPRESSOR DISCHARGE LINE
ELECTRONIC ENGINE INTEGRAL SHUTDOWN
PROTECTION SYSTEM
CUMMINS EXHAUST BRAKE INTEGRAL WITH
VARIABLE GEOMETRY TURBO WITH ON/OFF
DASH SWITCH
RH OUTBOARD UNDER STEP MOUNTED
HORIZONTAL AFTERTREATMENT SYSTEM
ASSEMBLY WITH RH B-PILLAR MOUNTED
VERTICAL TAILPIPE
ENGINE AFTERTREATMENT DEVICE,
AUTOMATIC OVER THE ROAD REGENERATION
AND DASH MOUNTED REGENERATION
REQUEST SWITCH
11 FOOT 06 INCH (138 INCH+0/-5.9 INCH)
EXHAUST SYSTEM HEIGHT
RH CURVED VERTICAL TAILPIPE B-PILLAR
MOUNTED ROUTED FROM STEP
6 GALLON DIESEL EXHAUST FLUID TANK
100 PERCENT DIESEL EXHAUST FLUID FILL
LH MEDIUM DUTY STANDARD DIESEL EXHAUST
FLUID TANK LOCATION
STANDARD DIESEL EXHAUST FLUID PUMP
MOUNTING
STANDARD DIESEL EXHAUST FLUID TANK CAP
ALUMINUM AFTERTREATMENT
DEVICE/MUFFLER/TAILPIPE SHIELD(S)
HORTON DRIVEMASTER ADVANTAGE ON/OFF
FAN DRIVE
AUTOMATIC FAN CONTROL WITHOUT DASH
SWITCH, NON ENGINE MOUNTED
CUMMINS SPIN ON FUEL FILTER
COMBINATION FULL FLOW/BYPASS OIL FILTER

Description

1300 SQUARE INCH ALUMINUM RADIATOR
ANTIFREEZE TO -34F, ETHYLENE GLYCOL PRE-
CHARGED SCA HEAVY DUTY COOLANT
GATES BLUE STRIPE COOLANT HOSES OR
EQUIVALENT
CONSTANT TENSION HOSE CLAMPS FOR
COOLANT HOSES
ALUMINUM FLYWHEEL HOUSING
ELECTRIC GRID AIR INTAKE WARMER
DELCO 12V 38MT HD STARTER WITH
INTEGRATED MAGNETIC SWITCH

Transmission

ALLISON 3000 RDS AUTOMATIC TRANSMISSION
WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -
AVAILABLE ON 3000/4000 PRODUCT FAMILIES
WITH VOCATIONAL MODELS RDS, HS, MH AND
TRV
ALLISON VOCATIONAL RATING FOR ON/OFF
HIGHWAY APPLICATIONS AVAILABLE WITH ALL
PRODUCT FAMILIES
PRIMARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
SECONDARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
PRIMARY SHIFT SCHEDULE RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SCHEDULE
RECOMMENDED BY DTNA AND ALLISON, THIS
DEFINED BY ENGINE AND VOCATIONAL USAGE
PRIMARY SHIFT SPEED RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SPEED RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
ENGINE BRAKE RANGE PRESELECT
RECOMMENDED BY DTNA AND ALLISON, THIS
DEFINED BY ENGINE AND VOCATIONAL USAGE

Description

ENGINE BRAKE RANGE ALTERNATE
PRESELECT RECOMMENDED BY DTNA AND
ALLISON, THIS DEFINED BY ENGINE AND
VOCATIONAL USAGE

LOAD BASED SHIFT SCHEDULE AND VEHICLE
ACCELERATION CONTROL RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED
VOCATIONAL USAGE

NEUTRAL AT STOP - DISABLED, FUELSENSE -
DISABLED

DRIVER SWITCH INPUT - DEFAULT - NO
SWITCHES

MAGNETIC PLUGS, ENGINE DRAIN,
TRANSMISSION DRAIN, AXLE(S) FILL AND
DRAIN

PUSH BUTTON ELECTRONIC SHIFT CONTROL,
DASH MOUNTED

TRANSMISSION PROGNOSTICS - ENABLED 2013

WATER TO OIL TRANSMISSION COOLER, IN
RADIATOR END TANK

TRANSMISSION OIL CHECK AND FILL WITH
ELECTRONIC OIL LEVEL CHECK

SYNTHETIC TRANSMISSION FLUID (TES-295
COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-20.0-5 20,000# FL1 71.0 KPI/3.74
DROP SINGLE FRONT AXLE

MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT
BRAKES, DOUBLE ANCHOR, FABRICATED
SHOES

NON-ASBESTOS FRONT BRAKE LINING

CONMET CAST IRON FRONT BRAKE DRUMS

FRONT BRAKE DUST SHIELDS

FRONT OIL SEALS

VENTED FRONT HUB CAPS WITH WINDOW,
CENTER AND SIDE PLUGS - OIL

STANDARD SPINDLE NUTS FOR ALL AXLES

MERITOR AUTOMATIC FRONT SLACK
ADJUSTERS

TRW THP-60 POWER STEERING WITH RCH45
AUXILIARY GEAR

POWER STEERING PUMP

4 QUART POWER STEERING RESERVOIR

Description

OIL/AIR POWER STEERING COOLER
SYNTHETIC 75W-90 FRONT AXLE LUBE

Front Suspension

20,000# FLAT LEAF FRONT SUSPENSION
GRAPHITE BRONZE BUSHINGS WITH SEALS -
FRONT SUSPENSION
FRONT SHOCK ABSORBERS

Rear Axle and Equipment

RT-46-160 46,000# R-SERIES TANDEM REAR
AXLE
5.63 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH STANDARD
AXLE HOUSING
MXL 17T MERITOR EXTENDED LUBE MAIN
DRIVELINE WITH HALF ROUND YOKES
MXL 17T MERITOR EXTENDED LUBE INTERAXLE
DRIVELINE WITH HALF ROUND YOKES
DRIVER CONTROLLED TRACTION
DIFFERENTIAL - BOTH TANDEM REAR AXLES
(1) INTERAXLE LOCK VALVE, (1) DRIVER
CONTROLLED DIFFERENTIAL LOCK FORWARD-
REAR AND REAR-REAR AXLE VALVE
BLINKING LAMP WITH EACH INTERAXLE LOCK
SWITCH, INTERAXLE UNLOCK DEFAULT WITH
IGNITION OFF
BLINKING LAMP WITH EACH MODE SWITCH,
DIFFERENTIAL UNLOCK WITH IGNITION OFF,
ACTIVE <5 MPH
MERITOR 16.5X8.62 Q+ CAST SPIDER CAM
REAR BRAKES, DOUBLE ANCHOR, FABRICATED
SHOES
NON-ASBESTOS REAR BRAKE LINING
ASPHALT SPREADER CLEARANCE REAR
BRAKE GEOMETRY
CONMET CAST IRON REAR BRAKE DRUMS
REAR OIL SEALS
BENDIX EVERSURE LONGSTROKE HEAVY DUTY
30/36 2-DRIVE AXLES SPRING PARKING
CHAMBERS
HALDEX AUTOMATIC REAR SLACK ADJUSTERS
SYNTHETIC 75W-90 REAR AXLE LUBE

Description

Rear Suspension

HENDRICKSON PRIMAAX EX 46,000# REAR AIR
SUSPENSION
HENDRICKSON PRIMAAX 10.00" RIDE HEIGHT
AXLE CLAMPING GROUP
54 INCH AXLE SPACING
IGNITION CONTROLLED ELECTRIC DUMP
SWITCH FOR AIR SUSPENSION WITHOUT
GAUGE
REAR AIR SUSPENSION DUMP VALVE AUTOFILL
WITH IGNITION OFF OR >5 MPH WITH
INDICATOR LIGHT
SINGLE AIR REAR SUSPENSION LEVELING
VALVE
TRANSVERSE CONTROL RODS

Brake System

AIR BRAKE PACKAGE
WABCO 4S/4M ABS
REINFORCED NYLON, FABRIC BRAID AND WIRE
BRAID CHASSIS AIR LINES
FIBER BRAID PARKING BRAKE HOSE
STANDARD BRAKE SYSTEM VALVES
STANDARD AIR SYSTEM PRESSURE
PROTECTION SYSTEM
STD U.S. FRONT BRAKE VALVE
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE,
NO REAR PROPORTIONING VALVE
WABCO SYSTEM SAVER HP WITH INTEGRAL
AIR GOVERNOR AND HEATER
AIR DRYER FRAME MOUNTED
STEEL AIR BRAKE RESERVOIRS
CLEAR FRAME RAILS FROM BACK OF CAB TO
FRONT REAR SUSPENSION BRACKET, BOTH
RAILS OUTBOARD
BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER
ON ALL TANK(S)

Trailer Connections

PRIMARY CONNECTOR/RECEPTACLE WIRED
FOR SEPARATE STOP/TURN, ABS CENTER PIN
POWERED THROUGH IGNITION

Description

SAE J560 7-WAY PRIMARY TRAILER CABLE
RECEPTACLE MOUNTED END OF FRAME
UPGRADED CHASSIS MULTIPLEXING UNIT
UPGRADED BULKHEAD MULTIPLEXING UNIT

Wheelbase & Frame

5200MM (205 INCH) WHEELBASE
7/16X3-9/16X11-1/8 INCH STEEL FRAME
(11.11MMX282.6MM/0.437X11.13 INCH) 120KSI
1/4 INCH (6.35MM) C-CHANNEL INNER FRAME
REINFORCEMENT
2450MM (96 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 91 INCH TO 100
INCH
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :
139.45 in
CALCULATED EFFECTIVE BACK OF CAB TO
REAR SUSPENSION C/L (CA) : 136.45 in
CALC'D FRAME LENGTH - OVERALL : 331.32
CALC'D SPACE AVAILABLE FOR DECKPLATE :
139.45 in
CALCULATED FRAME SPACE LH SIDE : 47.02 in
CALCULATED FRAME SPACE RH SIDE : 78.97 in
SQUARE END OF FRAME
FRONT CLOSING CROSSMEMBER
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD CROSSMEMBER BACK OF
TRANSMISSION
STANDARD MIDSHIP #1 CROSSMEMBER(S)
STANDARD REAR MOST CROSSMEMBER
HEAVY DUTY SUSPENSION CROSSMEMBER

Chassis Equipment

THREE-PIECE 14 INCH PAINTED STEEL
BUMPER WITH COLLAPSIBLE ENDS
REMOVABLE FRONT TOW HOOKS STORED ON
THE CHASSIS FRAME
BUMPER MOUNTING FOR SINGLE LICENSE
PLATE
FENDER AND FRONT OF HOOD MOUNTED
FRONT MUDFLAPS

Description
GRADE 8 THREADED HEX HEADED FRAME FASTENERS
Fuel Tanks
80 GALLON/302 LITER ALUMINUM FUEL TANK - LH 25 INCH DIAMETER FUEL TANK(S) PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS FUEL TANK(S) FORWARD PLAIN STEP FINISH FUEL TANK CAP(S) DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR EQUIFLO INBOARD FUEL SYSTEM NO NATURAL GAS VEHICLE FUEL TANK VENT LINE/STACK HIGH TEMPERATURE REINFORCED NYLON FUEL LINE
Tires
BF GOODRICH CROSS CONTROL S 425/65R22.5 20 PLY RADIAL FRONT TIRES BF GOODRICH CROSS CONTROL D 11R22.5 16 PLY RADIAL REAR TIRES
Hubs
CONMET PRESET PLUS PREMIUM IRON FRONT HUBS CONMET PRESET PLUS PREMIUM IRON REAR HUBS
Wheels
ACCURIDE 29374A 22.5X12.25 10-HUB PILOT 4.75 INSET 10-HAND ALUMINUM DISC FRONT WHEELS ACCURIDE 42644 ACCU-LITE 22.5X8.25 10-HP ALUMINUM DISC REAR WHEELS FRONT WHEEL MOUNTING NUTS REAR WHEEL MOUNTING NUTS
Cab Exterior
112 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB



Description

AIR CAB MOUNTING
NONREMOVABLE BUGSCREEN MOUNTED
BEHIND GRILLE
BOLT-ON MOLDED FLEXIBLE FENDER
EXTENSIONS
LH AND RH GRAB HANDLES
PAINTED PLASTIC GRILLE
ARGENT SILVER HOOD MOUNTED AIR INTAKE
GRILLE
FIBERGLASS HOOD
SINGLE 14 INCH ROUND HADLEY AIR HORN
UNDER LH DECK
SINGLE ELECTRIC HORN
SINGLE HORN SHIELD
DOOR LOCKS AND IGNITION SWITCH KEYED
THE SAME WITH (4) KEYS
REAR LICENSE PLATE MOUNT END OF FRAME
INTEGRAL HEADLIGHT/MARKER ASSEMBLY
LED AERODYNAMIC MARKER LIGHTS
DAYTIME RUNNING LIGHTS
FREIGHTLINER LED FLANGE MOUNTED
STOP/TAIL/TURN LIGHTS WITH SEPARATE
INCANDESCENT BACKUP LIGHTS
STANDARD FRONT TURN SIGNAL LAMPS
DUAL WEST COAST BRIGHT FINISH HEATED
MIRRORS WITH LH AND RH REMOTE
DOOR MOUNTED MIRRORS
102 INCH EQUIPMENT WIDTH
LH AND RH 8 INCH BRIGHT FINISH CONVEX
MIRRORS MOUNTED UNDER PRIMARY
MIRRORS
RH DOWN VIEW MIRROR
STANDARD SIDE/REAR REFLECTORS
63X14 INCH TINTED REAR WINDOW
TINTED DOOR GLASS LH AND RH WITH TINTED
NON-OPERATING WING WINDOWS
RH AND LH ELECTRIC POWERED WINDOWS,
PASSENGER SWITCHES ON DOOR(S)
TINTED WINDSHIELD

Description

2 GALLON WINDSHIELD WASHER RESERVOIR
WITHOUT FLUID LEVEL INDICATOR, FRAME
MOUNTED

Cab Interior

OPAL GRAY VINYL INTERIOR
MOLDED PLASTIC DOOR PANEL
MOLDED PLASTIC DOOR PANEL
BLACK MATS WITH SINGLE INSULATION
NO DASH MOUNTED ASH TRAYS AND LIGHTER
FORWARD ROOF MOUNTED CONSOLE WITH
UPPER STORAGE COMPARTMENTS WITHOUT
NETTING
IN DASH STORAGE BIN
(2) CUP HOLDERS LH AND RH DASH
GRAY/CHARCOAL FLAT DASH
SMART SWITCH EXPANSION MODULE
HEATER, DEFROSTER AND AIR CONDITIONER
STANDARD HVAC DUCTING
MAIN HVAC CONTROLS WITH RECIRCULATION
SWITCH
STANDARD HEATER PLUMBING
DENSO HEAVY DUTY AIR CONDITIONER
COMPRESSOR
BINARY CONTROL, R-134A
STANDARD INSULATION
SOLID-STATE CIRCUIT PROTECTION AND
FUSES
12V NEGATIVE GROUND ELECTRICAL SYSTEM
DOME LIGHT WITH 3-WAY SWITCH ACTIVATED
BY LH AND RH DOORS
LH AND RH ELECTRIC DOOR LOCKS
(1) 12 VOLT POWER SUPPLY IN DASH
BASIC HIGH BACK AIR SUSPENSION DRIVER
SEAT WITH MECHANICAL LUMBAR AND
INTEGRATED CUSHION EXTENSION
BASIC HIGH BACK AIR SUSPENSION
PASSENGER SEAT WITH MECHANICAL LUMBAR
AND INTEGRATED CUSHION EXTENSION
LH AND RH INTEGRAL DOOR PANEL ARMRESTS
VINYL WITH VINYL INSERT DRIVER SEAT

Description

VINYL WITH VINYL INSERT PASSENGER SEAT
BLACK SEAT BELTS
ADJUSTABLE TILT AND TELESCOPING
STEERING COLUMN
4-SPOKE 18 INCH (450MM) STEERING WHEEL
DRIVER AND PASSENGER INTERIOR SUN
VISORS

Instruments & Controls

GRAY DRIVER INSTRUMENT PANEL
GRAY CENTER INSTRUMENT PANEL
BLACK GAUGE BEZELS
LOW AIR PRESSURE INDICATOR LIGHT AND
AUDIBLE ALARM
2 INCH PRIMARY AND SECONDARY AIR
PRESSURE GAUGES
INTAKE MOUNTED AIR RESTRICTION
INDICATOR WITHOUT GRADUATIONS
97 DB BACKUP ALARM
ELECTRONIC CRUISE CONTROL WITH
SWITCHES IN LH SWITCH PANEL
KEY OPERATED IGNITION SWITCH AND
INTEGRAL START POSITION; 4 POSITION
OFF/RUN/START/ACCESSORY
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28
LED WARNING LAMPS AND DATA LINKED
HEAVY DUTY ONBOARD DIAGNOSTICS
INTERFACE CONNECTOR LOCATED BELOW LH
DASH
2 INCH ELECTRIC FUEL GAUGE
PROGRAMMABLE RPM CONTROL -
ELECTRONIC ENGINE
ELECTRICAL ENGINE COOLANT TEMPERATURE
GAUGE
2 INCH TRANSMISSION OIL TEMPERATURE
GAUGE
ENGINE AND TRIP HOUR METERS INTEGRAL
WITHIN DRIVER DISPLAY
ELECTRIC ENGINE OIL PRESSURE GAUGE
AM/FM/WB WORLD TUNER RADIO WITH
BLUETOOTH AND USB AND AUXILIARY INPUTS,
J1939
DASH MOUNTED RADIO

Description

(2) RADIO SPEAKERS IN CAB
AM/FM ANTENNA MOUNTED ON FORWARD LH
ROOF
ELECTRONIC MPH SPEEDOMETER WITH
SECONDARY KPH SCALE, WITHOUT
ODOMETER
STANDARD VEHICLE SPEED SENSOR
ELECTRONIC 3000 RPM TACHOMETER
NO VEHICLE PERFORMANCE MONITOR
IGNITION SWITCH CONTROLLED ENGINE STOP
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH
DRIVER DISPLAY
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR
WITH DELAY
MARKER LIGHT SWITCH INTEGRAL WITH
HEADLIGHT SWITCH
ONE VALVE PARKING BRAKE SYSTEM WITH
WARNING INDICATOR
SELF CANCELING TURN SIGNAL SWITCH WITH
DIMMER, WASHER/WIPER AND HAZARD IN
HANDLE
INTEGRAL ELECTRONIC TURN SIGNAL
FLASHER WITH HAZARD LAMPS OVERRIDING
STOP LAMPS

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: N0006EA WHITE ELITE SS
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS
PAINT
BUMPER PAINT: FP24812 ARGENT SILVER
DUPONT FLEX
STANDARD E COAT/UNDERCOATING

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES
CABS AND GLIDER KITS

Secondary Factory Options

CORPORATE PDI CENTER IN-SERVICE ONLY
DLR/CUST ADVISED&ACCEPTS POTENTIAL
INTERFERENCE BTWN FRONT TIRE & WASHER
BOTTLE

Extended Warranty

TOWING: 1 YEAR/UNLIMITED MILES/KM EXTENDED TOWING
COVERAGE \$550 CAP FEX APPLIES

Dealer Installed Options

	Weight Front	Weight Rear
4000 GALLON STEEL WATER TANKER PER ATTACHED SPECS SS TANK.	0	0
BACKUP CAMERA AND ALARM	0	0
Total Dealer Installed Options	0 lbs	0 lbs