

# ONE PIERCE CUSTOM VELOCITY PUC PUMPER

For

City of Key West, Florida

**SEPT. 1, 2015**

## **SINGLE SOURCE MANUFACTURER**

Pierce Manufacturing, Inc. provides an integrated approach to the design and manufacture of our products that delivers superior apparatus and a dedicated support team. From our facilities, the chassis, cab weldment, cab, pumphouse (including the sheet metal enclosure, valve controls, piping and operators panel) and body will be entirely designed, tested, and hand assembled to the customer's exact specifications. The electrical system either hardwired or multiplexed, will be both designed and integrated by Pierce Manufacturing. The warranties relative to these major components (excluding component warranties such as engine, transmission, axles, pump, etc.) will be provided by Pierce as a single source manufacturer. Pierce's single source solution adds value by providing a fully engineered product that offers durability, reliability, maintainability, performance, and a high level of quality.

Your apparatus will be manufactured in Appleton, Wisconsin.

## **SPECIAL INSTRUCTIONS**

The apparatus being proposed will be designed and built to match the Job 26500. However, some variation may be necessary due to changes in our manufacturing processes or our product offering. Revisions in NFPA guidelines and/or other regulations may also affect our ability to match the previous unit.

## **NFPA 2009 STANDARDS**

This unit will comply with the NFPA standards effective January 1, 2009, except for fire department directed exceptions. These exceptions will be set forth in the Statement of Exceptions.

Certification of slip resistance of all stepping, standing and walking surfaces will be supplied with delivery of the apparatus.

A plate that is highly visible to the driver while seated will be provided. This plate will show the overall height, length, and gross vehicle weight rating.

The manufacturer will have programs in place for training, proficiency testing and performance for any staff involved with certifications.

An official of the company will designate, in writing, who is qualified to witness and certify test results.

### **NFPA COMPLIANCY**

Apparatus proposed by the bidder will meet the applicable requirements of the National Fire Protection Association (NFPA) as stated in current edition at time of contract execution. Fire department's specifications that differ from NFPA specifications will be indicated in the proposal as "non-NFPA".

### **VEHICLE INSPECTION PROGRAM CERTIFICATION**

To assure the vehicle is built to current NFPA standards, the apparatus, in its entirety, will be third-party, audit-certified through Underwriters Laboratory (UL) that it is built and complies to all applicable standards in the current edition of NFPA 1901. The certification will include: all design, production, operational, and performance testing of not only the apparatus, but those components that are installed on the apparatus.

A placard will be affixed in the driver's side area stating the third party agency, the date, the standard and the certificate number of the whole vehicle audit.

### **PUMP TEST**

Underwriters Laboratory (UL) will test, approved, and certify the pump. The test results and the pump manufacturer's certification of hydrostatic test; the engine manufacturer's certified brake horsepower curve; and the pump manufacturer's record of pump construction details will be forwarded to the Fire Department.

### **GENERATOR TEST**

If the unit has a generator, Underwriters Laboratory (UL) will test, approved, and certify the generator. The test results will be provided to the Fire Department at the time of delivery.

### **BREATHING AIR TEST**

If the unit has breathing air, Pierce Manufacturing will draw an air sample from the air system and have the sample certified that the air quality meets the requirements of NFPA 1989, *Standard on Breathing Air Quality for Fire and Emergency Services Respiratory Protection*.

### **BID BOND**

A bid bond as security for the bid in the form of a 10% bid bond will be provided with the proposal. This bid bond will be issued by a Surety Company who is listed on the U.S. Treasury Departments list of acceptable sureties as published in Department Circular 570. The bid bond will be issued by an authorized representative of the Surety Company and will be accompanied by a certified power of attorney dated on or before the date of bid. The bid bond will include language which assures that the bidder/principal will give a bond or bonds, as may be specified in the bidding or contract documents, with good and sufficient surety for the faithful performance of the contract, including the Basic One (1) Year Limited Warranty, and for the prompt payment of labor and material furnished in the prosecution of the contract.

Notwithstanding any document or assertion to the contrary, any surety bond related to the sale of a vehicle will apply only to the Basic One (1) Year Limited Warranty for such vehicle. Any surety bond

related to the sale of a vehicle will not apply to any other warranties that are included within this bid (OEM or otherwise) or to the warranties (if any) of any third party of any part, component, attachment or accessory that is incorporated into or attached to the vehicle. In the event of any contradiction or inconsistency between this provision and any other document or assertion, this provision will prevail.

### **PERFORMANCE BOND**

Notwithstanding any document or assertion to the contrary, any surety bond related to the sale of a vehicle will apply only to the Basic One (1) Year Limited Warranty for such vehicle. Any surety bond related to the sale of a vehicle will not apply to any other warranties that are included within this bid (OEM or otherwise) or to the warranties (if any) of any third party of any part, component, attachment or accessory that is incorporated into or attached to the vehicle. In the event of any contradiction or inconsistency between this provision and any other document or assertion, this provision will prevail.

### **APPROVAL DRAWING**

A drawing of the proposed apparatus will be prepared and provided to the purchaser for approval before construction begins. The Pierce sales representative will also be provided with a copy of the same drawing. The finalized and approved drawing will become part of the contract documents. This drawing will indicate the chassis make and model, location of the lights, siren, horns, compartments, major components, etc.

A "revised" approval drawing of the apparatus will be prepared and submitted by Pierce to the purchaser showing any changes made to the approval drawing.

### **ELECTRICAL WIRING DIAGRAMS**

Two (2) electrical wiring diagrams, prepared for the model of chassis and body, will be provided.

### **VELOCITY™ CHASSIS**

The Pierce Velocity is the custom chassis developed exclusively for the fire service. Chassis provided will be a new, tilt-type custom fire apparatus. The chassis will be manufactured in the apparatus body builder's facility eliminating any split responsibility. The chassis will be designed and manufactured for heavy-duty service, with adequate strength and capacity for the intended load to be sustained and the type of service required. The chassis will be the manufacturer's first line tilt cab.

### **MAXIMUM OVERALL HEIGHT**

The maximum overall height of the apparatus will be 132".

### **WHEELBASE**

The wheelbase of the vehicle will be 178.00 + wider crosslay +2".

### **GVW RATING**

The gross vehicle weight rating will be 53,800.

## **FRAME**

The chassis frame will be built with two (2) steel channels bolted to five (5) cross members or more, depending on other options of the apparatus. The side rails will have a 13.38" tall web over the front and mid sections of the chassis, with a continuous smooth taper to 10.75" over the rear axle. Each rail will have a section modulus of 25.992 cubic inches and a resisting bending moment (rbm) of 3,119,040 in-lb over the critical regions of the frame assembly, with a section modulus of 18.96 cubic inches with an rbm of 2,275,200 in-lb over the rear axle. The frame rails will be constructed of 120,000 psi yield strength heat-treated 0.38" thick steel with 3.50" wide flanges.

## **FRONT NON DRIVE AXLE**

The Oshkosh TAK-4® front axle will be of the independent suspension design with a ground rating of 19,500 lb.

Upper and lower control arms will be used on each side of the axle. Upper control arm castings will be made of 100,000-psi yield strength 8630 steel and the lower control arm casting will be made of 55,000-psi yield ductile iron.

The center cross members and side plates will be constructed out of 80,000-psi yield strength steel.

Each control arm will be mounted to the center section using elastomer bushings. These rubber bushings will rotate on low friction plain bearings and be lubricated for life. Each bushing will also have a flange end to absorb longitudinal impact loads, reducing noise and vibrations.

There will be nine (9) grease fittings supplied, one (1) on each control arm pivot and one (1) on the steering gear extension.

The upper control arm will be shorter than the lower arm so that wheel end geometry provides positive camber when deflected below rated load and negative camber above rated load.

Camber at load will be zero degrees for optimum tire life.

The ball joint bearing will be of low friction design and be maintenance free.

Toe links that are adjustable for alignment of the wheel to the center of the chassis will be provided.

The wheel ends must have little to no bump steer when the chassis encounters a hole or obstacle.

The steering linkage will provide proper steering angles for the inside and outside wheel, based on the vehicle wheelbase.

The axle will have a third party certified turning angle of 45 degrees. Front discharge, front suction, or aluminum wheels will not infringe on this cramp angle.

## **FRONT SUSPENSION**

Front Oshkosh TAK-4™ independent suspension will be provided with a minimum ground rating of 19,500 lb.

The independent suspension system will be designed to provide maximum ride comfort. The design will allow the vehicle to travel at highway speeds over improved road surfaces and at moderate speeds over rough terrain with minimal transfer of road shock and vibration to the vehicle's crew compartment.

Each wheel will have torsion bar type spring. In addition, each front wheel end will also have energy absorbing jounce bumpers to prevent bottoming of the suspension.

The suspension design will be such that there is at least 10.00" of total wheel travel and a minimum of 3.75" before suspension bottoms.

The torsion bar anchor lock system allows for simple lean adjustments, without the use of shims. One can adjust for a lean within 15 minutes per side. Anchor adjustment design is such that it allows for ride height adjustment on each side.

The independent suspension was put through a durability test that simulated 140,000 miles of inner city driving.

## **FRONT SHOCK ABSORBERS**

KONI heavy-duty telescoping shock absorbers will be provided on the front suspension.

## **FRONT OIL SEALS**

Oil seals with viewing window will be provided on the front axle.

## **FRONT TIRES**

The front tires will be Michelin 385/65R22.50 radials, load range L, XFE wide base tread, rated for 19,840 lb maximum axle load and 65 mph maximum speed.

The tires will be mounted on Alcoa 22.50" x 12.25" polished aluminum disc type wheels with a ten (10)stud, 11.25" bolt circle.

## **REAR AXLE**

The rear axle will be a Meritor™, Model RS-25-160, with a capacity of 27,000 lb.

## **TOP SPEED OF VEHICLE**

A rear axle ratio will be furnished to allow the vehicle to reach a top speed of 60 mph.

## **REAR SUSPENSION**

The rear suspension will be Standens, semi-elliptical, 3.00" wide x 53.00" long, 12-leaf pack with a ground rating of 27,000 lbs. The spring hangers will be castings.

The two (2) top leaves will wrap the forward spring hanger pin, and the rear of the spring will be a slipper style end that will ride in a rear slipper hanger. To reduce bending stress due to acceleration and braking, the front eye will be a berlin eye that will place the front spring pin in the horizontal plane within the main leaf.

A steel encased rubber bushing will be used in the spring eye. The steel encased rubber bushing will be maintenance free and require no lubrication.

### **REAR OIL SEALS**

Oil seals will be provided on the rear axle.

### **REAR TIRES**

Rear tires will be four (4) Michelin 12R22.50 radials, 16 ply "all position" XZE\* tread, rated for 27,120 lb maximum axle load and 75 mph maximum speed.

The tires will be mounted on Alcoa 22.50" x 8.25" polished aluminum disc wheels with a ten (10) stud 11.25" bolt circle.

### **TIRE BALANCE**

All tires will be balanced with Counteract balancing beads. The beads will be inserted into the tire and eliminate the need for wheel weights.

### **TIRE PRESSURE MANAGEMENT**

There will be a VECSAFE LED tire alert pressure management system provided that will monitor each tire's pressure. A chrome plated brass sensor will be provided on the valve stem of each tire for a total of six (6) tires.

The sensor will calibrate to the tire pressure when installed on the valve stem for pressures between 20 and 120 psi. The sensor will activate an integral battery operated LED when the pressure of that tire drops 8 psi.

Removing the cap from the sensor will indicate the functionality of the sensor and battery. If the sensor and battery are in working condition, the LED will immediately start blinking.

### **FRONT HUB COVERS**

Stainless steel hub covers will be provided on the front axle. An oil level viewing window will be provided.

### **REAR HUB COVERS**

A pair of stainless steel high hat hub covers will be provided on rear axle hubs.

### **MUD FLAPS**

Mud flaps with a Pierce logo will be installed behind the front and rear wheels.

## **WHEEL CHOCKS**

There will be one (1) pair of folding Ziamatic, Model SAC-44-E, aluminum alloy, Quick-Choc wheel blocks, with easy-grip handle provided.

## **WHEEL CHOCK BRACKETS**

There will be one (1) pair of Zico, Model SQCH-44-H, horizontal mounting wheel chock brackets provided for the Ziamatic, Model SAC-44-E, folding wheel chocks. The brackets will be made of aluminum and consist of a quick release spring loaded rod to hold the wheel chocks in place. The brackets will be mounted below the left side rear compartment.

## **ANTI-LOCK BRAKE SYSTEM**

The vehicle will be equipped with a Meritor WABCO 4S4M, anti-lock braking system. The ABS will provide a 4-channel anti-lock braking control on both the front and rear wheels. A digitally controlled system that utilizes microprocessor technology will control the anti-lock braking system. Each wheel will be monitored by the system. When any particular wheel begins to lockup, a signal will be sent to the control unit. This control unit then will reduce the braking of that wheel for a fraction of a second and then reapply the brake. This anti-lock brake system will eliminate the lockup of any wheel thus helping to prevent the apparatus from skidding out of control.

## **BRAKES**

The service brake system will be full air type.

The front brakes will be Knorr/Bendix disc type with a 17.00" ventilated rotor for improved stopping distance.

The brake system will be certified, third party inspected, for improved stopping distance.

The rear brakes will be Meritor™ 16.50" x 7.00" cam operated with automatic slack adjusters. Dust shields will be provided.

## **BRAKE SYSTEM AIR COMPRESSOR**

The air compressor will be a Cummins/WABCO with 18.7 cubic feet per minute output.

## **BRAKE SYSTEM**

The brake system will include:

- Bendix® dual brake treadle valve with vinyl covered foot surface
- Heated automatic moisture ejector on air dryer
- Total air system capacity of 4,362 cubic inches
- Two (2) air pressure gauges with a red warning light and an audible alarm, that activates when air pressure falls below 60 psi
- Spring set parking brake system
- Parking brake operated by a push-pull style control valve

- A parking "brake on" indicator light on instrument panel
- Park brake relay/inversion and anti-compounding valve, in conjunction with a double check valve system, with an automatic spring brake application at 40 psi
- A pressure protection valve to prevent all air operated accessories from drawing air from the air system when the system pressure drops below 80 psi (550 kPa)

The air tank will be primed and painted to meet a minimum 750 hour salt spray test.

To reduce the effects of corrosion, the air tank will be mounted with stainless steel brackets.

**BRAKE SYSTEM AIR DRYER**

The air dryer will be WABCO System Saver 1200 with spin-on coalescing filter cartridge and 100 watt heater.

**BRAKE LINES**

Color-coded nylon brake lines will be provided. The lines will be wrapped in a heat protective loom in the chassis areas that are subject to excessive heat.

**AIR INLET**

One (1) air inlet with male coupling will be provided. It will allow station air to be supplied to the apparatus brake system through a shoreline hose. The inlet will be located in the driver side lower step well of cab. A check valve will be provided to prevent reverse flow of air. The inlet will discharge into the "wet" tank of the brake system. A mating female coupling will also be provided with the loose equipment.

**AIR OUTLET**

One (1) air outlet will be installed with a female coupling and shut off valve, located on the driver side pump panel. This system will tie into the "wet" tank of the brake system and include an 85-psi pressure protection valve in the outlet line to prevent the brake system from losing all air.

Female coupling and male fitting will be .25" thread.

A mating male fitting will be provided with the loose equipment.

**AIR HOSE**

There will be one (1) 50' length(s) of air hose furnished with fittings.

An air chuck will be provided with the air hose. The air chuck will fit the valve stems that are provided on the tires.

**ENGINE**

The chassis will be powered by an electronically controlled engine as described below:

Make:	Cummins
Model:	ISL9



Power:	450 hp at 2100 rpm
Torque:	1250 lb-ft at 1400 rpm
Governed Speed:	2200 rpm
Emissions Level:	EPA 2016
Fuel:	Diesel
Cylinders:	Six (6)
Displacement:	543 cubic inches (8.9L)
Starter:	Delco 39MT™
Fuel Filters:	Spin-on style primary filter with water separator and water-in-fuel sensor. Secondary spin-on style filter.

The engine will include On-board diagnostics (OBD), which provides self diagnostic and reporting. The system will give the owner or repair technician access to state of health information for various vehicle sub systems. The system will monitor vehicle systems, engine and after treatment. The system will illuminate a malfunction indicator light on the dash console if a problem is detected.

**REPTO DRIVE**

A rear engine power take off will be provided to drive the water pump. A vibration dampener will be provided between the REPTO and water pump. Transmission PTO's used to drive the water pump will not be allowed due to their lower torque ratings. The rear engine power take off will be the same as used extensively throughout the construction industry. Rear engine PTO's allow for continuous 200 hp and 435 lb-ft torque ratings needed for large pump applications. The rear engine power take off will have the same warranty as the engine provided by the engine manufacturer.

**HIGH IDLE**

A high idle switch will be provided, inside the cab, on the instrument panel, that will automatically maintain a preset engine rpm. A switch will be installed, at the cab instrument panel, for activation/deactivation.

The high idle will be operational only when the parking brake is on and the truck transmission is in neutral. A green indicator light will be provided, adjacent to the switch. The light will illuminate when the above conditions are met. The light will be labeled "OK to Engage High Idle."

**ENGINE BRAKE**

A Jacobs® engine brake is to be installed with the controls located on the instrument panel within easy reach of the driver.

The driver will be able to turn the engine brake system on/off and have a high, medium and low setting.

The engine brake will activate when the system is on and the throttle is released.

The high setting of the brake application will activate and work simultaneously with the variable geometry turbo (VGT) provided on the engine.

The engine brake will be installed in such a manner that when the engine brake is slowing the vehicle the brake lights are activated.

The ABS system will automatically disengage the auxiliary braking device, when required.

### **CLUTCH FAN**

A Horton® fan clutch will be provided. The fan clutch will be automatic when the pump transmission is in "Road" position, and fully engaged in "Pump" position.

### **ENGINE AIR INTAKE**

An air intake with an ember separator (to prevent road dirt, burning embers, and recirculating hot air from entering the engine) will be mounted at the front of the apparatus, on the passenger side of the engine. The ember separator will be mounted in the air intake with flame retardant, roto-molded polyethylene housing. It will be easily accessible by the hinged access panel at the front of the vehicle.

### **EXHAUST SYSTEM**

The exhaust system will be stainless steel from the turbo to the inlet of the selective catalytic reduction (SCR) device, and will be 4.00" in diameter. The exhaust system will include a diesel particulate filter (DPF) and an SCR device to meet current EPA standards. An insulation wrap will be provided on all exhaust pipes between the turbo and DPF to minimize the transfer of heat to the cab. The exhaust will terminate horizontally ahead of the passenger side rear wheels. A tailpipe diffuser will be provided to reduce the temperature of the exhaust as it exits. Heat deflector shields will be provided to isolate chassis and body components from the heat of the tailpipe diffuser.

### **RADIATOR**

The radiator and the complete cooling system will meet or exceed NFPA and engine manufacturer cooling system standards.

For maximum corrosion resistance and cooling performance, the entire radiator core will be constructed using long life aluminum alloy. The core will be made of aluminum fins, having a serpentine design, brazed to aluminum tubes. The tubes will be brazed to aluminum headers. No solder joints or leaded material of any kind will be acceptable in the core assembly. The radiator core will have a minimum frontal area of 1434 square inches. Supply and return tanks made of glass-reinforced nylon will be crimped on to the core assembly using header tabs and a compression gasket to complete the radiator core assembly. The radiator will be compatible with commercial antifreeze solutions.

There will be a full steel frame around the entire radiator core assembly. The radiator core assembly will be isolated within the steel frame by rubber inserts to enhance cooling system durability and reliability. The radiator will be mounted in such a manner as to prevent the development of leaks caused

by twisting or straining when the apparatus operates over uneven ground. The radiator assembly will be isolated from the chassis frame rails with rubber isolators.

The radiator assembly will include an integral deaeration tank permanently mounted to the top of the radiator framework, with a readily accessible remote-mounted overflow tank. For visual coolant level inspection, the radiator will have a built-in sight glass. The radiator will be equipped with a 15 psi pressure relief cap.

A drain port will be located at the lowest point of the cooling system and/or the bottom of the radiator to permit complete flushing of the coolant from the system.

A heavy-duty fan will draw in fresh, cool air through the radiator. Shields or baffles will be provided to prevent recirculation of hot air to the inlet side of the radiator.

### **COOLANT LINES**

Gates® silicone hoses will be used for all engine/heater coolant lines installed by the chassis manufacturer.

The chassis manufacturer will also use Gates brand hose on other heater, defroster and auxiliary coolant circuits. There will be some areas in which an appropriate Gates product is not available. In those instances a comparable silicone hose from another manufacturer will be used.

Hose clamps will be stainless steel "constant torque type" to prevent coolant leakage. They will react to temperature changes in the cooling system and expand or contract accordingly while maintaining a constant clamping pressure on the hose.

### **FUEL TANK**

A 65 gallon fuel tank will be provided and mounted at the rear of the chassis. The tank will be constructed of 12-gauge, hot rolled steel. It will be equipped with swash partitions and a vent. To eliminate the effects of corrosion, the fuel tank will be mounted with stainless steel straps.

A 0.75" drain plug will be located in a low point of the tank for drainage.

A fill inlet will be located on the left hand side of the body and is covered with a hinged, spring loaded, stainless steel door that is marked "Ultra Low Sulfur - Diesel Fuel Only."

A 0.50" diameter vent will be installed from tank top to just below fuel fill inlet.

The fuel tank will meet all FHWA 393.67 requirements including a fill capacity of 95 percent of tank volume.

All fuel lines will be provided as recommended by the engine manufacturer.

### **DIESEL EXHAUST FLUID TANK**

A 4.5 gallon diesel exhaust fluid (DEF) tank will be provided and mounted in the driver's side body forward of the rear axle.

A 0.50" drain plug will be provided in a low point of the tank for drainage.

A fill inlet will be located on the driver's side of the body and be covered with a hinged, spring loaded, polished stainless steel door that is marked "Diesel Exhaust Fluid Only".

The tank will meet the engine manufacturers requirement for 10 percent expansion space in the event of tank freezing.

The tank will include an integrated heater unit that utilizes engine coolant to thaw the DEF in the event of freezing.

### **FUEL SHUTOFF**

A fuel line shutoff valve will be installed on both the inlet and outlet of the primary fuel filter.

The fuel filler cap will have a retaining chain and holder provided on the fuel fill door.

### **TRANSMISSION**

An Allison 5th generation, Model EVS 3000P, electronic torque converting automatic transmission will be provided.

The transmission will be equipped with prognostics to monitor oil life, filter life, and transmission health. A wrench icon on the shift selector's digital display will indicate when service is due.

Two (2) PTO openings will be located on left side and top of converter housing (positions 9 o'clock and 3 o'clock).

A transmission temperature gauge with red light and audible alarm will be installed on the cab dash.

### **TRANSMISSION SHIFTER**

A five (5)-speed push button shift module will be mounted to right of driver on console. Shift position indicator will be indirectly lit for after dark operation.

The transmission ratio will be:

1st	3.49 to 1.00
2nd	1.86 to 1.00
3rd	1.41 to 1.00
4th	1.00 to 1.00
5th	0.75 to 1.00
R	5.03 to 1.00

## **TRANSMISSION PROGRAMMING**

The transmission will be programmed to automatically shift the transmission to neutral when the parking brake is set to simplify operation and increase operational safety.

## **TRANSMISSION COOLER**

A Modine plate and fin transmission oil cooler will be provided using engine coolant to control the transmission oil temperature.

## **DRIVELINE**

Drivelines will be a heavy-duty metal tube and be equipped with Spicer® 1710 universal joints.

The shafts will be dynamically balanced before installation.

A splined slip joint will be provided in each driveshaft, slip joint will be coated with Glidecoat® or equivalent.

## **STEERING**

Dual Sheppard, Model M110, steering gears, with integral heavy-duty power steering, will be provided. For reduced system temperatures, the power steering will incorporate an air to oil cooler and an Eaton, Model VN20, hydraulic pump with integral pressure and flow control. All power steering lines will have wire braded lines with crimped fittings.

A tilt and telescopic steering column will be provided to improve fit for a broader range of driver configurations.

## **STEERING WHEEL**

The steering wheel will be 18.00" in diameter, have tilting and telescoping capabilities, and a 4-spoke design.

## **LOGO AND CUSTOMER DESIGNATION ON DASH**

The dash panel will have an emblem containing the Pierce logo and customer name. The emblem will have three (3) rows of text for the customer's department name. There will be a maximum of eight (8) characters in the first row, 11 characters in the second row and 11 characters in the third row.

The first row of text will be: Key West

The second row of text will be: Fire

The third row of text will be: Department

## **ADDITION WHEELBASE**

The cab gap will be increased one (1) additional inch to provide extra clearance for cab mounted equipment.

## **BUMPER**

A one (1) piece, ten (1) gauge, 304-2B type polished stainless steel bumper, a minimum of 10.00" high, will be attached to a bolted modular extension frame constructed of 50,000 psi tensile steel "C" channel mounted directly behind it to provide adequate support strength.

The bumper will be extended 19.00" from front face of cab.

Documentation will be provided, upon request to show that the options selected have been engineered for fit-up and approval for this modular bumper extension. A chart will be provided to indicate the option locations and will include, but not be limited to the following options: air horns, mechanical sirens, speakers, hose trays (with hose capacities), winches, lights, discharge, and suction connections.

## **GRAVEL PAN**

A gravel pan, constructed of bright aluminum treadplate, will be furnished between the bumper and cab face. The gravel pan will be properly supported from the underside to prevent flexing and vibration of the aluminum treadplate.

## **CENTER HOSE TRAY**

A hose tray, constructed of aluminum, will be placed in the center of the bumper extension.

The tray will have a capacity of 150' of 1.75" double jacket cotton-polyester hose.

Black rubber grating will be provided at the bottom of the tray. Drain holes are also provided.

## **CENTER HOSE TRAY RESTRAINT**

There will be one (1) pair of hose tray restraint straps located over the center mounted tray.

The restraints will be a pair of 2.00" wide black nylon straps with Velcro® fasteners provided. The strap(s) will be used to secure the hose in the tray.

## **LIFT AND TOW MOUNTS**

Mounted to the frame extension will be lift and tow mounts. The lift and tow mounts will be designed and positioned to adapt to certain tow truck lift systems.

The lift and tow mounts with eyes will be painted the same color as the frame.

## **TOW HOOKS**

Two (2) chromed steel tow hooks will be installed under the bumper and attached to the front frame members. The tow hooks will be designed and positioned to allow up to a 6,000 lb straight horizontal pull in line with the centerline of the vehicle. The tow hooks will not be used for lifting of the apparatus.

## **CAB**

The cab will be designed specifically for the fire service and will be manufactured by the chassis builder.

To provide quality at the source and single source customer support, the cab will be built by the apparatus manufacturer in a facility located on the manufacturer's premises.

For reasons of structural integrity and enhanced occupant protection, the cab will be of heavy duty design, constructed to the following minimal standards.

The cab will have 12 main vertical structural members located in the A-pillar (front cab corner posts), B-pillar (side center posts), C-pillar (rear corner posts) and rear wall areas. The A-pillar will be constructed of 0.25" heavy wall extrusions joined by a solid A356-T6 aluminum joint casting. The B-pillar and C-pillar will also be constructed from 0.25" heavy wall extrusions. The rear wall will be constructed of two (2) 4.00" x 2.00" outer aluminum extrusions and two (2) 3.00" x 2.00" inner aluminum extrusions. All main vertical structural members will run from the floor to 7.50" x 3.50" x 0.125" thick roof extrusions to provide a cage-like structure with the A-pillar and roof extrusions being welded into a 0.75" thick corner casting at each of the front corners of the roof assembly.

The front of the cab will be constructed of a 0.25" thick firewall, covered with a 0.125" front skin (for a total thickness of 0.38"), and reinforced with 24.50" wide x 10.00" deep x 0.50" thick supports on each side of the engine tunnel. The cross-cab support will be welded to the A-pillar, 0.25" firewall, and engine tunnel, on the left and right sides.

The cab floors will be constructed of 0.1875" thick aluminum plate and reinforced at the firewall with an additional 0.25" thick cross-floor support providing a total thickness of 0.44" of structural material at the front floor area. The front floor area will also be supported with three (3) 0.50" plates bolted together that also provides the mounting point for the cab lift. This tubing will run from the front of the cab to the 0.1875" thick engine tunnel, creating the structure to support the forces created when lifting the cab.

The cab will be a full-tilt style. A three (3)-point cab mount system with rubber isolators will improve ride quality by isolating chassis vibrations from the cab.

The crew cab will be a totally enclosed design with the interior area completely open to improve visibility and verbal communication between the occupants.

The overall height (from the cab roof to the ground) will be approximately 102.00". The overall height listed will be calculated based on a truck configuration with the lowest suspension weight ratings, the smallest diameter tires for the suspension, no water weight, no loose equipment weight, and no personnel weight. Larger tires, wheels, and suspension will increase the overall height listed.

The cab will have an interior width of not less than 93.50". The driver and passenger seating positions will have a minimum 24.00" clear width at knee level.

To reduce injuries to occupants in the seated positions, proper head clearance will be provided. The floor-to-ceiling height inside the forward cab will be no less than 60.25". The floor-to-ceiling height inside the crew cab will be no less than 52.95" in the center position and 58.75" in the outboard positions.

The crew cab will measure a minimum of 57.50" from the rear wall to the backside of the engine tunnel (knee level) for optimal occupant legroom.

### **CAB PUMP ENCLOSURE**

The rear of the cab will be made to house the fire pump below the forward facing crew cab seats. The cab side panels will be notched to accommodate the pump panel.

### **INTERIOR CAB INSULATION**

The cab walls, ceiling and engine tunnel will be insulated in all strategic locations to maximize acoustic absorption and thermal insulation. The cab will be insulated with 2.00" insulation in the rear wall, 3.00" insulation in the side walls, and 1.50" insulation in the ceiling.

### **FENDER LINERS**

Full-circular, aluminum, inner fender liners in the wheel wells will be provided.

### **PANORAMIC WINDSHIELD**

A one (1)-piece, safety glass windshield with more than 2,802 square inches of clear viewing area will be provided. The windshield will be full width and will provide the occupants with a panoramic view. The windshield will consist of three (3) layers: the outer light, the middle safety laminate, and the inner light. The 0.114" thick outer light layer will provide superior chip resistance. The middle safety laminate layer will prevent the windshield glass pieces from detaching in the event of breakage. The inner light will provide yet another chip resistant layer. The cab windshield will be bonded to the aluminum windshield frame using a urethane adhesive. A custom frit pattern will be applied on the outside perimeter of the windshield for a finished automotive appearance.

### **WINDSHIELD WIPERS**

Three (3) electric windshield wipers with a washer, in conformance with FMVSS and SAE requirements, will be provided. The wiper blades will be 21.65" long and together will clear a minimum of 1,783 square inches of the windshield for maximum visibility in inclement weather.

The windshield washer fluid reservoir will be located at the front of the vehicle and be accessible through the access hood for simple maintenance.

### **FAST SERVICE ACCESS FRONT TILT HOOD**

A full-width access hood will be provided for convenient access to engine coolant, steering fluid, wiper fluid, cab lift controls, headlight power modules, and ember separator. The hood will also provide complete access to the windshield wiper motor and components. The hood will be contoured to provide a sleek, automotive appearance. The hood will be constructed of two (2) fiberglass panels bonded together and will include reinforcing ribs for structural integrity. The hood will include air cylinders to hold the hood in open and closed positions, and a heavy duty latch system that will meet FMVSS 113 (Hood Latch System). The spring-loaded hood latch will be located at the center of the hood with a double-action release lever located behind the Pierce logo. The two (2)-step release requires the lever



first be pulled to the driver side until the hood releases from the first latch (primary latch) then to the passenger side to fully release the hood (secondary latch).

### **ENGINE TUNNEL**

To provide structural strength, the engine tunnel sidewalls will be constructed of .50" aluminum plate that is welded to both the .25" firewall and .38" heavy wall extrusion under the crew cab floor. To maximize occupant space, the top edges will be tapered.

The engine tunnel will be insulated on both sides for thermal and acoustic absorption. The underside of the tunnel will be covered with 1.00" thick polyether foam that is reinforced with an aluminized face. Thermal rating for this insulation will be -40 degrees Fahrenheit to 300 degrees Fahrenheit. The insulation will keep noise (dBA) levels at or lower than the specifications in the current edition of the NFPA 1901 standards.

### **CAB REAR WALL EXTERIOR COVERING**

The exterior surface of the rear wall of the cab will be overlaid with bright aluminum treadplate except for areas that are not typically visible when the cab is lowered.

### **CAB LIFT**

A hydraulic cab lift system will be provided, consisting of an electric-powered hydraulic pump, fluid reservoir, dual lift cylinders, remote cab lift controls and all necessary hoses and valves. The hydraulic pump will have a backup manual override, for use in the event of an electrical failure.

The cab lift controls will be located at the driver side front of the cab, easily accessible under the full width front access hood. The controls will include a permanently mounted raise/lower switch. For enhanced visibility during cab tilt operations, a remote control tether with on/off switch will be supplied on a coiled cord that will extend from 2.00' (coiled) to 6.00' (extended).

The cab will be capable of tilting 42 degrees and 80 degrees with crane assist to accommodate engine maintenance and removal. The cab pivots will be located 46.00" apart to provide stability while tilting the cab.

The rear of the cab will be locked down by a two (2)-point, automatic, hydraulic, double hook mechanism that fully engages after the cab has been lowered (self-locking). The dual 2.25" diameter hydraulic cylinders will be equipped with a velocity fuse that protects the cab from accidentally descending when the cab is in the tilt position.

For increased safety, a redundant mechanical stay arm will be provided that must be manually put in place on the driver side between the chassis and cab frame when cab is in the raised position. This device will be manually stowed to its original position before the cab can be lowered.

### **Cab Lift Interlock**

The cab lift safety system will be interlocked to the parking brake. The cab tilt mechanism will be active only when the parking brake is set and the ignition switch is in the on position. If the parking brake is released, the cab tilt mechanism will be disabled.

### **GRILLE**

A bright finished aluminum mesh grille screen, inserted behind a formed bright finished grille surround, will be provided on the front center of the cab, and will serve as an air intake to the radiator.

### **FRONT CAB TRIM**

Bright finished wrap-around housings will be provided on each side of the front cab face for mounting of the headlights and front directional lights. The housings will mate up to the side edge of the forward grille, and then extend around the front corners of the cab rearward, providing for a streamlined automotive appearance.

### **SIDE OF CAB MOLDING**

Chrome molding will be provided on both sides of cab.

### **MIRRORS**

One (1) Ramco, Model 6000FFHR-750, polished aluminum mirror will be mounted on each of the cab doors. The mirrors will be 9.25" wide x 13.50" high with a full flat face. An additional convex section will be bolted to the top of each mirror. The mirror head will have a highly polished aluminum finish.

The flat glass in each mirror will be heated and adjustable, with remote controls that are convenient to the driver.

The convex section in each mirror will be adjusted manually.

### **DOORS**

To enhance entry and egress to the cab, the forward cab doors will be a minimum of 43.59" wide x 76.46" high. The crew cab doors will be located on the sides of the cab and will be constructed in the same manner as the forward cab doors. The crew cab doors will measure a minimum of 37.87" wide x 76.46" high.

The forward cab and crew cab doors will be constructed of extruded aluminum with a nominal material thickness of 0.125". The exterior door skins will be constructed from 0.090" aluminum.

The forward cab door windows will include a 7.50" high x 10.00" wide drop area at the front to enhance visibility.

A customized, vertical, pull-down type door handle will be provided on the exterior of each cab door. The exterior handle will be designed specifically for the fire service to prevent accidental activation, and will provide 4.00" wide x 2.00" deep hand clearance for ease of use with heavy gloved hands. Each door will also be provided with an interior flush, open style paddle handle that will be readily operable

from fore and aft positions, and be designed to prevent accidental activation. The interior handles will provide 4.00" wide x 1.25" deep hand clearance for ease of use with heavy gloved hands.

The cab doors will be provided with both interior (rotary knob) and exterior (keyed) locks exceeding FMVSS standards. The locks will be capable of activating when the doors are open or closed. The doors will remain locked if locks are activated when the doors are opened, then closed.

A heavy duty, stainless steel, piano-type hinge with a 0.38" pin and 11 gauge leaf will be provided on all cab doors. There will be double automotive-type rubber seals around the perimeter of the door framing and door edges to ensure a weather-tight fit.

A dark grey vacuum formed ABS panel will house the window switches and will mold into the upper sill of the door panel.

The cab steps at each cab door location will be located inside the cab doors to protect the steps from weather elements.

### **DOOR PANELS**

The inner cab door panels will be constructed out of brushed stainless steel. The cab door panels will be removable without disconnecting door and window mechanisms.

### **RECESSED POCKET WITH ELASTIC COVER**

To provide organized storage (clutter control) in the cab for miscellaneous equipment, the cab interior will be provided with recessed storage pockets. The pockets will be 6.50" wide x 2.12" high x 6.00" deep and will be constructed of rugged, impact resistant, roto-molded low-density polyethylene. The pockets will be provided with a perforated elastic material cover to secure the equipment in the pocket. The pockets will be installed in all available mounting locations of the overhead console.

### **ELECTRIC WINDOW CONTROLS**

Each cab entry door will be equipped with an electrically operated tempered glass window. A window control panel will be ergonomically molded into the armrest of the door panel within easy reach of the respective occupant. Each switch will allow intermittent or auto down operation for ease of use. Auto down operation will be actuated by holding the window down switch for approximately 1/2 second. The driver control panel will contain a control switch for each cab door's window. All other door control panels will contain a single switch to operate the window within that door.

The window switches will be connected directly to the battery power. This allows the windows to be raised and lowered when the battery switch is in the off position.

### **CAB STEPS**

The forward cab and crew cab access steps will be a full size two (2) step design to provide largest possible stepping surfaces for safe ingress and egress. The bottom steps will be designed with a grip pattern punched into bright aluminum treadplate material to provide support, slip resistance, and drainage. The bottom steps will be a bolt-in design to minimize repair costs should they need to be

replaced. The forward cab steps will be a minimum 31.00" wide, and the crew cab steps will be 24.25" wide with an 8.00" minimum depth. The inside cab steps will not exceed 18.00" in height and be limited to two (2) steps. Three (3) step entrance designs will not be acceptable due to safety concerns. A slip-resistant handrail will be provided adjacent to each cab door opening to assist during cab ingress and egress.

### **STEP LIGHTS**

For reduced overall maintenance costs compared to incandescent lighting, there will be four (4) white LED step lights provided. The lights will be installed at each cab and crew cab door, one (1) per step. The lights will be located in the driver side front doorstep, driver side crew cab doorstep, passenger side front doorstep and passenger side crew cab doorstep.

In order to ensure exceptional illumination, each light will provide a minimum of 25 foot-candles (fc) covering an entire 15.00" x 15.00" square placed 10.00" below the light and a minimum of 1.5 fc covering an entire 30.00" x 30.00" square at the same 10.00" distance below the light.

The lights will be activated when the adjacent door is opened.

### **FENDER CROWNS**

Stainless steel fender crowns will be installed at the cab wheel openings.

### **CREW CAB WINDOWS**

One (1) fixed window with tinted glass will be provided on each side of the cab, to the rear of the front cab door. The windows will be sized to enhance light penetration into the cab interior. The windows will measure 20.00" wide x 20.50" high.

### **WINDOWS INTERIOR TRIM**

For improved aesthetics, the cab side windows will include a vacuum formed ABS interior trim panel.

### **WINDOWS, REAR**

The rear wall of the crew cab will have two (2) windows, each being 8.00" wide x 14.00" high.

### **WINDOW INTERIOR TRIM**

For improved aesthetics, the cab rear wall windows will include a vacuum formed ABS interior trim panel.

### **WINDOW TINT**

Crew cab windows will be provided with increased tint to reduce light transmission. The following windows are included:

- Crew cab side windows:25% light transmission
- Crew cab door, roll-up windows:14% light transmission
- Rear opera windows (if applicable):14% light transmission

## **CUP HOLDER**

There will be two (2) cup holder(s) provided. Each cup holder will have self-adjusting fingers that automatically grip beverage containers of various sizes. A recess in the cup holder will allow it to hold beverage containers with handles.

The cup holder(s) will be located at customer pick-up.

## **CAB INTERIOR**

With safety as the primary objective, the wrap-around style, high impact ABS polymer cab instrument panel will be designed with unobstructed visibility to instrumentation. The dash layout will provide the driver with a quick reference to gauges that allows more time to focus on the road. The center console will be a high impact ABS polymer, and will be easily removable for access to the defroster. The center console will include louvers strategically located for optimal air flow and defrost capability to the windshield. The passenger side dashboard will be constructed of painted aluminum for durability and low maintenance. For enhanced versatility, the passenger side dash will include a flat working surface. To provide optional (service friendly) control panels, switches and storage modules, a three (3)-piece, 4mm thick polyethylene roto-molded overhead console will also be provided. To complete the cab front interior design, painted aluminum modesty panels will be provided under the dash on both sides of the cab. The driver side modesty panel will provide mounting for the battery switch and diagnostic connectors, while the passenger side modesty panel provides a glove box, and ground access to the main electrical distribution panel via quick quarter turn fasteners.

To provide a deluxe automotive interior, the engine tunnel, side walls and rear wall will be covered by a leather grain vinyl that is resistant to oil, grease, and mildew.

The inner cab door panels will include grab handles and control panels molded into the upper section of the door panel. The door panels will extend 36.50" down from the door window.

The headliner will be installed in both forward and rear cab sections. The crew cab headliner will be one (1)-piece. The headliner panel will be a composition of a corrugated high density polyethylene panel covered with a sound barrier and upholstery. For quick, easy access of electrical wiring, or to perform other maintenance needs, the headliner will be held in place by a dual lock fastening system.

The cab structure will include designated raceways for electrical harness routing from the front of the cab to the rear upper portion of the cab. Raceways will be extruded in the forward door frame, floor, walls and overhead in the area where the walls meet the ceiling. The raceways located in the floor will be covered by aluminum extrusion, while the vertical and overhead raceways will be covered by a decorative composite panel. The raceways will improve harness integrity by providing a continuous harness path that eliminates wire chafing and abrasion associated with exposed wiring or routing through drilled metal holes. Harnesses will be laid in place, not pulled through holes drilled in aluminum tubing. Once laid in place, all harnesses will be held in position by a hook and loop fastening system. The hook and loop system will allow for bracket fastener points to not puncture harnesses. The raceways will include removable covers, providing maintenance personnel with quick and easy access

for trouble shooting, or the addition of accessories. Harnesses will be located within the raceway behind the wire way cover.

### **CAB INTERIOR UPHOLSTERY**

The cab interior upholstery will be dark silver gray. All cab interior materials will meet FMVSS 302 (flammability of interior materials).

### **INTERIOR PAINT (CAB)**

A rich looking interior will be provided by painting all the metal surfaces inside the cab gray, vinyl texture paint.

### **CAB FLOOR**

The cab and crew cab floor areas will be covered with Polydamp™ acoustical floor mat consisting of a black pyramid rubber facing and closed cell foam decoupler.

The top surface of the material has a series of raised pyramid shapes evenly spaced, which offer a superior grip surface. Additionally, the material has a .25" thick closed cell foam (no water absorption) which offers a sound dampening material for reducing sound levels.

### **CAB DEFROSTER**

To provide maximum defrost and heating performance, a 54,961 BTU heater-defroster unit with 558 SCFM of air flow will be provided inside the cab. The defroster unit will be strategically located under the center forward portion of the roto-molded instrument panel. For easy access, a removable roto-molded cover will be installed over the defroster unit. The defroster will include an integral aluminum frame air filter, high performance dual scroll blowers, and ducts designed to provide maximum defrosting capabilities for the 1-piece windshield. The defroster ventilation will be built into the design of the cab dash instrument panel and will be easily removable for maintenance. The defroster will be capable of clearing 98 percent of the windshield and side glass when tested under conditions where the cab has been cold soaked at 0 degrees Fahrenheit for 10 hours, and a 2 ounce per square inch layer of frost/ice has been able to build up on the exterior windshield. The defroster system will meet or exceed SAE J382 requirements.

### **CAB/CREW CAB HEATER**

Two (2) 36,702 BTU auxiliary heaters with 276 SCFM (each unit) of air flow will be provided inside the crew cab, one (1) within each rear facing seat riser. The heaters will include high performance dual scroll blowers, one (1) for each unit. Outlets for the heaters will be located below each rear facing seat riser and below the fronts of the driver and passenger seats, for efficient airflow. An extruded aluminum plenum will be incorporated in the cab structure that will transfer heat to the forward cab seating positions.

The heater/defroster and crew cab heaters will be controlled by a single integral electronic control panel. The heater control panel will allow the driver to control heat flow to the front and rear simultaneously. The control panel will include variable adjustment for temperature and fan control, and be conveniently

located on the dash in clear view of the driver. The control panel will include highly visible, progressive LED indicators for both fan speed and temperature. For increased convenience, an optional dual control for the passenger position will also be available.

### **AIR CONDITIONING**

A high-performance, customized air conditioning system will be furnished inside the cab and crew cab. A 19.10 cubic inch compressor will be installed on the engine.

The air conditioning system will be capable of cooling the average cab temperature from 100 degrees Fahrenheit to 64 degrees Fahrenheit in the forward section of the cab, and 69 degrees Fahrenheit in the rear section of the cab, at 50 percent relative humidity within 30 minutes. The cooling performance test will be run only after the cab has been heat soaked at 100 degrees Fahrenheit for a minimum of 4 hours.

A roof-mounted condenser with a 63,000 BTU output that meets and exceeds the performance specification will be installed on the cab roof. Mounting the condenser below the cab or body would reduce the performance of the system and will not be acceptable.

The evaporator unit will be installed in the cab, located in the center of the cab ceiling over the engine tunnel. The evaporator will include two (2) high performance cores and plenums with multiple outlets, one (1) plenum directed to the front and one (1) plenum directed to the rear of the cab.

The evaporator unit will have a 49,000 BTU rating that meets and exceeds the performance specifications.

Adjustable air outlets will be strategically located on the evaporator cover per the following:

- Two (2) will be directed towards the drivers location
- Two (2) will be directed towards the officers location
- Six (6) will be directed towards crew cab area

The air conditioner refrigerant will be R-134A and will be installed by a certified technician.

The air conditioner will be controlled by a single integral electronic control panel for the heater, defroster and air conditioner. For ease of operation, the control panel will include variable adjustment for temperature and fan control, and be conveniently located on the dash in clear view of the driver. The control panel will include highly visible, progressive LED indicators for both fan speed and temperature. For added convenience, an optional dual control for the passenger position will also be available.

### **INTERIOR CAB INSULATION**

The cab walls, ceiling and engine tunnel will be insulated in all strategic locations to maximize acoustic absorption and thermal insulation. The cab will be insulated with 2.00" insulation in the rear wall, 3.00" insulation in the side walls, and 1.50" insulation in the ceiling. Headliners will be constructed from a 0.20" high density polyethylene corrugated material. Each headliner will be wrapped with a 0.25" thick foil faced poly damp low emissivity foam insulation barrier for acoustic and thermal control. For ease

of installation and removal, all headliners will be held in place by a dual lock fastening system. Headliner installation requiring removal of mechanical fasteners will not be acceptable.

Designed for maximum sound absorption and thermal insulation, the rear cab wall will be insulated with a 1.50" thick open cell acoustical foam. The thermal protection of the foam will provide an R-value of four (4) per 1.00" thickness.

### **HVAC CONTROL PANEL**

An additional electronic control panel for the HVAC system will be provided. For ease of operation, the control panel will include variable adjustment for temperature and fan control, and be conveniently located on the passenger side overhead switch panel. The control panel will include highly visible, progressive LED indicators for both fan speed and temperature. Operational adjustments from any HVAC control panel will be indicated on all other control panel(s). If simultaneous operation exists, the HVAC control panel operated first will retain control.

### **SPECIAL DRAIN TUBES**

Two (2) condensate drain tubes will be provided for the air conditioning evaporator. The drip pan will have two (2) drain tubes plumbed separately to allow for the condensate to exit the drip pan. The standard evaporator pumps will be disabled.

### **SUN VISORS**

Two (2) smoked Lexan™ sun visors provided. The sun visors will be located above the windshield with one (1) mounted on each side of the cab.

There will be no retention bracket provided to help secure each sun visor in the stowed position.

### **GRAB HANDLE**

A black rubber covered grab handle will be mounted on the door post of the driver side cab door to assist in entering the cab. The grab handle will be securely mounted to the post area between the door and windshield.

A long rubber grab handle will be mounted on the dash board in front of the officer.

### **ENGINE COMPARTMENT LIGHTS**

There will be one (1) Whelen, Model 3SC0CDCR, 12 volt DC, 3.00" white LED light(s) with Whelen, Model 3FLANGEC, chrome flange kit(s) installed under the cab to be used as engine compartment illumination.

These light(s) will be activated automatically when the cab is raised.

### **ACCESS TO ENGINE DIPSTICKS**

For access to the engine oil and transmission fluid dipsticks, there will be a door on the engine tunnel, inside the crew cab. The door will be on the rear wall of the engine tunnel, on the vertical surface. The door will be 17.75" wide x 12.75" high and be flush with the wall of the engine tunnel.



The engine oil dipstick will allow for checking only. The transmission dipstick will allow for both checking and filling. An additional port will be provided for filling the engine oil.

The door will have a rubber seal for thermal and acoustic insulation. One (1) flush latch will be provided on the access door.

### **FRONTAL IMPACT PROTECTION**

The cab will be provided with a frontal impact protection system and will include the following:

- A supplemental restraint system (SRS) sensor will be installed on a structural cab member behind the instrument panel. The SRS sensor will perform real time diagnostics of all critical subsystems and will record sensory inputs immediately before and during a frontal impact event.
- A fault-indicating light will be provided on the vehicle's instrument panel allowing the driver to monitor the operational status of the SRS system.
- A driver side front air bag will be mounted in the steering wheel and will be designed to protect the head and upper torso of the occupant, when used in combination with the three (3)-point seat belt.
- A passenger side knee bolster air bag will be mounted in the modesty panel below the dash panel and will be designed to protect the legs of the occupant, when used in combination with the three (3)-point seat belt.
- Driver and front passenger suspension seats will be provided with devices to retract them to the lowest travel position during a frontal impact event.
- Driver and front passenger seat belts will be provided with pre-tensioners to remove slack from the seat belt during frontal impact event.

The SRS system will provide protection during a frontal or oblique impact event. The system will activate when the vehicle decelerates at a predetermined G force known to cause injury to the occupants. The cab and chassis will have been subjected, via third party test facility, to a crash impact during frontal and oblique impact testing. Testing included all major chassis and cab components such as mounting straps for fuel and air tanks, suspension mounts, front suspension components, rear suspensions components, frame rail cross members, engine and transmission and their mounts, pump house and mounts, frame extensions and body mounts. The testing provided configuration specific information used to optimize the timing for firing the safety restraint system. The sensor will activate the pyrotechnic devices when the correct crash algorithm, wave form, is detected.

The SRS system will deploy the following components in the event of a frontal or oblique impact event:

- Driver side front air bag.
- Passenger side knee bolster air bag.
- Driver and front passenger suspension seats will be retracted to the lowest travel position.
- Driver and front passenger seat belts will be pre-tensioned to firmly hold the occupant in place.

## **SEATING CAPACITY**

The seating capacity in the cab will be six (6).

## **DRIVER SEAT**

A Pierce PS6® seat will be provided in the cab for the driver. The seat design will be a cam action type, with air suspension. For increased convenience, the seat will include electric controls to adjust the rake (15 degrees), height (1.12" travel) and horizontal (7.75" travel) position. Electric controls will be located below the forward part of the seat cushion. To provide flexibility for multiple driver configurations, the seat will have a reclining back, adjustable from 20 degrees back to 45 degrees forward. Providing for maximum comfort, the seat back will be a high back style with manual lumbar adjustment lever, for lower back support, and will include minimum 7.50" deep side bolster pads for maximum support. The lumbar adjustment lever will be easily located at the lower outboard position of the seat cushion. For optimal comfort, the seat will be provided with 17.00" deep dual density foam cushions designed with EVC (elastomeric vibration control).

The seat will include the following features incorporated into the frontal impact protection system:

- A suspension seat safety system will be included. When activated in the event of a frontal impact, this system will pretension the seat belt and retract the seat to its lowest travel position.

The seat will be furnished with a 3-point, shoulder type seat belt. To provide quick, easy use for occupants wearing bunker gear, the seat belt will have a minimum 120.00" shoulder length and 55.00" lap length. The seat belt tongue will be stored at waist position for quick application by the seat occupant. The seat belt receptacle will be provided on a cable conveniently nested next to the seat cushion, providing easy accessibility. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

## **OFFICER SEAT**

A Pierce, PS6®, seat will be provided in the cab for the passenger. The seat will be a cam action type with air suspension. For increased convenience, the seat will include a manual control to adjust the horizontal position 6.00" travel. The manual horizontal control will be a towel-bar style located below the forward part of the seat cushion. For optimal comfort, the seat will be provided with 17.00" deep dual density foam cushions designed with EVC (elastomeric vibration control). To ensure safe operation, the seat will be equipped with seat belt sensors in the seat cushion and belt receptacle that will activate an alarm indicating a seat is occupied but not belted.

The seat back will be an SCBA back style with 7.50 degree fixed recline angle and will include minimum 4.50" wide x 7.50" deep side bolster pads for maximum support. The SCBA cavity will be adjustable from front to rear in 1.00" increments to accommodate different sized SCBA cylinders. Moving the SCBA cavity will be accomplished by unbolting, relocating, and re-bolting it in the desired location.

The seat will include the following feature incorporated into the frontal impact protection system:

- A suspension seat safety system will be included. When activated, this system will pretension the seat belt and retract the seat to its lowest travel position.

The seat will be furnished with a 3-point, shoulder type seat belt. To provide quick, easy use for occupants wearing bunker gear, the seat belt will have a minimum 120.00" shoulder length and 55.00" lap length. The seat belt tongue will be stored at waist position for quick application by the seat occupant. The seat belt receptacle will be provided on a cable conveniently nested next to the seat cushion, providing easy accessibility. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

### **REAR FACING DRIVER SIDE OUTBOARD SEAT**

There will be one (1) rear facing, Pierce PS6 seat provided at the driver side outboard position in the crew cab. For optimal comfort, the seat will be provided with 17.00" deep dual density foam cushions designed with EVC (elastomeric vibration control). To ensure safe operation, the seat will be equipped with seat belt sensors in the seat cushion and belt receptacle that will activate an alarm indicating a seat is occupied but not buckled.

The seat back will be an SCBA back style with 7.50 degree fixed recline angle, and will include minimum 4.50" wide x 7.50" deep side bolster pads for maximum support. The SCBA cavity will be adjustable from front to rear in 1.00" increments, to accommodate different sized SCBA cylinders. Moving the SCBA cavity will be accomplished by unbolting, relocating, and re-bolting it in the desired location.

The seat will be furnished with a three (3)-point, shoulder type seat belt. To provide quick, easy use for occupants wearing bunker gear, the seat belt will have a minimum 120.00" shoulder length and 55.00" lap length. The seat belt tongue will be stored at waist position for quick application by the seat occupant. The seat belt receptacle will be provided on a cable conveniently nested next to the seat cushion, providing easy accessibility. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

### **REAR FACING PASSENGER SIDE OUTBOARD SEAT**

There will be one (1) rear facing, Pierce PS6 seat provided at the passenger side outboard position in the crew cab. For optimal comfort, the seat will be provided with 17.00" deep dual density foam cushions designed with EVC (elastomeric vibration control). To ensure safe operation, the seat will be equipped with seat belt sensors in the seat cushion and belt receptacle that will activate an alarm indicating a seat is occupied but not buckled. The seat back will be an SCBA back style with 7.5 degree fixed recline angle, and will include minimum 4.50" wide x 7.50" deep side bolster pads for maximum support. The SCBA cavity will be adjustable from front to rear in 1.00" increments, to accommodate different sized SCBA cylinders. Moving the SCBA cavity will be accomplished by unbolting, relocating, and re-bolting it in the desired location.

The seat will be furnished with a three (3)-point, shoulder type seat belt. To provide quick, easy use for occupants wearing bunker gear, the seat belt will have a minimum 120.00" shoulder length and 55.00"

lap length. The seat belt tongue will be stored at waist position for quick application by the seat occupant. The seat belt receptacle will be provided on a cable conveniently nested next to the seat cushion, providing easy accessibility. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

#### **FORWARD FACING DRIVER SIDE OUTBOARD SEAT**

There will be one (1) forward facing, Pierce PS6 seat provided at the driver side outboard position in the crew cab. The seat back will be a high back style with 7.50 degree fixed recline angle, and will include minimum 7.50" deep side bolster pads for maximum support. For optimal comfort, the seat will be provided with 17.00" deep dual density foam cushions designed with EVC (elastomeric vibration control). To ensure safe operation, the seat will be equipped with seat belt sensors in the seat cushion and belt receptacle, that will activate an alarm indicating a seat is occupied but not buckled.

The seat will be furnished with a three (3)-point, shoulder type seat belt. To provide quick, easy use for occupants wearing bunker gear, the seat belt will have a minimum 120.00" shoulder length and 55.00" lap length. The seat belt tongue will be stored at waist position for quick application by the seat occupant. The seat belt receptacle will be provided on a cable conveniently nested next to the seat cushion, providing easy accessibility. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

#### **EMS COMPARTMENT**

An EMS compartment, 42.00" wide x 36.00" high x 24.00" deep with one (1) Gortite roll up door, locking, with anodized finish will be provided in the crew cab. The compartment will be provided with no false floor.

The compartment will be constructed of smooth aluminum, and painted to match the cab interior.

#### **COMPARTMENT LIGHT**

There will be two (2) white Amdor, LED strip lights installed, one (1) each side of the compartment opening. The lights will be controlled by an automatic door switch.

#### **FORWARD FACING PASSENGER SIDE OUTBOARD SEAT**

There will be one (1) forward facing, Pierce PS6 seat provided at the passenger side outboard position in the crew cab. The seat back will be a high back style with 7.5 degree fixed recline angle, and will include minimum 7.50" deep side bolster pads for maximum support. For optimal comfort, the seat will be provided with 17.00" deep dual density foam cushions designed with EVC (elastomeric vibration control). To ensure safe operation, the seat will be equipped with seat belt sensors in the seat cushion and belt receptacle that will activate an alarm indicating a seat is occupied but not buckled.

The seat will be furnished with a three-point, shoulder type seat belt. To provide quick, easy use for occupants wearing bunker gear, the seat belt will have a minimum 120.00" shoulder length and 55.00" lap length. The seat belt tongue will be stored at waist position for quick application by the seat occupant. The seat belt receptacle will be provided on a cable conveniently nested next to the seat

cushion, providing easy accessibility. The seat belt will be furnished with dual automatic retractors that will provide ease of operation in the normal seating position.

### **SHELVING**

There will be one (1) shelf provided. Each shelf will be constructed of 0.090" aluminum with a 1.25" up-turned lip. Shelving will be infinitely adjustable by means of a threaded tightener sliding in a track.

The location will be one (1) shelf in the center forward facing EMS cabinet.

### **SEAT UPHOLSTERY**

All Pierce PS6 seat upholstery will be gray woven with black Imperial 1200 material.

### **AIR BOTTLE HOLDERS**

All SCBA type seats in the cab will have a "Hands-Free" auto clamp style bracket in its backrest. For efficiency and convenience, the bracket will include an automatic spring clamp that allows the occupant to store the SCBA bottle by simply pushing it into the seat back. For protection of all occupants in the cab, in the event of an accident, the inertial components within the clamp will constrain the SCBA bottle in the seat and will exceed the NFPA standard of 9G. Bracket designs with manual restraints (belts, straps, buckles) that could be inadvertently left unlocked and allow the SCBA to move freely within the cab during an accident, will not be acceptable.

There will be a quantity of three (3) SCBA brackets.

### **SEAT BELTS**

All seating positions in the cab and crew cab will have red seat belts.

The belts will also include the Ready Reach® D-loop assembly to the shoulder belt system. The Ready Reach feature adds an extender arm to the D-loop location placing the D-loop in a closer, easier to reach location.

### **SHOULDER HARNESS HEIGHT ADJUSTMENT**

All seating positions furnished with three (3)-point shoulder type seat belts will include a height adjustment. This adjustment will optimize the belts effectiveness and comfort for the seated firefighter.

A total of six (6) seating positions will have the adjustable shoulder harness.

### **SEAT BELT MONITORING SYSTEM**

A seat belt monitoring system (SBMS) will be provided. The SBMS will be capable of monitoring up to ten (10) seat positions indicating the status of each seat position with a green or red LED indicator as follows:

- Seat Occupied & Buckled = Green
- Seat Occupied & Unbuckled = Red
- No Occupant & Buckled = Red

- No Occupant & Unbuckled = Not Illuminated

### **Audible Alarm**

The SBMS will include an audible alarm that will be activated when a red illumination condition exists and the parking brake is released, or a red illumination condition exists and the transmission is not in park.

### **HELMET HOLDER**

There will be a total of six (6) Zico, Model UHH-1, helmet holder bracket(s) provided in the cab. The brackets will provide secure storage and quick access to each helmet. The location of the helmet holder bracket(s) will be determined at the time of final inspection.

### **CAB DOME LIGHTS**

There will be four (4) dual LED dome lights with black bezels provided. Two (2) lights will be mounted above the inside shoulder of the driver and officer and two (2) lights will be installed and located, one (1) on each side of the crew cab.

The color of the LED's will be red and white.

The white LED's will be controlled by the door switches and the lens switch.

The color LED's will be controlled by the lens switch.

In order to ensure exceptional illumination, each white LED dome light will provide a minimum of 10.1 foot-candles (fc) covering an entire 20.00" x 20.00" square seating position when mounted 40.00" above the seat.

### **MAP LIGHT**

There will be one (1) Sunnex®, LS75\* Series, LED map light(s) provided in the cab and located on officer side of dash. Each map light will have a rectangular base with an on/off switch. The map light(s) will have a 20.00" long flexible neck that exits the top of the chassis mount.

The light switch(es) will be connected directly to the battery switched power.

### **HAND HELD LIGHT**

There will be four (4) 12v Streamlight, Model #44401, Fire Vulcan, lights mounted two (2) mounted on rear of engine cover facing inboard, and, two (2) located under forward facing seats, one each side.

Each light housing will be orange in color and be provided with a single filament halogen bulb and two "ultra bright blue taillight LEDs" The LEDs will have a dual mode (blinking or steady).

### **HAND HELD SPOTLIGHT**

There will be one (1) spotlight provided which will be a Collins, Model CL-12-M hand held spot/flood light(s) installed match Job 26500. The light(s) will be furnished with a 9 foot coil cord and momentary

switch. The housing will be made from aircraft aluminum that is powder coat painted black. The mounting bracket will be fabricated from stainless steel.

### **CAB INSTRUMENTATION**

The cab instrument panel will consist of gauges, an LCD display, telltale indicator lights, alarms, control switches, and a diagnostic panel. The function of instrument panel controls and switches will be identified by a label adjacent to each item. Actuation of the headlight switch will illuminate the labels in low light conditions. Telltale indicator lamps will not be illuminated unless necessary. The cab instruments and controls will be conveniently located within the forward cab section directly forward of the driver. Gauge and switch panels will be designed to be removable for ease of service and low cost of ownership.

### **GAUGES**

The gauge panel will include the following ten (10) ivory gauges with chrome bezels to monitor vehicle performance:

- Voltmeter gauge (Volts)

  - Low volts (11.8 VDC)

  - Amber indicator on gauge assembly with alarm

- High volts (15 VDC)

  - Amber indicator on gauge assembly with alarm

- Very low volts (11.3 VDC)

  - Amber indicator on gauge assembly with alarm

- Very high volts (16 VDC)

  - Amber indicator on gauge assembly with alarm

- Tachometer (RPM)

- Speedometer (Primary (outside) MPH, Secondary (inside) Km/H)

- Fuel level gauge (Empty - Full in fractions)

  - Low fuel (1/8 full)

  - Amber indicator on gauge assembly with alarm

- Very low fuel (1/32) fuel

  - Amber indicator on gauge assembly with alarm

- Engine oil pressure gauge (PSI)

Low oil pressure to activate engine warning lights and alarms

Red indicator on gauge assembly with alarm

- Front air pressure gauge (PSI)

Low air pressure to activate warning lights and alarm

Red indicator on gauge assembly with alarm

- Rear air pressure gauge (PSI)

Low air pressure to activate warning lights and alarm

Red indicator on gauge assembly with alarm

- Transmission oil temperature gauge (Fahrenheit)

High transmission oil temperature activates warning lights and alarm

Amber indicator on gauge assembly with alarm

- Engine coolant temperature gauge (Fahrenheit)

High engine temperature activates an engine warning light and alarm

Red indicator on gauge assembly with alarm

- Diesel Exhaust Fluid Level Gauge (Empty - Full in fractions)

Low fluid (1/8 full)

Amber indicator on gauge assembly with alarm

All gauges and gauge indicators will perform prove out at initial power-up to ensure proper performance.

### **INDICATOR LAMPS**

To promote safety, the following telltale indicator lamps will be integral to the gauge assembly and are located above and below the center gauges. The indicator lamps will be "dead-front" design that is only visible when active. The colored indicator lights will have descriptive text or symbols.

The following amber telltale lamps will be present:

- Low coolant

- Trac cntl (traction control) (where applicable)



- Check engine
- Check trans (check transmission)
- Aux brake overheat (Auxiliary brake overheat)
- Air rest (air restriction)
- Caution (triangle symbol)
- Water in fuel
- DPF (engine diesel particulate filter regeneration)
- Trailer ABS (where applicable)
- Wait to start (where applicable)
- HET (engine high exhaust temperature) (where applicable)
- ABS (antilock brake system)
- MIL (engine emissions system malfunction indicator lamp) (where applicable)
- SRS (supplemental restraint system) fault (where applicable)
- DEF (low diesel exhaust fluid level)

The following red telltale lamps will be present:

- Warning (stop sign symbol)
- Seat belt
- Parking brake
- Stop engine
- Rack down

The following green telltale lamps will be provided:

- Left turn
- Right turn
- Battery on

The following blue telltale lamp will be provided:

- High beam

## **ALARMS**

Audible steady tone warning alarm: A steady audible tone alarm will be provided whenever a warning message is present.

Audible pulsing tone caution alarm: A pulsing audible tone alarm (chime/chirp) will be provided whenever a caution message is present without a warning message being present.

Alarm silence: Any active audible alarm will be able to be silenced by holding the ignition switch at the top position for three (3) to five (5) seconds. For improved safety, silenced audible alarms will intermittently chirp every 30 seconds until the alarm condition no longer exists. The intermittent chirp will act as a reminder to the operator that a caution or warning condition still exists. Any new warning or caution condition will enable the steady or pulsing tones respectively.

## **INDICATOR LAMP AND ALARM PROVE-OUT**

Telltale indicators and alarms will perform prove-out at initial power-up to ensure proper performance.

## **CONTROL SWITCHES**

For ease of use, the following controls will be provided immediately adjacent to the cab instrument panel within easy reach of the driver.

Emergency master switch: A molded plastic push button switch with integral indicator lamp will be provided. Pressing the switch will activate emergency response lights and siren control. A green lamp on the switch provides indication that the emergency master mode is active. Pressing the switch again disables the emergency master mode.

Headlight / Parking light switch: A three (3)-position maintained rocker switch will be provided. The first switch position will deactivate all parking lights and the headlights. The second switch position will activate the parking lights. The third switch position will activate the headlights.

Panel backlighting intensity control switch: A three (3)-position momentary rocker switch will be provided. The first switch position decreases the panel backlighting intensity to a minimum level as the switch is held. The second switch position is the default position that does not affect the backlighting intensity. The third switch position increases the panel backlighting intensity to a maximum level as the switch is held.

The following standard controls will be integral to the gauge assembly and are located below the right hand gauges. All switches have backlit labels for low light applications.

High idle engagement switch: A two (2)-position momentary rocker switch with integral indicator lamp will be provided. The first switch position is the default switch position. The second switch position will activate and deactivate the high idle function when pressed and released. The "Ok To Engage High

Idle" indicator lamp must be active for the high idle function to engage. A green indicator lamp integral to the high idle engagement switch will indicate when the high idle function is engaged.

"Ok To Engage High Idle" indicator lamp: A green indicator light will be provided next to the high idle activation switch to indicate that the interlocks have been met to allow high idle engagement.

The following standard controls will be provided adjacent to the cab gauge assembly within easy reach of the driver. All switches will have backlit labels for low light applications.

Ignition switch: A three (3)-position maintained/momentary rocker switch will be provided. The first switch position will deactivate vehicle ignition. The second switch position will activate vehicle ignition. The third momentary position will disable the Command Zone audible alarm if held for three (3) to five (5) seconds. A green indicator lamp will be activated with vehicle ignition.

Engine start switch: A two (2)-position momentary rocker switch will be provided. The first switch position is the default switch position. The second switch position will activate the vehicle's engine. The switch actuator is designed to prevent accidental activation.

4-way hazard switch: A two (2)-position maintained rocker switch will be provided. The first switch position will deactivate the 4-way hazard switch function. The second switch position will activate the 4-way hazard function. The switch actuator will be red and includes the international 4-way hazard symbol.

Heater, defroster, and optional air conditioning control panel: A control panel with membrane switches will be provided to control heater/defroster temperature and heater, defroster, and air conditioning fan speeds. A green LED status bar will indicate the relative temperature and fan speed settings.

Turn signal arm: A self-canceling turn signal with high beam headlight and windshield wiper/washer controls will be provided. The windshield wiper control will have high, low, and intermittent modes.

Parking brake control: An air actuated push/pull park brake control valve will be provided.

Chassis horn control: Activation of the chassis horn control will be provided through the center of the steering wheel.

### **CUSTOM SWITCH PANELS**

The design of cab instrumentation will allow for emergency lighting and other switches to be placed within easy reach of the operator thus improving safety. There will be positions for up to four (4) switch panels in the overhead console on the driver's side, up to four (4) switch panels in the engine tunnel console facing the driver, up to four (4) switch panels in the overhead console on the officer's side and up to two (2) switch panels in the engine tunnel console facing the officer. All switches will have backlit labels for low light applications.

## **DIAGNOSTIC PANEL**

A diagnostic panel will be accessible while standing on the ground and located inside the driver's side door left of the steering column. The diagnostic panel will allow diagnostic tools such as computers to connect to various vehicle systems for improved troubleshooting providing a lower cost of ownership. Diagnostic switches will allow engine and ABS systems to provide blink codes should a problem exist.

The diagnostic panel will include the following:

- Engine diagnostic port
- Transmission diagnostic port
- ABS diagnostic port
- SRS diagnostic port (where applicable)
- Command Zone USB diagnostic port
- Engine diagnostic switch (blink codes flashed on check engine telltale indicator)
- ABS diagnostic switch (blink codes flashed on ABS telltale indicator)
- Diesel particulate filter regeneration switch (where applicable)
- Diesel particulate filter regeneration inhibit switch (where applicable)

## **CAB LCD DISPLAY**

A digital four (4)-row by 20-character dot matrix display will be integral to the gauge panel. The display will be capable of showing simple graphical images as well as text. The display will be split into three (3) sections. Each section will have a dedicated function. The upper left section will display the outside ambient temperature.

The upper right section will display, along with other configuration specific information:

- Odometer
- Trip mileage
- PTO hours
- Fuel consumption
- Engine hours

The bottom section will display INFO, CAUTION, and WARNING messages. Text messages will automatically activate to describe the cause of an audible caution or warning alarm. The LCD will be capable of displaying multiple text messages should more than one caution or warning condition exist.

### **AIR RESTRICTION INDICATOR**

A high air restriction warning indicator light LCD message with amber warning indicator and audible alarm will be provided.

- Ammeter.

### **"DO NOT MOVE APPARATUS" INDICATOR**

There will be a Whelen, Model 5SR00FRR, flashing red LED indicator light located in the driving compartment. The light will be illuminated automatically per the current NFPA requirements and labeled "Do Not Move Apparatus If Light Is On".

The same circuit that activates the Do Not Move Apparatus indicator will activate a steady tone alarm when the parking brake is released.

### **DO NOT MOVE TRUCK MESSAGES**

Messages will be displayed on the Command Zone™, color display located within sight of the driver whenever the Do Not Move Truck light is active. The messages will designate the item or items not in the stowed for vehicle travel position (parking brake disengaged).

The following messages will be displayed (where applicable):

- Do Not Move Truck
- DS Cab Door Open (Driver Side Cab Door Open)
- PS Cab Door Open (Passenger's Side Cab Door Open)
- DS Crew Cab Door Open (Driver Side Crew Cab Door Open)
- PS Crew Cab Door Open (Passenger's Side Crew Cab Door Open)
- DS Body Door Open (Driver Side Body Door Open)
- PS Body Door Open (Passenger's Side Body Door Open)
- Rear Body Door Open
- DS Ladder Rack Down (Driver Side Ladder Rack Down)
- PS Ladder Rack Down (Passenger Side Ladder Rack Down)
- Deck Gun Not Stowed
- Lt Tower Not Stowed (Light Tower Not Stowed)
- Hatch Door Open
- Fold Tank Not Stowed (Fold-A-Tank Not Stowed)
- Aerial Not Stowed (Aerial Device Not Stowed)
- Stabilizer Not Stowed
- Steps Not Stowed
- Handrail Not Stowed

Any other device that is opened, extended, or deployed that creates a hazard or is likely to cause major damage to the apparatus if the apparatus is moved will be displayed as a caution message after the parking brake is disengaged.

### **SWITCH PANELS**

The emergency light switch panel will have a master switch for ease of use plus individual switches for selective control. Each switch panel will contain eight (8) membrane-type switches each rated for one million (1,000,000) cycles. Panels containing less than eight (8) switch assignments will include non-functioning black appliques. Documentation will be provided by the manufacturer indicating the rated cycle life of the switches. The switch panel(s) will be located in the overhead position above the windshield on the driver side overhead to allow for easy access.

The switches will be membrane-type and also act as an integral indicator light. For quick, visual indication the entire surface of the switch will be illuminated white whenever back lighting is activated and illuminated green whenever the switch is active. For ease of use, a two (2)-ply, scratch resistant laser engraved Gravoply label indicating the use of each switch will be placed in the center of the switch. The label will allow light to pass through the letters for ease of use in low light conditions.

### **WIPER CONTROL**

For simple operation and easy reach, the windshield wiper control will be an integral part of the directional light lever located on the steering column. The wiper control will include high and low wiper speed settings, a one (1)-speed intermittent wiper control and windshield washer switch. The control will have a "return to park" provision, which allows the wipers to return to the stored position when the wipers are not in use.

### **SPARE CIRCUIT**

There will be one (1) pair of wires, including a positive and a negative, installed on the apparatus.

The above wires will have the following features:

The positive wire will be connected directly to the battery power.

The negative wire will be connected to ground.

Wires will be protected to 15 amps at 12 volts DC.

Power and ground will terminate one rear engine box for dealer installed camera.

Termination will be with heat shrinkable butt splicing.

Wires will be sized to 125% of the protection.

This circuit(s) may be load managed when the parking brake is set.

### **SPARE CIRCUIT**

There will be one (1) pair of wires, including a positive and a negative, installed on the apparatus.

The above wires will have the following features:

- The positive wire will be connected directly to the battery power
- The negative wire will be connected to ground
- Wires will be protected to 15 amps at 12 volts DC
- Power and ground will terminate officer side front dash for dept. computer
- Termination will be with heat shrinkable butt splicing
- Wires will be sized to 125 percent of the protection

The circuit(s) may be load managed when the parking brake is set.

### **SPARE CIRCUIT**

There will be two (2) pair of wires, including a positive and a negative, installed on the apparatus.

The above wires will have the following features:

The positive wire will be connected directly to the battery power.

The negative wire will be connected to ground.

Wires will be protected to 15 amps at 12 volts DC.

Power and ground will terminate officer side panel 9 side wall to match Job 26500 layout.

Termination will be with 15 amp, power point plug with rubber cover.

Wires will be sized to 125% of the protection.

This circuit(s) may be load managed when the parking brake is set.

### **RADIO WITH CD PLAYER**

There will be a Panasonic™, AM/FM/Weather Band stereo radio with compact disc player and auxiliary input jack installed.

The compact disc stereo radio will be mounted within reach of the officer.

The quantity and location of the speakers will be one (1) pair of 5.25" speakers in the cab and one (1) pair of 5.25" speakers in the crew cab.

The type and location of the antenna will be a roof-mounted rubber antenna located in an open space, on the cab roof.

## **INFORMATION CENTER**

An information center employing a 7.00" diagonal touch screen color LCD display will be encased in an ABS plastic housing.

The information center will have the following specifications:

- Operate in temperatures from -40 to 185 degrees Fahrenheit
- An Optical Gel will be placed between the LCD and protective lens
- Five weather resistant user interface switches
- Grey with black accents
- Sunlight Readable
- Linux operating system
- Minimum of 1000nits rated display
- Display can be changed to an available foreign language
- A LCD display integral to the cab gauge panel will be included as outlined in the cab instrumentation area.
- Programmed to read US Customary

## **GENERAL SCREEN DESIGN**

Where possible, background colors will be used to provide "At a Glance" vehicle information. If information provided on a screen is within acceptable limits, a green background will be used.

If a caution or warning situation arises the following will occur:

- An amber background/text color will indicate a caution condition
- A red background/text color will indicate a warning condition
- The information center will utilize an "Alert Center" to display text messages for audible alarm tones. The text messages will be written to identify the item(s) causing the audible alarm to sound. If more than one (1) text message occurs, the messages will cycle every second until the problem(s) have been resolved. The background color for the "Alert Center" will change to indicate the severity of the "warning" message. If a warning and a caution condition occur simultaneously, the red background color will be shown for all alert center messages.
- A label for each button will exist. The label will indicate the function for each active button for each screen. Buttons that are not utilized on specific screens will have a button label with no text or symbol.

## **HOME/TRANSIT SCREEN**

This screen will display the following:

- Vehicle Mitigation (if equipped)
- Water Level (if equipped)
- Foam Level (if equipped)



- Seat Belt Monitoring Screen
- Tire Pressure Monitoring (if equipped)
- Digital Speedometer
- Active Alarms

### **ON SCENE SCREEN**

This screen will display the following and will be auto activated with pump engaged (if equipped):

- Battery Voltage
- Fuel
- Oil Pressure
- Coolant Temperature
- RPM
- Water Level (if equipped)
- Foam Level (if equipped)
- Foam Concentration (if equipped)
- Water Flow Rate (if equipped)
- Water Used (if equipped)
- Active Alarms

### **VIRTUAL BUTTONS**

There will be four (4) virtual switch panel screens that match the overhead and lower lighting and HVAC switch panels.

### **PAGE SCREEN**

The page screen will display the following and allow the user to progress into other screens for further functionality:

- Diagnostics
  - Faults
    - Listed by order of occurrence
    - Allows to sort by system
  - Interlock
    - Throttle Interlocks
    - Pump Interlocks (if equipped)
    - Aerial Interlocks (if equipped)
    - PTO Interlocks (if equipped)
  - Load Manager
    - A list of items to be load managed will be provided. The list will provide a description of the load.

- The lower the priority numbers the earlier the device will be shed should a low voltage condition occur.
    - The screen will indicate if a load has been shed (disabled) or not shed.
    - "At a glance" color features are utilized on this screen.
  - Systems
    - Command Zone
      - Module type and ID number
      - Module Version
      - Input or output number
      - Circuit number connected to that input or output
      - Status of the input or output
      - Power and Constant Current module diagnostic information
    - Foam (if equipped)
    - Pressure Controller (if equipped)
    - Generator Frequency (if equipped)
  - Live Data
    - General Truck Data
- Maintenance
  - Engine oil and filter
  - Transmission oil and filter
  - Pump oil (if equipped)
  - Foam (if equipped)
  - Aerial (if equipped)
- Setup
  - Clock Setup
  - Date & Time
    - 12 or 24 hour format
    - Set time and date
  - Backlight
    - Daytime
    - Night time
    - Sensitivity
  - Unit Selection
  - Home Screen
  - Virtual Button Setup
  - On Scene Screen Setup
  - Configure Video Mode
    - Set Video Contrast
    - Set Video Color
    - Set Video Tint

- Do Not Move
  - The screen will indicate the approximate location and type of item that is open or is not stowed for travel. The actual status of the following devices will be indicate
    - Driver Side Cab Door
    - Passenger's Side Cab Door
    - Driver Side Crew Cab Door
    - Passenger's Side Crew Cab Door
    - Driver Side Body Doors
    - Passenger's Side Body Doors
    - Rear Body Door(s)
    - Ladder Rack (if applicable)
    - Deck Gun (if applicable)
    - Light Tower (if applicable)
    - Hatch Door (if applicable)
    - Stabilizers (if applicable)
    - Steps (if applicable)
- Notifications
  - View Active Alarms
    - Shows a list of all active alarms including date and time of the occurrence is shown with each alarm
    - Silence Alarms - All alarms are silenced
- Timer Screen
- HVAC (if equipped)
- Tire Information (if equipped)

Button functions and button labels may change with each screen.

### **VEHICLE DATA RECORDER**

A vehicle data recorder (VDR) will be provided. The VDR will be capable of reading and storing vehicle information.

The information stored on the VDR can be downloaded through a USB port mounted in a convenient location determined by cab model. A CD provided with the apparatus will include the programming to download the information from the VDR. A USB cable can be used to connect the VDR to a laptop to retrieve required information.

The vehicle data recorder will be capable of recording the following data via hardwired and/or CAN inputs:

- Vehicle Speed - MPH
- Acceleration - MPH/sec
- Deceleration - MPH/sec

- Engine Speed - RPM
- Engine Throttle Position - % of Full Throttle
- ABS Event - On/Off
- Seat Occupied Status - Yes/No by Position (7-12 Seating Capacity)
- Seat Belt Buckled Status - Yes/No by Position (7-12 Seating Capacity)
- Master Optical Warning Device Switch - On/Off
- Time - 24 Hour Time
- Date - Year/Month/Day

### **HEADSET HANGERS**

There will be six (6) headset hanger(s) installed driver's seat, officer's seat, driver's side outboard forward facing seat, driver's side outboard rear facing seat, passenger's side outboard forward facing seat and passenger's side outboard rear facing seat. The hanger(s) will meet NFPA 1901, Section 14.1.11, requirement for equipment mounting.

### **OPTICOM EMITTER INSTALLATION**

There will be a customer supplied Opticom emitter only, no switching or additional wiring, sent to the apparatus manufacturers preferred installer to be installed center cab roof. Specific shipping requirements will be followed.

### **TWO WAY RADIO INSTALLATION**

There will be one (1) customer supplied two way radio(s) sent to the apparatus manufacturers preferred radio installer to be installed TBD at Pre Build meeting per the shipping document.

No antenna mount or whip will be included in this option.

Specific radio shipping requirements will be followed.

### **RADIO ANTENNA MOUNT**

There will be one (1) standard 1.125", 18 thread antenna-mounting base(s) installed PS seat area TBD on the cab roof with high efficiency, low loss, coaxial cable(s) routed to the radio box. A weatherproof cap will be installed on the mount.

### **ELECTRICAL POWER CONTROL SYSTEM**

The primary power distribution will be located forward of the officer's seating position and be easily accessible while standing on the ground for simplified maintenance and troubleshooting. Additional electrical distribution centers will be provided throughout the vehicle to house the vehicle's electrical power, circuit protection, and control components. The electrical distribution centers will be located strategically throughout the vehicle to minimize wire length. For ease of maintenance, all electrical distribution centers will be easily accessible. All distribution centers containing fuses, circuit breakers and/or relays will be easily accessible.

Distribution centers located throughout the vehicle will contain battery powered studs for supplying customer installed equipment thus providing a lower cost of ownership.

Circuit protection devices, which conform to SAE standards, will be utilized to protect electrical circuits. All circuit protection devices will be rated per NFPA requirements to prevent wire and component damage when subjected to extreme current overload. General protection circuit breakers will be Type-I automatic reset (continuously resetting). When required, automotive type fuses will be utilized to protect electronic equipment. Control relays and solenoid will have a direct current rating of 125 percent of the maximum current for which the circuit is protected per NFPA.

### **SOLID-STATE CONTROL SYSTEM**

A solid-state electronics based control system will be utilized to achieve advanced operation and control of the vehicle components. A fully computerized vehicle network will consist of electronic modules located near their point of use to reduce harness lengths and improve reliability. The control system will comply with SAE J1939-11 recommended practices.

The control system will operate as a master-slave system whereas the main control module instructs all other system components. The system will contain patented Mission Critical software that maintains critical vehicle operations in the unlikely event of a main controller error. The system will utilize a Real Time Operating System (RTOS) fully compliant with OSEK/VDX™ specifications providing a lower cost of ownership.

For increased reliability and simplified use the control system modules will include the following attributes:

- Green LED indicator light for module power
- Red LED indicator light for network communication stability status
- Control system self test at activation and continually throughout vehicle operation
- No moving parts due to transistor logic
- Software logic control for NFPA mandated safety interlocks and indicators
- Integrated electrical system load management without additional components
- Integrated electrical load sequencing system without additional components
- Customized control software to the vehicle's configuration
- Factory and field re programmable to accommodate changes to the vehicle's operating parameters
- Complete operating and troubleshooting manuals
- USB connection to the main control module for advanced troubleshooting

To assure long life and operation in a broad range of environmental conditions, the solid-state control system modules will meet the following specifications:

- Module circuit board will meet SAE J771 specifications

- Operating temperature from -40C to +70C
- Storage temperature from -40C to +70C
- Vibration to 50g

IP67 rated enclosure (Totally protected against dust and also protected against the effect of temporary immersion between 15 centimeters and one (1) meter)

Operating voltage from eight (8) volts to 16 volts DC

The main controller will activate status indicators and audible alarms designed to provide warning of problems before they become critical.

### **CIRCUIT PROTECTION AND CONTROL DIAGRAM**

Copies of all job-specific, computer network input and output (I/O) connections will be provided with each chassis. The sheets will indicate the function of each module connection point, circuit protection information (where applicable), wire numbers, wire colors and load management information.

### **ON-BOARD ADVANCED/VISUAL ELECTRICAL SYSTEM DIAGNOSTICS**

The on-board information center will include the following diagnostic information:

- Text description of active warning or caution alarms
- Simplified warning indicators
- Amber caution indication with intermittent alarm
- Red warning indication with steady tone alarm

All control system modules, with the exception of the main control module, will contain on-board visual diagnostic LEDs that assist in troubleshooting. The LEDs will be enclosed within the sealed, transparent module housing near the face of the module. One LED for each input or output will be provided and will illuminate whenever the respective input or output is active. Color-coded labels within the modules will encompass the LEDs for ease of identification. The LED indicator lights will provide point of use information for reduced troubleshooting time without the need for an additional computer.

### **TECH MODULE WITH WIFI**

An in cab module will provide Wifi wireless interface and data logging capability. (No Exception) The Wifi interface will comply with IEEE 802.11 b/g/n capabilities while communicating at 2.4 Gigahertz. The module will provide an external antenna connection allowing a line of site communication range of up to 300 feet with a roof mounted antenna.

The module will transmit a password protected web page to a wifi enabled device (i.e. most smart phones, tablets or laptops) allowing two levels of user interaction. The firefighter level will allow vehicle monitoring of the vehicle and firefighting systems on the apparatus. The technician level will

allow diagnostic access to inputs and outputs installed on the Command Zone™, control and information system.

The data logging capability will record faults from the engine, transmission, ABS and Command Zone™, control and information systems as they occur. No other data will be recorded at the time the fault occurs. The data logger will provide up to 2 Gigabytes of data storage.

A USB connection will be provided on the Tech Module. It will provide a means to download data logger information and update software in the device.

### **PROGNOSTICS**

A software based vehicle tool will be provided to predict remaining life of the vehicles critical fluid and events (no exceptions).

The system will send automatic indications to the Command Zone, color display and/or wireless enabled device to proactively alert of upcoming service intervals.

Prognostics will include:

- Engine oil and filter
- Transmission oil and filter
- Pump oil (if equipped)
- Foam oil (if equipped)
- Aerial oil and filter (if equipped)

### **ADVANCED DIAGNOSTICS**

An advanced, Windows-based, diagnostic software program will be provided for this control system. The software will provide troubleshooting tools to service technicians equipped with a Windows-based computer or wireless enabled device.

The service and maintenance software will be easy to understand and use and have the ability to view system input/output (I/O) information.

### **INDICATOR LIGHT AND ALARM PROVE-OUT SYSTEM**

A system will be provided which automatically tests basic indicator lights and alarms located on the cab instrument panel.

### **VOLTAGE MONITOR SYSTEM**

A voltage monitoring system will be provided to indicate the status of the battery system connected to the vehicle's electrical load. The system will provide visual and audible warning when the system voltage is below or above optimum levels.

The alarm will activate if the system falls below 11.8 volts DC for more than two (2) minutes.

## **DEDICATED RADIO EQUIPMENT CONNECTION POINTS**

There will be three (3) studs provided in the primary power distribution center located in front of the officer for two-way radio equipment.

- The studs will consist of the following:
- 12-volt 40-amp battery switched power
- 12-volt 60-amp ignition switched power
- 12-volt 60-amp direct battery power

There will also be a 12-volt 100-amp ground stud located in or adjacent to the power distribution center.

## **ENHANCED SOFTWARE**

The solid-state control system will include the following software enhancements:

All perimeter lights and scene lights (where applicable) will be deactivated when the parking brake is released.

Cab and crew cab dome lights will remain on for ten (10) seconds for improved visibility after the doors close. The dome lights will dim after ten (10) seconds or immediately if the vehicle is put into gear.

Cab and crew cab perimeter lights will remain on for ten (10) seconds for improved visibility after the doors close. The dome lights will dim after ten (10) seconds or immediately if the vehicle is put into gear.

## **EMI/RFI PROTECTION**

To prevent erroneous signals from crosstalk contamination and interference, the electrical system will meet, at a minimum, SAE J551/2, thus reducing undesired electromagnetic and radio frequency emissions. An advanced electrical system will be used to ensure radiated and conducted electromagnetic interference (EMI) or radio frequency interference (RFI) emissions are suppressed at their source.

The apparatus will have the ability to operate in the electromagnetic environment typically found in fire ground operations to ensure clean operations. The electrical system will meet, without exceptions, electromagnetic susceptibility conforming to SAE J1113/25 Region 1, Class C EMR for 10KHz-1GHz to 100 Volts/Meter. The vehicle OEM, upon request, will provide EMC testing reports from testing conducted on an entire apparatus and will certify that the vehicle meets SAE J551/2 and SAE J1113/25 Region 1, Class C EMR for 10KHz-1GHz to 100 Volts/Meter requirements. Component and partial (incomplete) vehicle testing is not adequate as overall vehicle design can impact test results and thus is not acceptable by itself.

EMI/RFI susceptibility will be controlled by applying appropriate circuit designs and shielding. The electrical system will be designed for full compatibility with low-level control signals and high-powered two-way radio communication systems. Harness and cable routing will be given careful attention to minimize the potential for conducting and radiated EMI/RFI susceptibility.



## **ELECTRICAL**

All 12-volt electrical equipment installed by the apparatus manufacturer will conform to modern automotive practices. All wiring will be high temperature crosslink type. Wiring will be run, in loom or conduit, where exposed and have grommets where wire passes through sheet metal. Automatic reset circuit breakers will be provided which conform to SAE Standards. Wiring will be color, function and number coded. Function and number codes will be continuously imprinted on all wiring harness conductors at 2.00" intervals. Exterior exposed wire connectors will be positive locking, and environmentally sealed to withstand elements such as temperature extremes, moisture and automotive fluids.

Electrical wiring and equipment will be installed utilizing the following guidelines:

1. All holes made in the roof will be caulked with silicon, rope caulk is not acceptable. Large fender washers, liberally caulked, will be used when fastening equipment to the underside of the cab roof.
2. Any electrical component that is installed in an exposed area will be mounted in a manner that will not allow moisture to accumulate in it. Exposed area will be defined as any location outside of the cab or body.
3. Electrical components designed to be removed for maintenance will not be fastened with nuts and bolts. Metal screws will be used in mounting these devices. Also a coil of wire will be provided behind the appliance to allow them to be pulled away from mounting area for inspection and service work.
4. Corrosion preventative compound will be applied to all terminal plugs located outside of the cab or body. All non-waterproof connections will require this compound in the plug to prevent corrosion and for easy separation (of the plug).
5. All lights that have their sockets in a weather exposed area will have corrosion preventative compound added to the socket terminal area.
6. All electrical terminals in exposed areas will have silicon (1890) applied completely over the metal portion of the terminal.

All lights and reflectors, required to comply with Federal Motor Vehicle Safety Standard #108, will be furnished. Rear identification lights will be recessed mounted for protection. Lights and wiring mounted in the rear bulkheads will be protected from damage by installing a false bulkhead inside the rear compartments.

An operational test will be conducted to ensure that any equipment that is permanently attached to the electrical system is properly connected and in working order.

The results of the tests will be recorded and provided to the purchaser at time of delivery.

## **BATTERY SYSTEM**

There will be four (4) 12 volt Exide®, Model 31S950X3W, batteries that include the following features will be provided:

- 950 CCA, cold cranking amps
- 190 amp reserve capacity
- High cycle
- Group 31
- Rating of 3800 CCA at 0 degrees Fahrenheit
- 760 minutes of reserve capacity
- Threaded stainless steel studs

Each battery case will be a black polypropylene material with a vertically ribbed container for increased vibration resistance. The cover will be manifold vented with a central venting location to allow a 45 degree tilt capacity.

The inside of each battery will consist of a "maintenance free" grid construction with poly wrapped separators and a flooded epoxy bottom anchoring for maximum vibration resistance.

### **BATTERY SYSTEM**

There will be a single starting system with an ignition switch and starter button provided and located on the cab instrument panel.

### **MASTER BATTERY SWITCH**

There will be a master battery switch provided within the cab within easy reach of the driver to activate the battery system.

An indicator light will be provided on the instrument panel to notify the driver of the status of the battery system.

### **BATTERY COMPARTMENTS**

The batteries will be stored in well-ventilated compartments that are located under the cab and bolted directly to the chassis frame. The battery compartments will be constructed of 3/16" steel plate and be designed to accommodate a maximum of three (3) group 31 batteries in each compartment. The compartments will include formed fit heavy-duty roto-molded polyethylene battery tray inserts with drains on each side of the frame rails. The batteries will be mounted inside of the roto-molded trays.

### **JUMPER STUDS**

One (1) set of battery jumper studs with plastic color-coded covers will be installed on the battery box on the driver's side. This will allow enough room for easy jumper cable access.

### **BATTERY CHARGER**

There will be an IOTA™, Model DSL 75, battery charger with IQ4, controller provided.

The battery charger will be wired to the AC shoreline inlet through an AC receptacle adjacent to this battery charger.

There will be a Kussmaul™, Model #091-94-12, remote indicator included.

The battery charger will be located in the left body compartment mounted on the left wall as high as possible.

The battery charger indicator will be located behind the driver's door on the outside of the cab.

### **KUSSMAUL AUTO EJECT FOR SHORELINE**

There will be one (1) Kussmaul Model 091-20WP-120, 20 amp 120 volt AC shoreline inlet(s) provided to operate the dedicated 120 volt AC circuits on the apparatus.

The shoreline inlet(s) will include red weatherproof flip up cover(s).

There will be a release solenoid wired to the vehicle's starter to eject the AC connector when the engine is starting.

The shoreline(s) will be connected to battery charger.

There will be a mating connector body supplied with the loose equipment.

There will be a label installed near the inlet(s) that state the following:

- Line Voltage
- Current Rating (amps)
- Phase
- Frequency

The shoreline receptacle will be located on the driver side of cab, above wheel.

### **ALTERNATOR**

A Leece-Neville, Model BLP4004H, alternator will be provided. It will have a rated output current of 350 amp as measured by SAE method J56. The alternator will feature an integral, self diagnostic regulator and rectifier. The alternator will be connected to the power and ground distribution system with heavy-duty cables sized to carry the full rated alternator output.

### **ELECTRONIC LOAD MANAGER**

An electronic load management (ELM) system will be provided that monitors the vehicles 12-volt electrical system, automatically reducing the electrical load in the event of a low voltage condition, and automatically restoring the shed electrical loads when a low voltage condition expires. This ensures the integrity of the electrical system.

For improved reliability and ease of use, the load manager system will be an integral part of the vehicle's solid state control system requiring no additional components to perform load management tasks. Load management systems which require additional components will not be allowed.

The system will include the following features:

- System voltage monitoring.
- A shed load will remain inactive for a minimum of five minutes to prevent the load from cycling on and off.
- Sixteen available electronic load shedding levels.
- Priority levels can be set for individual outputs.
- High Idle to activate before any electric loads are shed and deactivate with the service brake.
  - If enabled:
    - "Load Man Hi-Idle On" will display on the information center.
    - Hi-Idle will not activate until 30 seconds after engine start up.
- Individual switch "on" indicator to flash when the particular load has been shed.
- The information center indicates system voltage.

The information center, where applicable, includes a "Load Manager" screen indicating the following:

- Load managed items list, with priority levels and item condition.
- Individual load managed item condition:
  - ON = not shed
  - SHED = shed

### **SEQUENCER**

A sequencer will be provided that automatically activates and deactivates vehicle loads in a preset sequence thereby protecting the alternator from power surges. This sequencer operation will allow a gradual increase or decrease in alternator output, rather than loading or dumping the entire 12 volt load to prolong the life of the alternator.

For improved reliability and ease of use, the load sequencing system will be an integral part of the vehicle's solid state control system requiring no additional components to perform load sequencing tasks. Load sequencing systems which require additional components will not be allowed.

Emergency light sequencing will operate in conjunction with the emergency master light switch. When the emergency master switch is activated, the emergency lights will be activated one by one at half-second intervals. Sequenced emergency light switch indicators will flash while waiting for activation.

When the emergency master switch is deactivated, the sequencer will deactivate the warning light loads in the reverse order.

Sequencing of the following items will also occur, in conjunction with the ignition switch, at half-second intervals:

- Cab Heater and Air Conditioning
- Crew Cab Heater (if applicable)
- Crew Cab Air Conditioning (if applicable)
- Exhaust Fans (if applicable)

- Third Evaporator (if applicable)

### **HEADLIGHTS**

There will be four (4) JW Speaker Evolution, Model 8630, 5.60" round LED lights with polycarbonate lenses mounted in the front chrome trim housing on each side of the cab grille:

- One (1) part number 0549911, low and high beam installed in the outside position on the driver's side.
- One (1) part number 0549911, low and high beam installed in the inside position on the driver's side.
- One (1) part number 0549211, low and high beam installed in the inside position on the passenger's side.
- One (1) part number 0549211, low and high beam installed in the outside position on the passenger's side.

### **DIRECTIONAL LIGHTS**

There will be two (2) Whelen 600® series, LED combination directional/marker lights provided. The lights will be located on the outside cab corners, next to the headlights.

The color of the lenses will be the same color as the LED's.

### **INTERMEDIATE LIGHT**

There will be two (2) Truck-Lite®, Model 60115Y, amber LED lights furnished, one (1) each side, horizontally in the rear fender panel. The light will double as a turn signal and marker light.

A stainless steel trim will be included with this installation.

### **CAB CLEARANCE/MARKER/ID LIGHTS**

There will be seven (7) amber LED lights provided to indicate the presence and overall width of the vehicle in the following locations:

- Three (3) amber LED identification lights will be installed in the center of the cab above the windshield.
- Two (2) amber LED clearance lights will be installed, one (1) on each outboard side of the cab above the windshield.
- Two (2) amber LED marker lights will be installed, one (1) on each side above the cab doors.

### **REAR CLEARANCE/MARKER/ID LIGHTING**

There will be three (3) Truck-Lite®, Model 26250R, LED lights used as identification lights located at the rear of the apparatus per the following:

- As close as practical to the vertical centerline

- Centers spaced not less than 6.00" or more than 12.00" apart
- Red in color
- All at the same height

There will be two (2) Truck-Lite, Model 26250R, LED lights installed at the rear of the apparatus used as clearance lights located at the rear of the apparatus per the following:

- To indicate the overall width of the vehicle
- One (1) each side of the vertical centerline
- As near the top as practical
- Red in color
- To be visible from the rear
- All at the same height

There will be two (2) Truck-Lite, Model 26250R, LED lights installed on the side of the apparatus as marker lights as close to the rear as practical per the following:

- To indicate the overall length of the vehicle
- One (1) each side of the vertical centerline
- As near the top as practical
- Red in color
- To be visible from the side
- All at the same height

There will be two (2) red reflectors located on the rear of the truck facing to the rear. One (1) each side, as far to the outside as practical, at a minimum of 15.00", but no more than 60.00", above the ground.

There will be two (2) red reflectors located on the side of the truck facing to the side. One (1) each side, as far to the rear as practical, at a minimum of 15.00", but no more than 60.00", above the ground.

Per FMVSS 108 and CMVSS 108 requirements.

### **REAR FMVSS LIGHTING**

The rear stop/tail and directional LED lighting will consist of the following:

- Two (2) Whelen®, Model M6BTT, red LED stop/tail lights
- Two (2) Whelen, Model M6T, amber LED arrow turn lights

The lights shall be provided with color lenses.

The lights will be mounted in a polished combination housing.

There will be two (2) Whelen Model M6BUW, LED backup lights provided in the tail light housing.

### **LICENSE PLATE BRACKET**

There will be one (1) license plate bracket mounted on the rear of the body.

A white LED light will illuminate the license plate. A polished stainless steel light shield will be provided over the light that will direct illumination downward, preventing white light to the rear.

### **LIGHTING BEZEL**

There will be two (2) Whelen, Model M6FCV4P, four (4) place chromed ABS housings with Pierce logos provided for the rear M6 series stop/tail, directional, back up, scene lights or warning lights.

### **BACK-UP ALARM**

A PRECO, Model 1040, solid-state electronic audible back-up alarm that actuates when the truck is shifted into reverse will be provided. The device will sound at 60 pulses per minute and automatically adjust its volume to maintain a minimum ten (10) dBA above surrounding environmental noise levels.

### **CAB PERIMETER SCENE LIGHTS**

There will be four (4) Amdor LumaBar H2O, Model AY-9500-020, 20.00" white LED strip lights provided, one (1) for each cab door.

These lights will be activated automatically when the battery switch is on and the exit doors are opened or by the same means as the body perimeter scene lights.

### **PUMP HOUSE PERIMETER LIGHTS**

There will be two (2) Truck-Lite, Model 6060C, 6.00" oval LED 12 volt DC weatherproof lights with grommets provided under the pump panel running boards, one (1) each side.

The lights will be controlled by the same means as the body perimeter lights.

### **BODY PERIMETER SCENE LIGHTS**

There will be two (2) Truck-Lite, Model 6060C, 6.00" x 2.00" oval LED lights with Model 60700, grommets provided under at the rear step area of the body, one (1) each side shining to the rear.

The perimeter scene lights will be activated when the parking brake is applied.

### **STEP LIGHTS**

There will be two (2) white LED step lights will be provided at the rear to illuminate the tailboard/step area.

In order to ensure exceptional illumination, each light will provide a minimum of 25 foot-candles (fc) covering an entire 15" x 15" square placed ten (10) inches below the light and a minimum of 1.5 fc covering an entire 30" x 30" square at the same ten (10) inch distance below the light.

These step lights will be actuated with the perimeter scene lights.

All other steps on the apparatus will be illuminated per the current edition of NFPA 1901.

## **12 VOLT LIGHTING**

There will be one (1) Whelen Model PFP2P, 12 volt DC LED dual floodlight(s) installed on the apparatus.

The painted parts of this light assembly to be white.

The lights will be installed driver side behind cab.

The light(s) to be installed on a side body/surface mount push-up pole(s).

The length of the outside pole to be 12.00".

The inside pole length to be 57.00" long or as long as practical to fit in the location selected.

The light pole(s) to be installed without handle holder(s).

The lights will be controlled by the following:

- a switch at the driver's side switch panel.
- no additional switch location.
- no additional switch location.
- no additional switch location.

These light(s) may be load managed when the parking brake is applied.

## **12 VOLT LIGHTING**

There will be one (1) Whelen Model PFP2P, 12 volt DC LED dual floodlight(s) installed on the apparatus.

The painted parts of this light assembly to be white.

The lights will be installed passenger side behind cab.

The light(s) to be installed on a side body/surface mount push-up pole(s).

The length of the outside pole to be 12.00".

The inside pole length to be 57.00" long or as long as practical to fit in the location selected.

The light pole(s) to be installed without handle holder(s).

The lights will be controlled by the following:

- a switch at the driver's side switch panel.
- no additional switch location.
- no additional switch location.
- no additional switch location.



These light(s) may be load managed when the parking brake is applied.

### **12 VOLT LIGHTING**

There will be one (1) Whelen® Pioneer™, Model PCP2\*, 12 volt LED combination spot/flood light(s) provided on the front visor, centered.

The painted parts of this light assembly to be white.

The light(s) will be controlled by the following:

- a switch at the driver's side switch panel
- no additional switch location
- no additional switch location

These light(s) may be load managed when the parking brake is set.

### **REAR WORK LIGHTS**

There will be one (1) pair of Whelen, Model PELCC white 12 volt DC LED scene lights installed at the rear of the body to the outside of the rear compartment. The lights will be directed down ward by a 40 degree angle and mounted with a chrome flange.

The lights will be controlled by a control from a switch at the rear of the truck.

### **WATER TANK**

Booster tank will have a capacity of 750 gallons and be constructed of UV stabilized ultra high impact polypropylene plastic by a manufacturer with a minimum of 20 years experience building tanks, is ISO 9001:2000 certified in all its manufacturing facilities, and has over 50,000 tanks in service.

The booster tank will be a form-fitting design that serves to keep the tank height as low as possible. The tank will be no wider than 39.00" at the base to allow for greater compartment depth and no wider than 53.00" at the top.

Tank joints and seams will be nitrogen welded inside and out.

Tank will be baffled in accordance with NFPA Bulletin 1901 requirements.

Baffles will have vent openings at both the top and bottom to permit movement of air and water between compartments.

Longitudinal partitions will be constructed of .38" polypropylene plastic and will extend from the bottom of the tank through the top cover to allow for positive welding.

Transverse partitions will extend from 4.00" off the bottom of the tank to the underside of the top cover.

All partitions will interlock and will be welded to the tank bottom and sides.

Tank top will be constructed of .50" polypropylene. It will be recessed .38" and will be welded to the tank sides and the longitudinal partitions.

Tank top will be sufficiently supported to keep it rigid during fast filling conditions.

Construction will include 2.00" polypropylene dowels spaced no more than 30.00" apart and welded to the transverse partitions. Two (2) of the dowels will be drilled and tapped (.50" diameter, 13.00" deep) to accommodate lifting eyes.

A sump that is 8.00" long x 8.00" wide x 6.00" deep will be provided at the bottom of the water tank.

Sump will include a drain plug and the tank outlet.

Tank will be installed in a fabricated cradle assembly constructed of structural steel.

Sufficient crossmembers will be provided to properly support bottom of tank. Crossmembers will be constructed of steel bar channel or rectangular tubing.

Tank will "float" in cradle to avoid torsional stress caused by chassis frame flexing. Rubber cushions, .50" thick x 3.00" wide, will be placed on all horizontal surfaces that the tank rests on.

Stops or other provision will be provided to prevent an empty tank from bouncing excessively while moving vehicle.

Mounting system will be approved by the tank manufacturer.

Fill tower will be constructed of .50" polypropylene and will be a minimum of 8.00" wide x 14.00" long.

Fill tower will be furnished with a .25" thick polypropylene screen and a hinged cover.

An overflow pipe, constructed of 4.00" schedule 40 polypropylene, will be installed approximately halfway down the fill tower and extend through the water tank and exit to the rear of the rear axle.

The water tank fill dome will be located Locate at Pre Build for best location.

Two (2) sleeves will be provided in the water tank for a 3.00" pipe to the rear.

### **BODY HEIGHT**

The height of the body will be 89.00" from the bottom of the body to the top of the body.

### **HOSE BED**

The hose bed will be fabricated of .125"-5052 aluminum with a nominal 38,000 psi tensile strength.

Flooring of the hose bed will be removable aluminum grating with the top surface corrugated to aid in hose aeration. The grating slats will be a minimum of 0.50" x 4.50" with spacing between slats for hose ventilation.

Hose bed will accommodate 1600' 3" and 400' 2 1/2".

### **HOSE BED DIVIDER**

Three (3) adjustable hosebed dividers will be furnished for separating hose.

Each divider will be constructed of a .125" brushed aluminum sheet fitted and fastened into a slotted, 1.50" diameter radiused extrusion along the top, bottom, and rear edge.

Divider will be fully adjustable by sliding in tracks, located at the front and rear of the hose bed.

Divider will be held in place by tightening bolts, at each end.

Acorn nuts will be installed on all bolts in the hose bed which have exposed threads.

### **HOSE BED HOSE RESTRAINT**

The hose in the hose bed will be restrained by a black nylon Velcro® strap at the top of the hosebed. At the rear of the hose bed, 2.00" black nylon webbing with a 1.50" x 4.00" box pattern will attach at the top rear outside corners with seat belt buckle fasteners. The webbing will have straps connected with seat belt buckle fasteners located at the rear body sheet below the hose bed.

One (1) additional adjustable track will be provided at the cross divider in the hosebed. The track will be located mid-height between the standard tracks with the hosebed dividers bolted to the track.

The driver side hose bed side sheet will be moved out to the inboard edge of the body compartment.

The passenger side hose bed side sheet will be moved out to the inboard edge of the body compartment.

### **HOSEBED HOSE RESTRAINT**

A red hosebed cover will be furnished with Lift-a-dot fasteners at the front and Lift-a-dot fasteners on the sides. There will be 1.00" cam buckle fasteners at the bottom of the rear body sheet below the hosebed. The flap at the rear will be lead shot weighted.

### **RUNNING BOARDS**

A running board will be provided on each side of the front body to allow access to the backboard/crosslay storage area. The running boards will be designed with a grip pattern punched into .125" bright aluminum treadplate material providing support, slip resistance, and drainage.

### **TAILBOARD**

The tailboard will be constructed of .125" bright aluminum treadplate and spaced .50" from the body, as well as supported by a structural steel assembly.

The tailboard area will be 16.00" deep and full width of the body. The outboard sides of the tailboard will be angled at 45 degrees beginning at the point where the body meets the tailboard at the outboard edge angling rearward to the rear edge of the tailboard.

The exterior side will be flanged down and in for increased rigidity of tailboard structure.

## **REAR WALL, BODY MATERIAL, PUC**

The rear wall will be smooth and the same material as the body.

The rear wall body material will be painted. Unpainted aluminum overlays will be provided to allow for chevron application and to provide continuously smooth rear wall panels.

The outboard edges of the rear wall will be trimmed in polished stainless steel.

## **TOW BAR**

A tow bar will be installed under the tailboard at center of truck.

Tow bar will be fabricated of 1.00" CRS bar rolled into a 3.00" radius.

Tow bar assembly will be constructed of .38" structural angle. When force is applied to the bar, it will be transmitted to the frame rail.

Tow bar assembly will be designed and positioned to allow up to a 30-degree upward angled pull of 17,000 lb, or a 20,000 lb straight horizontal pull in line with the centerline of the vehicle.

Tow bar design will have been fully tested and evaluated using strain gauge testing and finite element analysis techniques.

## **COMPARTMENTATION**

The apparatus body will be built of aluminum construction using a minimum of .125" thick, 5052-H32 aluminum.

The body panel assembly will be constructed in a fixture and consist of formed sheet metal for the front and rear bulkheads, door frames, floors, ceilings, and back walls. These parts will be welded together to ensure greatest longevity with no visible welds in compartment interior.

Welded construction will consist of 1.00" x .38" engineered plug weld holes that control the size, location, and the amount of weld required. The bodies will be assembled and welded from engineered prints that call out the size, location, and type of weld required.

In structural areas the sheet metal components will have flanges for welding. No butt joints will be allowed. Gussets and support posts will be provided for additional strength where needed.

The fender panel will be an integral part of the complete welded body assembly. All light and compartment holes are pre punched prior to construction to provide accuracy and rounded corners to prevent stress risers in the material.

Circular fender liners will be provided. For prevention of paint chips and ease of suspension maintenance the fender liners will be formed from brush finished 304L stainless steel, be unpainted, and removable for suspension maintenance.

Compartment flooring will be of the sweep out design with the floor minimum of 1.00" higher than the compartment door lip.

Drip protection will be provided above the doors by means of aluminum extrusion, or formed bright aluminum treadplate.

The top of the compartment will be sheet metal and covered with bright aluminum treadplate rolled over the edges on the front, and rear. These covers will have the corners welded.

The aluminum treadplate covers will not make up the ceiling of the compartment.

All screws and bolts, which are not Grade 8, will be stainless steel and where they protrude into a compartment will have acorn nuts on the ends to prevent injury.

### **UNDERBODY SUPPORT SYSTEM**

Due to the severe loading requirements of this pumper a method of body and compartment support suitable for the intended load will be provided.

The backbone of the body support system will begin with the chassis frame rails which is the strongest component of the chassis and is designed for sustaining maximum loads. The support system will include lateral frame rail extensions that are formed from .375" 80k high strength steel and bolted to the chassis frame rails with .625" diameter Grade 8 bolts.

The vertical and horizontal members of the frame rail extensions are to be reinforced with welded gussets and extend to the outside edge of the body. The lateral frame extensions will be electro-coated for superior corrosion resistance.

The floating substructure will be separated from the lateral frame extensions with neoprene elastomer isolators. These isolators will reduce the natural flex stress of the chassis from being transmitted to the body, and absorb road shock and vibration.

The isolators will have a broad load range, proven viability in vehicular applications, be of a fail safe design and allow for all necessary movement in three (3) transitional and rotational modes.

The neoprene isolators will be installed in a modified V three (3)-point mounting pattern to reduce the natural flex of the chassis being transmitted to the body. Two (2) 3.50" diameter isolators are provided at the front of the body near the centerline of the vehicle above the chassis frame. A minimum of eight (8) - 2.55" diameter isolators will be provided, two (2) under each front compartment and two (2) under each rear side compartment. A minimum of four (4) 3.50" diameter isolators will be provided under the rear compartment.

A design with body compartments simply hanging/sitting on the chassis in an unsupported (cantilever) fashion will not be acceptable.

### **AGGRESSIVE WALKING SURFACE**

All exterior surfaces designated as stepping, standing, and walking areas will comply with the required average slip resistance of the current NFPA standards. Documentation of the material meeting the standard will be provided at time of delivery.

### **LOUVERS**

All body compartments will have a minimum of one (1) set of automotive style, dust resistant louvers pressed into a wall. The louvers will incorporate a one (1)-way rubber valve that provides airflow out of the compartment and prevents water and dirt from gaining access to the compartment. Compartments over the wheel will not have louvers.

### **TESTING OF BODY DESIGN**

Body structural analysis will be fully tested. Proven engineering and test techniques such as finite element analysis and strain gauging have been performed with special attention given to fatigue life and structural integrity of the body and substructure.

The body will be tested while loaded to its greatest in-service weight.

The criteria used during the testing procedure will include:

- Raising opposite corners of the vehicle tires 9.00" to simulate the twisting a truck may experience when driving over a curb.
- Making a 90 degree turn, while driving at 20 mph to simulate aggressive driving conditions.
- Driving the vehicle on at 35 mph on a washboard road.
- Driving the vehicle at 55 mph on a smooth road.
- Accelerating the vehicle fully, until reaching the approximate speed of 45 mph on rough pavement.

Evidence of the actual testing techniques will be made available upon request.

FEA will have been performed on all substructure components.

### **COMPARTMENTATION, DRIVER'S SIDE**

A full height, roll-up door compartment ahead of the rear wheels will be provided. The pump operator's panel will be located in this compartment. The interior dimensions of this compartment will be 50.00" wide x 53.50" high x 25.88" deep. The area behind the roll up door spool will be notched for exterior storage or larger capacity water tank tee. The depth of the compartment will be calculated with the compartment door closed. The compartment interior will be fully open from the compartment ceiling to the compartment floor and designed so that no permanent dividers are required between the upper and lower sections. The clear door opening of this compartment will be 47.00" wide x 53.50" high.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

A roll-up door compartment over the rear wheels will be provided. The interior dimensions of this compartment will be 60.00" wide x 22.75" high x 25.88" deep. The area behind the roll up door spool will be notched for exterior storage or larger capacity water tank tee. The depth of the compartment will be calculated with the compartment door closed. The clear door opening of this compartment will be 57.00" wide x 22.75" high.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

A full height, roll-up door compartment behind the rear wheels will be provided. The interior dimensions of this compartment will be 52.00" wide x 54.50" high x 25.88" deep. The area behind the roll up door spool will be notched for exterior storage or larger capacity water tank tee. The depth of the compartment will be calculated with the compartment door closed. The compartment interior will be fully open from the compartment ceiling to the compartment floor and designed so that no permanent dividers are required between the upper and lower sections. The clear door opening of this compartment will be 49.00" wide x 54.50" high.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

All compartments will include a drip pan below the roll of the door.

#### **COMPARTMENTATION, PASSENGER'S SIDE**

A full height, jump off compartment with a roll-up door ahead of the rear wheels will be provided, as convenient large storage compartment for often used items for the crew. The interior dimensions of this compartment will be 50.00" wide x 54.50" high x 25.88" deep. The area behind the roll up door spool will be notched for exterior storage or larger capacity water tank tee. The depth of the compartment will be calculated with the compartment door closed. The compartment interior will be fully open from the compartment ceiling to the compartment floor and designed so that no permanent dividers are required between the upper and lower sections. The clear door opening of this compartment will be 47.00" wide x 54.50" high.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

A roll-up door compartment over the rear wheels will be provided. The interior dimensions of this compartment will be 60.00" wide x 23.00" high x 25.88" deep. The area behind the roll up door spool will be notched for exterior storage or larger capacity water tank tee. The depth of the compartment will be calculated with the compartment door closed. The clear door opening of this compartment will be 57.00" wide x 23.00" high.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

A full height, roll-up door compartment behind the rear wheels will be provided. The interior dimensions of this compartment will be 52.00" wide x 54.50" high x 25.88" deep. The area behind the roll up door spool will be notched for exterior storage or larger capacity water tank tee. The depth of the compartment will be calculated with the compartment door closed. The compartment interior will be fully open from the compartment ceiling to the compartment floor and designed so that no permanent dividers are required between the upper and lower sections. The clear door opening of this compartment will be 49.00" wide x 54.50" high.

Closing of the door will not require releasing, unlocking, or unlatching any mechanism and will easily be accomplished with one hand.

All compartments will include a drip pan below the roll of the door.

### **ROLLUP DOOR, SIDE COMPARTMENTS**

There will be six (6) compartment doors installed on the side compartments. The doors will be double faced aluminum construction, painted one (1) color to match the lower portion of the body and manufactured by A&A Manufacturing (Gortite).

Lath sections will be an interlocking rib design and will be individually replaceable without complete disassembly of door.

Between each slat at the pivoting joint will be a PVC inner seal to prevent metal to metal contact and prevent dirt or moisture from entering the compartments. Seals will allow door to operate in extreme temperatures ranging from plus 180 to minus 40 degrees Fahrenheit. Side, top and bottom seals will be provided to resist ingress of dirt and weather and be made of Santoprene.

All hinges, barrel clips and end pieces will be nylon 66. All nylon components will withstand temperatures from plus 300 to minus 40 degrees Fahrenheit.

A polished stainless steel lift bar to be provided for each roll-up door. Lift bar will be located at the bottom of door and have latches on the outer extrusion of the doors frame. A ledge will be supplied over lift bar for additional area to aid in closing the door.

Doors will be constructed from an aluminum box section. The exterior surface of each slat will be flat. The interior surfaces will be concave to provide strength and prevent loose equipment from jamming the door from inside.

To conserve space in the compartments, the spring roller assembly will not exceed 3.00" in diameter.

The header for the rollup door assembly will not exceed 4.00".

A heavy-duty magnetic switch will be used for control of open compartment door warning lights.



### **COMPARTMENTATION, REAR**

A roll-up door compartment above the rear tailboard shall be provided.

Interior dimensions of this compartment shall be approximately 36.75" wide x 42.38" high x 25.88" deep in the lower 33.75" of height and 15.75" deep in the remaining upper portion. Depth of the compartment shall be calculated with the compartment door closed.

A removable access panel shall be furnished on the back wall of the compartment.

Rear compartment shall be open to the rear side compartments. The transverse opening will be a minimum of approximately 22.00" wide x 28.75" high.

Clear door opening of this compartment shall be 33.50" wide x 33.75" high.

Closing of the door shall not require releasing, unlocking, or unlatching any mechanism and shall easily be accomplished with one hand.

### **ROLL-UP DOOR, REAR COMPARTMENT**

The rear compartment will have a roll-up door. The door will be double faced aluminum construction, an anodized satin finish and manufactured by A&A Manufacturing (Gortite).

Lath sections will be an interlocking rib design and will be individually replaceable without complete disassembly of door.

Between each slat at the pivoting joint will be a PVC inner seal to prevent metal to metal contact and prevent dirt or moisture from entering the compartments. Seals will allow door to operate in extreme temperatures ranging from plus 180 to minus 40 degrees Fahrenheit. Side, top and bottom seals will be provided to resist ingress of dirt and weather and be made of Santoprene.

All hinges, barrel clips and end pieces will be nylon 66. All nylon components will withstand temperatures from plus 300 to minus 40 degrees Fahrenheit.

A polished stainless steel lift bar to be provided for each roll-up door. Lift bar will be located at the bottom of door and have latches on the outer extrusion of the doors frame. A ledge will be supplied over lift bar for additional area to aid in closing the door.

Door will be constructed from an aluminum box section. The exterior surface of each slat will be flat. The interior surface will be concave to provide strength and prevent loose equipment from jamming the door from inside.

To conserve space in the compartments, the spring roller assembly will not exceed 3.00" in diameter.

The header for the roll-up door assembly will not exceed 4.00".

A heavy-duty magnetic switch will be used for control of open compartment door warning lights.

### **COMPARTMENT LIGHTING**

There will be seven (7) compartment(s) with two (2) white 12 volt DC LED compartment light strips. The dual light strips will be centered vertically along each side of the door framing. There will be two (2) light strips per compartment. The dual light strips will be in compartment(s): all body compartments.

Any remaining compartments without light strips will have a 6.00" diameter Truck-Lite, Model: 79384 light. Each light will have a number 1076 one filament, two wire bulb.

Opening the compartment door will automatically turn the compartment lighting on.

### **MOUNTING TRACKS**

There will be recessed tracks installed vertically to support the adjustable shelf(s).

Tracks will not protrude into any compartment in order to provide the greatest compartment space and widest shelves possible.

The tracks will be provided in each compartment except for the one that contains the pump operator's panel.

### **ADJUSTABLE SHELVES**

There will be eight (8) shelves, with a capacity of 500 lb provided. The shelf construction will consist of .188" thick aluminum with 2.00" sides. Each shelf will as wide and as deep as the compartment space will allow. Each shelf will be painted spatter gray.

Each shelf will be infinitely adjustable by means of a threaded fastener, which slides in a track.

The shelves will be held in place by .12" thick stamped plated brackets and bolts.

The location will be (3) three in D3, (2) two upper & (1) one lower, (2) two in D1, (2) two in P1 upper, (1) one P2.

### **SLIDE-OUT FLOOR MOUNTED TRAY**

There will be three (3) floor mounted slide-out tray(s) with 2.00" sides provided in R1, P1, & D1. Each tray will be rated for up to 500lb in the extended position. The tray(s) will be constructed of .19" aluminum with non-welded corners. The finish will be painted to match compartment interior.

There will be two undermount-roller bearing type slides rated at 250lb each provided. The pair of slides will have a safety factor rating of 2.

To ensure years of dependable service, the slides will be coated with a finish that is tested to withstand a minimum of 1,000 hours of salt spray per ASTM B117.

To ensure years of easy operation, the slides will require no more than a 50lb force for push-in or pull-out movement when fully loaded after having been subjected to a 40 hour vibration (shaker) test under full load. The vibration drive file will have been generated from accelerometer data collected from a

heavy truck chassis driven over rough gravel roads in an unloaded condition. Proof of compliance will be provided upon request.

Automatic locks will be provided for both the "in" and "out" positions. The trip mechanism for the locks will be located at the front of the tray for ease of use with a gloved hand.

### **BACKBOARD STORAGE**

Mounting will be provide for two (2) backboard(s) located above the crosslays. The backboard(s) will be enclosed and removable from either side of the truck. The backboard(s) will be 18" x 74" x 3" each.

### **ALUMINUM PEGBOARD**

Two (2) horizontally installed tracks, with .19" aluminum pegboard will be installed on the back wall of one (1) compartments. The holes will be .203" diameter , punched 1.00" on center. The pegboard will be spatter gray painted. The pegboard(s) will be located D2 .

Retainers will be used to mount the pegboard to the tracks.

### **RUB RAIL**

Bottom edge of the side compartments will be trimmed with a bright aluminum extruded rub rail.

Trim will be 3.12" high with 1.50" flanges turned outward for rigidity.

The rub rails will not be an integral part of the body construction, which allows replacement in the event of damage.

Rub rails will be attached with bolts and spaced from the body with isolators that will help to absorb any moderate impact without damaging the body.

### **BODY FENDER CROWNS**

Polished stainless steel fender crowns will be provided around the rear wheel openings.

A brushed stainless steel unpainted fender liner will be provided to avoid paint chipping. The liners will be removable to aid in the maintenance of rear suspension components.

A dielectric barrier will be provided between the fender crown fasteners (screws) and the fender sheet metal to prevent corrosion.

The fender crowns will be held in place with stainless steel screws that thread directly into a composite nut and not directly into the parent body sheet metal to eliminate dissimilar metals contact and greatly reduce the chance for corrosion.

### **HARD SUCTION HOSE**

NFPA 1901, 2009 edition, section 5.7.2 requires a minimum of 20 feet of suction hose or 15 feet of supply hose.

Hose is not on the apparatus as manufactured. The fire department will provide suction or supply hose.

There will be Two (2) lengths of 10' long x 6.00" diameter hose provided and equipped with rocker lug couplings provided on the ends.

### **HOSE TROUGHS**

One (1) trough for a hard suction hose will be installed on top of each high side compartment.

Both troughs will be constructed of aluminum, V-shaped and have chrome plated, quarter turn, spring loaded clamps.

Troughs will be painted to match the body.

### **HANDRAILS**

The handrails will be 1.25" diameter anodized aluminum extrusion, with a ribbed design, to provide a positive gripping surface.

Chrome plated end stanchions will support the handrail. Plastic gaskets will be used between end stanchions and any painted surfaces.

Drain holes will be provided in the bottom of all vertically mounted handrails..

Handrails will be located on the front of the body in positions needed to meet NFPA requirements.

- One (1) vertical handrail, and not less than 29.00" long, will be located on each rear bulkhead.
- Two (2) handrails will be provided mounted on top of the left side sheet forward and on top of the right side sheet forward.

### **AIR BOTTLE STORAGE (DOUBLE)**

A quantity of two (2) air bottle compartments, 15.25" wide x 7.75" tall x 26.00" deep, will be provided on the passenger side forward of the rear wheels and on the passenger side rearward of the rear wheels . A polished stainless steel door with a chrome plated flush lift & turn latch will be provided to contain the air bottle. A dielectric barrier will be provided between the door hinge, hinge fasteners and the body sheet metal.

Inside the compartment, black rubber matting will be provided.

### **AIR BOTTLE HOLDERS**

Two (2) brackets will be provided for mounting air bottles. Each bracket will be a Ziamatic, model UN-6-30-3-SF, and contain a collision restraint strap. It will be mounted on tracks and used for adjusting the location of the bracket within the compartment. The brackets will be installed in compartment in P3 upper on back wall to front of truck.

### **EXTENSION LADDER**

There will be a 24', two-section, aluminum, Duo-Safety, Series 900-A extension ladder provided.

### **ROOF LADDER**

There will be a 14' aluminum, Duo-Safety, Series 775-A roof ladder provided.

### **LADDER STORAGE**

The ladders will be stored inside the upper section of the passenger's side compartments. This ladder rack will reduce the depth of the upper section in the side compartments.

A partition will be installed inside the compartment on the side of the rack to allow for equipment storage and to conceal the ladders.

The ladders will be banked in separate storage troughs.

The ladder storage assembly will be fabricated of stainless steel track channels to aid in loading and removal of ladders.

Rear of the ladder storage area will have a vertically hinged smooth aluminum door with a D-handle latch to contain the ladders.

### **FOLDING LADDER**

One (1) 10.00' aluminum, Series 585-A, Duo-Safety folding ladder will be installed in a U-shaped trough inside the ladder storage compartment.

### **PIKE POLE, 10'**

One (1) pike pole 10' long Akron with a fiberglass I-beam shaped handle, will be provided and located pike pole compartment.

### **PIKE POLE, 8'**

One (1) pike pole, 8' long Nupla with a fiberglass I-beam handle, will be provided and located PS pike pole compt. same as last unit 26500.

### **6 FT PIKE POLE**

There will be one (1) Fire Hooks Unlimited NY roof hook RH-6, 6 foot pike pole(s) with steel handles and pry end provided PS pike pole compartment above ladders.

### **PIKE POLE/FOLDING LADDER COMPARTMENT**

One (1) pike pole compartment will be provided, recessed in the upper, inside part of body compartment on the passenger's side. The compartment will be equipped with two (2) aluminum tubes to hold two (2) pike poles and a stainless steel trough for the folding ladder. The door will be made of smooth aluminum and have a lift and turn latch.

### **PIKE POLE STORAGE**

Aluminum tubing will be used for the storage of four (4) pike poles and will be located in ladder storage compartment. If the head of a pike pole can come in contact with a painted surface, a stainless steel scuffplate will be provided.

### **BELL**

A chrome plated, 12.00" bronze cast bell, complete with an eagle, will be mounted on the passenger's side of the front bumper extension. A rope pull, for the bell, will be installed inside the cab.

### **REAR FOLDING STEPS**

Bright finished, non-skid folding steps with a luminescent coating that is rechargeable from any light source and can hold a charge for up to 24 hours will be provided at the rear. Each step will incorporate an LED light to illuminate the stepping surface. The steps can be used as a hand hold with two openings wide enough for a gloved hand.

Two (2) additional folding steps will be located front of body. The step(s) will be bright finished, non-skid, with a luminescent coating. The luminescent coating is rechargeable from any light source and can hold a charge for up to 24 hours. Each step will incorporate an LED light to illuminate the stepping surface. The step(s) can be used as a hand hold with two openings wide enough for a gloved hand.

### **ADDITIONAL STEP**

An 8.00" deep, full width bright aluminum treadplate step will be provided at the rear of the body.

### **PUMP**

Pump will be a Pierce, low profile, 1500 gpm single stage midship mounted centrifugal type, mounted below the cab. The pump will have a 15 percent reserve capacity to allow for extended time between pump rebuild. To ensure efficient pump/vehicle design the capacity to weight ratio will not be less than 1.5:1.

The pump casing will consist of three (3) discharge outlets, one (1) to each side in line with the impeller and one (1) to the rear. The pump casing will incorporate two (2) water strippers to maintain radial balance.

Pump will be the Class A type.

Pump will be certified to deliver the percentage of rated discharge from draft at pressure indicated below:

- 100 percent of rated capacity at 150 psi net pump pressure
- 70 percent of rated capacity at 200 psi net pump pressure
- 50 percent of rated capacity at 250 psi net pump pressure

The pump will have the capacity to deliver the percentage of rated discharge from a pressurized source as indicated below:

- 135 percent of rated capacity at 100 psi net pump pressure from a 5 psi source

Pump body will be fine-grained gray iron. Pump will incorporate a heater/cooling jacket integral to the pump housing.

The impeller will be high strength vacuum cast bronze alloy accurately machine balanced and splined to a 10 spline stainless steel pump shaft for precision fit, exceptional durability, and efficiency. Double replaceable reverse flow labyrinth type bronze wear ring design will help to minimize end thrust. The impeller will be a twisted vane design to create higher lift.

The pump will include o-ring gaskets throughout the pump.

Deep groove radial type oversize ball bearings will be provided. The bearings will be protected at the openings from road dirt and water with an oil seal and a water slinger.

The pump will have a flat, patterned area on the top of the pump intake wye to allow standing for plumbing maintenance. The main inlet manifold will be 6.00" in diameter and will have a low profile design to facilitate low crosslays and high flows.

For ease of service, the pump housing, intake wye, impeller, mechanical seal, and gear case will be accessible from above the chassis frame by tilting the cab. The intake wyes will be removable without having to remove the main intake casting. Removal of the main inlet wyes will provide access to the impeller, mechanical seal, and wear ring.

The tank to pump line and the primary discharge line will be the only piping required to be removed for overhaul.

For ease of service and overhaul there will be no piping or manifolding located directly over the pump.

### **PUMP MOUNTING**

Pump will be mounted to the chassis frame rails directly below the crew cab, to minimize wheelbase and facilitate service, using rubber isolators in a modified V pattern that include two (2) central mounted isolators located between the frame rails, and one (1) on each side outside the frame rails. The mounting will allow chassis frame rails to flex independently without damage to the fire pump. Each isolator will be 2.55" in total outside diameter and will be rated at 490 lb. The pump will be completely accessible by tilting the cab with no piping located directly above the pump.

### **MECHANICAL SEALS**

Silicon carbide mechanical seals will be provided. The seals will be spring loaded and self-adjusting. The seals will have a minimum thermal conductivity of 126 W/m\*K to run cooler. Seals will have a minimum hardness of 2800 kg/mm<sup>2</sup> to be more resistant to wear, and have thermal expansion characteristics of no more than 4.0 X10<sup>-6</sup>mm/mm\*K to be more resistant to thermal shock.

## **PUMP GEARCASE**

Pump gearcase will be a pressure-lubricated gearcase to cool, lubricate, and filter the oil. The gearcase will include an auxiliary PTO opening. The gearcase will be constructed of lightweight aluminum, and impregnated with resin in accordance to MIL Spec MIL-I-17563. A dipstick, accessible by tilting the cab, will be provided for easy fluid level checks. A filter screen will be provided for long life.

The gearcase will consist of two (2) gears to drive the pump impeller and one (1) for the auxiliary PTO.

The auxiliary PTO opening will provide for the addition of PTO driven accessories.

The pump will be driven through the rear engine power take-off and clutch. The rear engine power take-off drive will be live at all times to allow for pump and roll applications. Rear engine power take-off's allow for high horsepower and torque ratings needed for large pump applications, and is a proven drive system throughout the rugged construction industry.

## **CLUTCH**

Pierce "Sure Shift Technology" will incorporate a heavy-duty electric clutch mounted directly to the front of the pump to engage and disengage the pump without gear clash. The clutch will be a multiple disc design for maximum torque. The clutch will be fully self-adjusting to provide automatic wear compensation, and consistent torque throughout the life of the clutch. Positive engagement and disengagement will be provided through a high efficient and dependable magnetic system to assure superior performance. The clutch will have a 500 lb-ft rating. Clutch will be of a time-tested design used in critical military applications.

## **PUMPING MODE**

Pump will provide for both pump and roll mode and stationary pumping mode.

Stationary pumping mode will be accomplished by stopping the vehicle, setting the parking brake and engaging the water pump switch on the cab switch panel. The transmission will shift to "Neutral" range automatically when the parking brake is set. The "OK to Stationary Pump" indicator will also illuminate when the parking brake is set. If the vehicle is equipped with a foam system or CAFS system, these systems will be engaged from the cab switch panel as well.

Pump and roll mode will be accomplished by the use of the main pump and will not require the use of a secondary pump. Pump and roll mode will use the same operation sequence as stationary pumping mode with a few additional steps. After the vehicle is setup for stationary pumping, the operator will leave the cab and set-up the pump panel to discharge at the desired outlet(s). Upon returning to the cab, the operator will disengage the parking brake. An "OK to Pump & Roll" indicator will illuminate on the cab switch panel. First gear on the transmission gear selector will be selected by the operator for pump and roll operations. The operator as needed will apply the foot throttle. Pump and roll mode will be maintained unless the transmission shifts out of first gear.



Stopping either stationary pumping mode or pump and roll mode will be accomplished by pressing the "Water Pump" switch down to disengage the pump.

### **PUMP SHIFT**

Pump will be engaged in not more than two steps, by simply setting the parking brake, which will automatically put the transmission into neutral, and activating a rocker switch in the cab. Switches in the cab will also allow for water, foam, or CAFS if equipped, and activate the appropriate system to preset parameters. The engagement will provide simple two-step operation, enhance reliability, and completely eliminate gear clash. The shift will include the indicator lights as mandated by NFPA. A direct override switch will be located behind a door in the lower pump operator's panel. The switch will automatically disengage when the door is closed.

As the parking brake is applied, the pump panel throttle will be activated and deactivate the chassis foot throttle for stationary operation.

Pump and roll operation will be available by releasing the parking brake with the pump in the pumping mode. Releasing the parking brake will activate the chassis foot throttle, and deactivate the pump panel throttle. To protect from accidental pump overheating, the pump will automatically disengage when the truck transmission shifts into second gear.

### **TRANSMISSION LOCK UP**

Transmission lock up is not required as transmission will automatically shift to neutral as soon as the parking brake is set.

### **AUXILIARY COOLING SYSTEM**

A supplementary heat exchange cooling system will be provided to allow the use of water from the discharge side of the pump for cooling the engine water. A water-to-coolant heat exchanger will be used.

### **INTAKE RELIEF VALVE**

An Elkhart relief valve will be installed on the suction side of the pump preset at 125 psig.

Relief valve will have a working range of 75 psig to 250 psig.

Outlet will terminate below the frame rails with a 2.50" National Standard hose thread adapter and will have a "do not cap" warning tag.

Control will be located behind an access door at a side pump panel.

### **PRESSURE CONTROLLER**

A Pierce Pressure Governor will be provided. An electric pressure governor will be provided which is capable of automatically maintaining a desired preset discharge pressure in the water pump. When operating in the pressure control mode, the system will automatically maintain the discharge pressure set

by the operator (within the discharge capabilities of the pump and water supply) regardless of flow, within the discharge capacities of the water pump and water supply.

A pressure transducer will be installed in the water discharge of the pump. The transducer continuously monitors pump pressure sending a signal to the Electronic Control Module (ECM).

The governor can be used in two (2) modes of operation, RPM mode and pressure modes.

In the RPM mode, the governor can be activated after vehicle parking brake has been set. When in this mode, the governor will maintain the set engine speed, regardless of engine load (within engine operation capabilities).

In the pressure mode, the governor system can only operate after the fire pump has been engaged and the vehicle parking brake has been set. When in the pressure mode, the pressure controller monitors the pump pressure and varies engine speed to maintain a precise pump pressure. The pressure controller will use a quicker reacting J1939 database for engine control.

A preset feature allows a predetermined pressure or rpm to be set.

A pump cavitation protection feature is also provided which will return the engine to idle should the pump cavitate. Cavitation is sensed by the combination of pump pressure below 30 psi and engine speed above 2000 rpm for more than five (5) seconds.

The throttle will be a vernier style control, with a large control knob for use with a gloved hand. A throttle ready light will be provided adjacent to the throttle control. A large 0.75" RPM display will be provided to be visible at a glance.

Check engine, and stop engine indicator lights will be provided for easy viewing.

Large 0.75" push buttons will be provided for menu, mode, preset, and silence selections.

The water tank level indicator will be incorporated in the pressure governor.

A fuel level indicator will be incorporated in the pressure controller.

A pump hour meter will be incorporated in the pressure controller.

The pressure controller will incorporate monitoring for engine temperature, oil pressure, fuel level alarm, and voltage. Pump monitoring will include, pump gearcase temperature, error codes, diagnostic data, pump service reminders, and time stamped data logging, to allow for fast accurate trouble shooting. It will also notify the driver/engineer of any problems with the engine and the apparatus. Complete understandable messages will be provided in a 20-character display, providing for fewer abbreviations in the messages. An automatic dim feature will be included for night operations.

The pressure controller will include a USB port for easy software upgrades, which can be downloaded through a USB memory stick, eliminating the need for a laptop for software installations.

A complete interactive manual will be provided with the pressure controller.

### **PRIMING PUMP**

Priming pump will be a positive displacement vane type, electrically driven, and conforming to standards outlined in NFPA pamphlet #1901.

One (1) priming control will open the priming valve and start the priming motor.

Primer will be environmentally safe and self lubricating.

### **PUMP MANUALS**

There will be a total of two (2) pump manuals provided by the pump manufacturer and furnished with the apparatus. The manuals will be provided by the pump manufacturer in the form of two (2) CDs. Each manual will cover pump operation, maintenance, and parts.

### **PLUMBING**

All inlet and outlet plumbing, 3.00" and smaller, will be plumbed with either stainless steel pipe or synthetic rubber hose reinforced with high-tensile polyester braid. Small diameter secondary plumbing such as drain lines will be stainless steel, brass or hose.

Where vibration or chassis flexing may damage or loosen piping or where a coupling is required for servicing, the piping will be equipped with victaulic or rubber couplings.

Plumbing manifold bodies will be ductile cast iron or stainless steel.

All lines will drain through a master drain valve or will be equipped with individual drain valves. All individual drain lines for discharges will be extended with a hose to drain below the chassis frame.

All water carrying gauge lines will be of flexible polypropylene tubing.

### **MAIN PUMP INLETS**

A 6.00" pump manifold inlet will be provided on each side of the vehicle. The suction inlets will include removable die cast zinc screens that are designed to provide cathodic protection for the pump, thus reducing corrosion in the pump.

Main pump inlets will not be located on the main operator's panel and will maintain a low connection height by terminating below the top of the chassis frame rail.

### **MAIN PUMP INLET CAP**

The main pump inlets will have National Standard Threads with a long handle chrome cap.

The cap will be the Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

## **VALVES**

All ball valves will be Akron® Brass. The Akron valves will be the 8000 series heavy-duty style with a stainless steel ball and a simple two-seat design. No lubrication or regular maintenance is required on the valve.

Valves will have a **ten (10) year** warranty.

## **LEFT SIDE INLET**

On the left side pump panel will be one (1) - 2.50" auxiliary inlet, terminating in 2.50" National Standard Hose Thread. The auxiliary inlet will be provided with a strainer, chrome swivel and plug.

## **RIGHT SIDE INLET**

On the right side pump panel will be one (1) - 2.50" auxiliary inlet, terminating in 2.50" National Standard Hose Thread. The auxiliary inlet will be provided with a strainer, chrome swivel and plug.

The location of the valve for the two (2) inlets will be recessed behind the pump panel.

## **ANODE, INLET**

A pair of sacrificial zinc anodes will be provided in the water pump inlets to protect the pump from corrosion.

## **INLET CONTROL**

Control for the side auxiliary inlet(s) will be located at the inlet valve.

## **INLET BLEEDER VALVE**

A 0.75" bleeder valve will be provided for each side gated inlet. The valves will be located behind the panel with a swing style handle control extended to the outside of the panel. The handles will be chrome plated and provide a visual indication of valve position. The swing handle will provide an ergonomic position for operating the valve without twisting the wrist and provides excellent leverage. The water discharged by the bleeders will be routed below the chassis frame rails.

## **TANK TO PUMP**

The booster tank will be connected to the intake side of the pump with heavy duty 4.00" piping and a quarter turn 3.00" full flow line valve with the control located at the operator's panel. A rubber coupling will be included in this line to prevent damage from vibration or chassis flexing.

A check valve will be provided in the tank to pump supply line to prevent the possibility of "back filling" the water tank.

## **TANK REFILL**

A 1.50" combination tank refill and pump re-circulation line will be provided, using a quarter-turn full flow ball valve controlled from the pump operator's panel.

### **LEFT SIDE DISCHARGE OUTLETS**

There will be two (2) discharges with a 2.50" valves on the left side of the apparatus, terminating with a 2.50" (M) National Standard hose thread adapter. Discharges will be located below the cab, and will be no higher than the top of the chassis frame rail. Discharges will not be located on the pump operator's panel. Lever controls will be provided at the valve.

### **RIGHT SIDE DISCHARGE OUTLETS**

There will be one (1) discharge outlet with a 2.50" valve on the right side of the apparatus, terminating with a male 2.50" National Standard hose thread adapter. The discharge will be located below the crew cab, and will be no higher than the top of the chassis frame rail.

There will be an Akron® 9325 Navigator Pro electric valve controller provided at the pump panel. The controller unit will be of true position feedback design, requiring no clutches in the motor or current limiting. The controller will be completely sealed with two (2) button open and close valve position capability and a full color LCD display with backlight. In addition to valve position, each controller will include a pressure display.

### **LARGE DIAMETER DISCHARGE OUTLET**

There will be a 4.00" discharge outlet with a 4.00" Akron valve body installed on the right side of the apparatus, terminating with a 4.00" (M) National Standard hose thread. The discharge will be located below the crew cab, and will be no higher than the top of the chassis frame rail.

There will be an Akron 9325 Navigator Pro electric valve controller provided at the pump panel. The controller unit will be of true position feedback design, requiring no clutches in the motor or current limiting. The controller will be completely sealed with two (2) button open and close valve position capability and a full color LCD display with backlight. In addition to valve position, each controller will include a pressure display.

### **FRONT DISCHARGE OUTLET**

There will be one (1) 1.50" discharge outlet piped to the front of the apparatus and located on the top of the left side of the front bumper.

Plumbing will consist of 2.00" piping and flexible hose with a 2.00" ball valve with control at the pump operator's panel. A fabricated weldment made of stainless steel pipe will be used in the plumbing where appropriate. The piping will terminate with a 1.50" NST with 90 degree stainless steel swivel.

There will be Class 1 automatic drains provided at all low points of the piping.

### **REAR DISCHARGE OUTLET**

There will be two (2) discharge outlets piped to the rear of the hose bed, on driver's side, installed so proper clearance is provided for spanner wrenches or adapters. Plumbing will consist of 3.00" piping along with a 2.50" full flow ball valve with the control from the pump operator's panel. Discharge will

terminate with 2.50" NST thread. Discharge piping will be schedule 10 304L welded or formed stainless steel and routed through the water tank.

### **DISCHARGE CAPS**

Chrome plated, rocker lug, caps with chains will be furnished for all side discharge outlets.

The caps will be the Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

### **OUTLET BLEEDERS**

A 0.75" bleeder valve will be provided for each outlet 1.50" or larger. Automatic drain valves are acceptable with some outlets if deemed appropriate with the application.

The valves will be located behind the panel with a swing style handle control extended to the outside of the side pump panel. The handles will be chrome plated and provide a visual indication of valve position. The swing handle will provide an ergonomic position for operating the valve without twisting the wrist and provides excellent leverage. Bleeders will be located at the bottom of the pump panel. They will be properly labeled identifying the discharge they are plumbed in to. The water discharged by the bleeders will be routed below the chassis frame rails.

### **ADDITIONAL RIGHT SIDE OUTLET ELBOWS**

The 2.50" discharge outlets, located on the right side pump panel, will be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) National Standard hose thread, chrome plated, 30 degree elbow.

The elbow will be the Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

### **ADDITIONAL REAR OUTLET ELBOWS**

one (1) discharge outlet 2.50" discharge outlets, located at the rear of the apparatus, will be furnished with a 2.50" (F) National Standard hose thread x 2.50" (M) National Standard hose thread, chrome plated, 45 degree elbow.

The elbow will be the Pierce VLH, which incorporates an exclusive thread design to automatically relieve stored pressure in the line when disconnected.

### **LARGE DIAMETER OUTLET CAP**

The large diameter outlet will have a National Standard hose thread adapter with a 4.00" rocker lug chrome plated cap and chain.

The cap will be the Pierce VLH, which incorporates a patent pending thread design to automatically relieve stored pressure in the line when disconnected.

## **DISCHARGE OUTLET CONTROLS**

The discharge outlets will incorporate a quarter-turn ball valve with the control located at the pump operator's panel. The valve operating mechanism will indicate the position of the valve or an indicator will be provided to show when the valve is closed.

The passenger side discharges will be controlled by an Akron 9325 Navigator Pro electric valve controllers with the manual override located on the passenger side pump panel. The controller unit will be of true position feedback design, requiring no clutches in the motor or current limiting. The controller will be completely sealed with two (2) button open and close valve position capability and a full color LCD display with backlight. In addition to valve position, each controller will include a pressure display.

All other outlets will have manual swing handles that operate in a vertical up and down motion. These handles will be able to lock in place to prevent valve creep under pressure.

## **DELUGE RISER**

A 3.00" deluge riser will be installed above the pump in such a manner that a monitor can be mounted and used effectively. 3.00" piping will be installed securely so no movement develops when the line is charged. A 2.50" gated valve will be installed and controlled at the pump operator's panel. The deluge outlet will flow a minimum 1000 GPM.

## **MONITOR, PROVIDED BY DEALER**

NFPA 1901, 2009 edition, section 11.9.2 requires one (1) pre-connected monitor, rated to discharge a minimum of 1000 GPM, mounted on top of the fire apparatus with a spray or foam nozzle rated at a minimum of 1000 GPM.

The monitor is not on the apparatus as manufactured. The dealer will provide and mount the monitor.

The deluge riser will have male National Pipe Threads for mounting the monitor.

## **CROSSLAY HOSE BEDS**

Two (2) crosslays with 1.50" outlets will be provided. Each bed to be capable of carrying 200 feet of 1.75" double jacketed hose and will be plumbed with 2.00" i.d. schedule 10 304L welded or formed stainless steel pipe and gated with a 2.00" quarter turn ball valve. Threaded pipe will not be acceptable. Crosslays will be low mounted with the bottom of both crosslay trays no more than 11.00" above the frame rails for simple, safe reloading and deployment.

Outlets to be equipped with a 1.50" National Standard hose thread 90-degree swivel located in the hose bed so that hose may be removed from either side of apparatus.

The crosslay controls will be at the pump operator's panel.

A removable tray will be provided for the crosslay hose bed. The crosslay tray will be constructed of black poly to provide a lightweight sturdy tray. Two (2) hand holes will be in the floor and additional

hand holes will be provided in the sides for easy removal and installation from the compartment. The floor of the trays will be perforated to allow for drainage and hose drying. Trays will be held in place by a mechanical spring loaded stainless steel latch that automatically deploys upon loading the trays to hold the trays in place during transit.

Special width trays a minimum of 7.00" inside dimension will be provided.

### **CROSSLAY/DEADLAY HOSE RESTRAINT**

A black 1.00" nylon webbing design with 2.00" box pattern will be provided across each end of two (2) crosslay/deadlay(s) to secure the hose during travel. The webbing will be permanently attached at the front of the crosslay/deadlay bed. Two (2) vertical metal bars the height of the crosslay/deadlay bed will hook onto footman loops at the top of the bed and 1.00" web straps will loop through footman loops located at the bottom of the crosslay/deadlay bed. The straps will attach to the bottom of the bar with a spring clip and hook fastener.

### **FOAM PROPORTIONER**

A foam proportioning system will be provided that is an on demand, automatic proportioning, single point, direct injection system suitable for all types of Class A and B foam concentrates, including the high viscosity (6000 cps), alcohol resistant Class B foams. Operation will be based on direct measurement of water flow, and remain consistent within the specified flows and pressures. The system will automatically balance and proportion foam solution at rates from .1 percent to 9.9 percent regardless of variations in water pressure and flow, up to the maximum rated capacity of the foam concentrate pump.

The design of the system will allow operation from draft, hydrant, or relay operation. This will provide a versatile system to meet the demands at a fire scene.

### **SYSTEM CAPACITY**

The system will have the ability to deliver the following minimum foam solution flow rates that meet or exceed NFPA requirements at a pump rating of 250 psi.

200 gpm @ 6 percent

400 gpm @ 3 percent

1200 gpm @ 1 percent

The foam concentrate setting may be adjusted in .1 percent increments from .1 percent to 9.9 percent. Typical settings are .3 percent, .5 percent and 1.0 percent (The maximum capacity will be limited to the plumbing and water pump capacity).

### **CONTROL SYSTEM**

The system will be equipped with a digital electronic control display located on the pump operators panel. Push button controls will be integrated into the panel to turn the system on/off, control the foam



percentage, direct which foam to use on a multi-tank system, and to set the operation modes (automatic, manual, draft, calibration, or flush).

The percent of injection will have presets for Class A or Class B foam. These presets can be changed at the fire department as desired. The percent of injection will be able to be easily changed at the scene to adjust to changing demands.

In order to minimize the use of abbreviations and interpretations, system information will be displayed on the panel by way of .50 tall LEDs that total 14 characters (two (2) lines of seven (7) each). System on and foam pump on indicator lights will also be included. Information displayed will include mode of operation (automatic, manual, draft, calibration, or flush), foam supply selected (Class A or Class B), water total, foam total, foam percentage, remaining gallons, and time remaining.

The control display will direct a microprocessor, which receives input from the systems water flow meter while also monitoring the position of the foam concentrate pump. The microprocessor will compare the values of the water flow versus the position/rate of the foam pump, to ensure the proportion rate is accurate. One (1) check valve will be installed in the plumbing to prevent foam from contaminating the water pump.

### **LOW LEVEL, FOAM TANK**

The control head will display a warning message when the foam tank in use is below a quarter tank.

### **HYDRAULIC DRIVE SYSTEM**

The foam concentrate pump will be powered by a hydraulic drive system, which is automatically activated, whenever the vehicle water pump is engaged. A system that drives the foam pump via an electric motor will not be acceptable. A large parasitic electric load used to power the foam pump can cause an overload of the chassis electrical system.

Hydraulic oil cooler will be provided to automatically prevent overheating of the hydraulic oil, which is detrimental to system components. The oil/water cooler will be designed to allow continuous system operation without allowing hydraulic oil temperature to exceed the oil specifications.

The hydraulic oil reservoir will be of four (4) gallons minimum capacity and will also be of sufficient size to minimize foaming and be located to facilitate checking oil level or adding oil without spillage or the need to remove access panels.

### **FOAM CONCENTRATE PUMP**

The foam concentrate pump will be of positive displacement, self-priming; linear actuated design, driven by the hydraulic motor. The pump will be constructed of brass body; chrome plated stainless steel shaft, with a stainless steel piston. In order to increase longevity of the pump, no aluminum will be present in its construction.

A relief system will be provided which is designed to protect the drive system components and prevent over pressuring the foam concentrate pump.

The foam concentrate pump will have minimum capacity for 12 gpm with all types of foam concentrates with a viscosity at or below 6000 cps including protein, fluoroprotein, AFFF, FFFP, or AR-AFFF. The system will deliver only the amount of foam concentrate flow required, without recirculating foam back to the storage tank. Recirculating foam concentrate back to the storage tank can cause agitation and premature foaming of the concentrate, which can result in system failure. The foam concentrate pump will be self-priming and have the ability to draw foam concentrate from external supplies such as drums or pails.

### **EXTERNAL FOAM CONCENTRATE CONNECTION**

An external foam pick-up will be provided to enable use of a foam agent that is not stored on the vehicle. The external foam pick-up will be designed to allow continued operation after the on-board foam tank is empty. The external foam pick-up will be designed to allow use with training foam or colored water for training purposes.

### **PANEL MOUNTED STRAINER/EXTERNAL PICK-UP CONNECTION**

A bronze body strainer/connector unit will be provided. The unit will be mounted to the pump panel. The external foam pick-up will be one (1) 1.00" male connection with chrome-plated cap integrated to a 2.00" strainer cleanout cap. A check valve will be installed in the pick-up portion of the cleanout cap. A basket style stainless steel screen will be installed in the body of the strainer/connector unit. Removal of the 2.00" cleanout cap will be all that is required to gain access to and remove the stainless steel basket screen. The strainer/connector unit will be ahead of the foam concentrate pump inlet port to insure that all agent reaching the foam pump has been strained.

### **PICK-UP HOSE**

A 1.00" flexible hose with an end for insertion into foam containers will be provided. The hose will be supplied with a 1.00" female swivel NST thread swivel connector. The hose will be shipped loose.

### **DISCHARGES**

The foam system will be plumbed to the lower rear crosslay, lower front crosslay and left side of front bumper.

### **SYSTEM ELECTRICAL LOAD**

The foam proportioning will not impose an electrical load on the vehicle electrical system any greater than five (5) amps at 12VDC.

### **FOAM SUPPLY VALVE**

An electric valve will be used for the foam supply valve. The foam supply valve will be controlled at the foam system control head for ease of operation. The supply valve will be electric, remote controlled, to eliminate air pockets in the foam tank supply hose.

## **MAINTENANCE MESSAGE**

A message will be displayed on the control head to advise when system maintenance needs to be performed. The message will display interval for cleaning the foam strainer, cleaning for the water strainers, and changing the hydraulic oil.

## **FLUSH SYSTEM**

The system will be designed such that a flush mode will be provided to allow the system to flush all foam concentrate with clear water. The flush circuit control logic will ensure the foam tank supply valve is closed prior to opening the flush valve. The flush valve will be operated at the foam system control head for ease of operation. The valve will be electrically controlled and located as close to the foam tank supply valve as possible. A manual flush drain valve will be labeled and conveniently located.

## **REFILL, SINGLE FOAM TANK**

The foam system's proportioning pump will be used to fill the Class B foam tank. This will allow use of the auxiliary foam pick-up to pump the foam from pails or a drum on the ground into the foam tank. A foam shut-off switch will be installed in the fill dome of the tank to shut the system down when the tank is full. The fill operation will be controlled by a mode in the foam system controller stating TANK FILL. While the proportioner pump is filling the tank, the controller will display FILL TANK. When the tank is full, as determined by the float switch in the tank dome, the pump will stop and the controller will display TANK FULL.

## **FOAM TANK**

The foam tank will be an integral portion of the polypropylene water tank. The cell will have a capacity of 40 gallons of foam with the intended use of Class B foam. The brand of foam stored in this tank will be National. The foam cell will reduce the capacity of the water tank. The foam cell will have a screen in the fill dome and a breather in the lid.

## **FOAM TANK DRAIN**

A system of 1.00" foam tank drains will be provided, integrated into the foam systems strainer and tank to foam pump valve management system. The tank to pump hoses running from the tank(s) to the panel mounted strainer will 1.00" diameter. The foam system controller will have a mode that allows for a given foam valve to be opened at will. Flow of foam from the tank valve to the strainer will be usable as a tank drain mode.

An adaptor will be supplied, that allows the 1.00" foam intake screen to assembly to be used as a drain outlet. The standard supplied 1.00" foam pick up hose will be attached to the screen assembly by way of the adaptor. The drain mode will allow the operator to open and close the tank valve as required from the control head, to drain foam and re-fill foam containers through the connected hose, without foam spillage beneath the vehicle.

## **PUMP CONTROL PANELS (LEFT SIDE CONTROL)**

Pump controls and gauges will be located midship at the left (driver's) side of the apparatus and properly identified.

The main pump operator's control panel will be completely enclosed and located in the forward section of the body compartment, to protect against road debris and weather elements. The pump operator's panels will be no more than 31.00" wide, and made in four (4) sections with the center section easily removable with simple hand tools. For the safety of the pump operator, there will be no discharge outlets or pump inlets located on the main pump operators panel.

Layout of the pump control panel will be ergonomically efficient and systematically organized. The upper section will contain the master gauges. This section will be angled down for easy visibility. The center section will contain the pump controls aligned in two horizontal rows. The pressure control device, engine monitoring gauges, electrical switches, and foam controls (if applicable) will be located on or adjacent to the center panel, on the side walls for easy operation and visibility. The lower section will contain the outlet drains.

Manual controls will be easy moving 8" long lever style controls that operate in a vertical, up and down swing motion. These handles will have a 2.25" diameter knob and be able to lock in place to prevent valve creep under any pressure. Bright finish bezels will encompass the opening, be securely mounted to the pump operator's panel, and will incorporate the discharge gauge bezel. Bezels will be bolted to the panel for easy removal and gauge service. The driver's side discharges will be controlled directly at the valve. There will be no push-pull style control handles.

Identification tags for the discharge controls will be recessed within the same bezel. The discharge identification tags will be color coded, with each discharge having its own unique color.

All remaining identification tags will be mounted on the pump panel in chrome-plated bezels.

All discharge outlets will be color coded and labeled to correspond with the discharge identification tag.

The pump panels for the midship discharge and intake ports will be located ahead of the body compartments with no side discharge or intake higher than the frame rail. The pump panels will be easily removable with simple hand tools.

A recessed cargo area will be provided at the front of the body, ahead of the water tank above the plumbing.

## **PUMP PANEL CONFIGURATION**

The pump panel configuration will be arranged and installed in an organized manner that will provide user-friendly operation.

## **PUMP AND GAUGE PANEL**

The pump operator's panel and gauge panels will be constructed of stainless steel with a brushed finish.

The side control panels will be constructed of stainless steel with a brushed finish for durability and ease of maintenance.

### **PUMP AND PLUMBING ACCESS**

Simple access to the plumbing will be provided through the front of the body area by raising the cab for complete plumbing service and valve maintenance. Access to valves will not require removal of operator panels or pump panels. Access for rebuilding of the pump will not require removal of more than the tank to pump line and a single discharge line. This access will allow for fast, easy valve or pump rebuilding, making for reduced out of service times. Steps will be provided for access to the top of the pump.

Access to the pump will be provided by raising the cab. The pump will be positioned such that all maintenance and overhaul work can be performed above the frame and under the tilted cab. The service and overhaul work on the pump will not require the removal of operator panels or pump panels. Complete pump casing and gear case removal will require no more than removal of the intake and discharge manifolds, driveline, coolers and a single discharge line. The pump case and gear case will be able to be removed by lifting upward without interference from piping and be removable in less than 3 hours.

### **PUMP COMPARTMENT LIGHT**

There will be one (1) Whelen®, Model 3SC0CDCR, 3.00" white 12 volt DC LED light(s) with Whelen, Model 3FLANGEC, flange(s) installed in the plumbing area.

The light(s) will be activated by a toggle switch located in the pump compartment area.

Engine monitoring graduated LED indicators will be incorporated with the pressure controller.

### **VACUUM AND PRESSURE GAUGES**

The pump vacuum and pressure gauges will be liquid filled and manufactured by Class 1 Incorporated ©.

The gauges will be a minimum of 4.50" in diameter and will have white faces with black lettering, with a pressure range of 30.00"-0-600#.

The pump pressure and vacuum gauges will be installed adjacent to each other at the pump operator's control panel.

Test port connections will be provided at the pump operator's panel. One will be connected to the intake side of the pump, and the other to the discharge manifold of the pump. They will have 0.25 in. standard pipe thread connections and polished stainless steel plugs. They will be marked with a label.

### **PRESSURE GAUGES**

The individual "line" pressure gauges for the discharges will be Class 1© interlube filled.

They will be 2.50" in diameter and have white faces with black lettering.

Gauges will have a pressure range of 0-400#.

The individual pressure gauge will be installed as close to the outlet control as practical.

### **WATER LEVEL GAUGE**

An electric water level gauge will be incorporated in the pressure controller that registers water level by means of nine (9) LEDs. They will be at 1/8 level increments with a tank empty LED. The LEDs will be a bright type that is readable in sunlight, and have a full 180-degree of clear viewing.

To further alert the pump operator, the gauge will have a warning flash when the tank volume is less than 25 percent, and will have down chasing LEDs when the tank is almost empty.

The level measurement will be ascertained by sensing the head pressure of the fluid in the tank or cell.

### **MINI SLAVE UNIT**

An electric water level gauge will be provided in the cab that registers water level by means of five (5) LEDs. They will be at 1/4 level increments with a tank empty LED. The LEDs will be a bright type that is readable in sunlight, and have a full 180-degree of clear viewing.

The water level gauge in the cab will be activated when the pump is in gear.

### **FOAM LEVEL GAUGE**

A Pierce electric foam level gauge will be provided on the operator's panel, that registers foam level by means of nine (9) LEDs. There will also be a mini foam level gauge with five (5) LEDs in the cab. They will be at 1/8 level increments with a tank empty LED. The LEDs will be a bright type that is readable in sunlight, and have a full 180 degree of clear viewing. The gauge will match the water level gauge in the pressure controller.

To further alert the pump operator, will have a warning flash when the tank volume is less than 25 percent, and will have Down Chasing LEDs when the tank is almost empty.

The level measurement will be ascertained by sensing the head pressure of the fluid in the tank or cell. This method provides accuracy with an array of multi-viscosity foams.

The foam level gauge in the cab will be activated by pump is in gear.

### **SIDE CONTROL PUMP OPERATOR'S/PUMP PANEL LIGHTING**

Illumination will be provided for controls, switches, essential instructions, gauges, and instruments necessary for the operation of the apparatus and the equipment provided on it. External illumination will be a minimum of five (5) foot-candles on the face of the device. Internal illumination will be a minimum of four (4) footlamberts.

The pump panels will be illuminated by four (4) Truck-Lite, Model 6060C white LED lights installed on the back of the cab, two (2) on the driver's side and two (2) on the passenger's side.

The pump operator's panel will utilize the same LED strip lighting at the forward doorframe as all other compartment lighting.

There will be a small white LED pump engaged indicator light installed overhead.

### **MICROPHONE & SPEAKER COMPARTMENT**

A microphone and speaker compartment will be furnished adjacent to the pump operator's panel in the center compartment divider. Compartment size will be 12.00" high x 8.00" wide x 6.00" deep.

### **AIR HORN SYSTEM**

There will be two (2) Grover, air horns provided and located in the front bumper, recessed to the outside of the frames. The horn system will be piped to the air brake system wet tank utilizing 0.38" tubing. A pressure protection valve will be installed in-line to prevent loss of air in the air brake system.

### **AIR HORN CONTROL**

The air horn will be actuated by a chrome push button switch located on the officer side of the engine tunnel and by a foot switch on the driver's side.

### **ELECTRONIC SIREN**

A "Code 3", model 3692, electronic siren with noise canceling microphone will be provided.

This siren to be active when the battery switch is on and that emergency master switch is on.

NFPA 1901, Section 13.9.1.1 requires the siren manufacturer to certify the siren as meeting the requirements of SAE J1849, *Emergency Vehicle Sirens*.

Per the fire department specification, the siren and siren speaker come from separate manufacturers and a certification is therefore invalid. The apparatus will be non compliant to NFPA 1901 standards at time of contract execution.

Electronic siren head will be recessed in the overhead console above the engine tunnel on the driver side.

The electronic siren will be actuated by a push button located on the officer's side instrument panel and by the horn button in the steering wheel.

The driver will have the option to control the siren or the chassis horns from the horn button by means of a selector switch located on the instrument panel.

### **SPEAKER**

A Federal, Model BP200-EF, 200 watt speaker will be provided. A chrome-plated "EF" flat grille will be installed in front of the speaker.

The speaker(s) will be recessed in the front bumper on the passenger's side.

### **AUXILIARY MECHANICAL SIREN**

A Federal Q2B® siren will be furnished. A siren brake button will be installed on the switch panel.

The control solenoid will be powered up after the emergency master switch is activated.

The mechanical siren will be mounted on the bumper deck plate. It will be mounted on the left side. A reinforcement plate will be furnished to support the siren.

### **MECHANICAL SIREN CONTROL**

The mechanical siren Will be actuated by a push button located on the officer's side instrument panel and by a foot switch on the driver's side.

### **CAB ROOF LIGHTBAR**

There will be one (1) 72.00" Whelen®, Freedom™, Model FN\*\*QLED, lightbar provided.

The lightbar will include the following:

- Six (6) red flashing forward facing LED modules
- Two (2) clear flashing forward facing LED modules
- Two (2) red flashing front corner LED modules
- One (1) red flashing driver side end LED module
- One (1) red flashing passenger side end LED module

The color of the lenses shall be clear.

There will be a switch, located in the cab on the switch panel, to control this lightbar.

The white warning lights will be disabled when the parking brake is set.

### **TRAFFIC LIGHT CONTROLLER, WIRING ONLY**

Wiring only will be provided for the Opticom traffic light controller remote mounted on the cab, cab roof, mobile traffic tech, optic 1020A-GPS. The control box for the GPS/Opticom will be mounted behind the officer's seat.

The Opticom traffic light controller will be activated by a cab switch with emergency master control.

The Opticom traffic light controller will have no momentary activation switch.

The Opticom traffic light controller will be disabled when the parking brake is applied.

The wiring terminals will be clearly identified.

### **CAB FACE WARNING LIGHTS**

There will be four (4) Whelen®, Model M6\*C, LED flashing warning lights installed on the cab face, above the headlights, mounted in a common bezel.



- The driver's side front outside warning light to be red
- The driver's side front inside warning light to be red
- The passenger's side front inside warning light to be red
- The passenger's side front outside warning light to be red

All four (4) lights will include a clear lens.

There will be a switch located in the cab, on the switch panel, to control the four (4) lights.

The inside lights may be load managed if colored or disabled if white, when the parking brake is set.

### **HEADLIGHT FLASHER**

The high beam headlights will flash alternately between the left and right side.

There will be a switch installed in the cab on the switch panel to control the high beam flash. This switch will be live when the battery switch and the emergency master switches are on.

The flashing will automatically cancel when the hi-beam headlight switch is activated or when the parking brake is set.

### **SIDE ZONE LOWER LIGHTING**

There will be six (6) Whelen®, Model M6\*C, LED flashing warning lights with Model 6EFLANGE, chrome flanges located in the following positions:

- Two (2) lights, one (1) each side on the bumper extension
  - The side front lights to be red
- Two (2) lights, one (1) each side above the front wheels
  - The side middle lights to be red
- Two (2) lights, one (1) each side above rear wheels
  - The side rear lights to be red

All six (6) lights will include a clear lens.

There will be a switch located in the cab on the switch panel to control the lights.

### **REAR ZONE LOWER LIGHTING**

There shall be two (2) Whelen®, Model M6\*C, LED flashing warning lights located at the rear of the apparatus.

- The driver's side rear light to be red
- The passenger's side rear light to be red

Both lights will include a lens that is clear.

There will be a switch located in the cab on the switch panel to control the lights.

### **REAR OF HOSE BED WARNING LIGHTS**

There will be two (2) Whelen, Model L31H\*F, LED warning beacons provided at the rear of the truck, located one (1) each side.

The color of the driver side LED light will be red and the passenger side LED light will be amber.

The dome colors will be both domes clear.

There will be a switch located in the cab on the switch panel to control the beacons.

The rear warning lights will be mounted on top of the compartmentation with all wiring totally enclosed. The rear deck lights will be mounted on the beavertails as high as possible.

### **TRAFFIC DIRECTING LIGHT**

There will be one (1) Whelen®, Model TAL65, 36.01" long x 2.84" high x 2.24" deep, amber LED traffic directing light installed at the rear of the apparatus.

The Whelen, Model TACTLD1, control head will be included with this installation.

The auxiliary warning mode will be activated with the control head only.

This traffic directing light will be recessed with a stainless steel trim plate at the rear of the apparatus as high as practical.

The traffic directing light control head will be located in the driver side overhead switch panel in the right panel position.

### **12'-20' LOW PRESSURE HYDRAULIC CONNECTION HOSE**

A 12'-20' section of Hurst low pressure 5,000 psi twin line connection hose will be provided. The hose color will be grey/yellow.

The hose will be one (1) continuous length without unions.

The hose will be equipped with quick disconnect type fittings on one (1) end with swivel fittings on the opposite end.

A total of two (2) section(s) of low pressure connection hose will be provided.

The hose(s) will be located R1, power unit located on tray in R1.

### **LOW PRESSURE HYDRAULIC HOSE**

A 100' section of Hurst low pressure 5,000 psi twin line hose will be provided. The hose color will be grey/yellow.

The hose will be one (1) continuous length without unions.

The hose will be equipped with quick disconnect type fittings on one (1) end with swivel fittings on the opposite end.

A total of two (2) section(s) of low pressure connection hose will be provided.

The hose(s) will be located R1.

### **HYDRAULIC REEL WITH CAPACITY FOR 100' OF HOSE**

A hydraulic hose reel will be provided. The reel will be operated by a 12 volt electric motor controlled by a rewind switch. The motor will be protected by a circuit breaker and the rewind circuit will be protected by a fuse. The switch will be installed at a height not to exceed 72.00" above the operator's standing position. The switch will be guarded to prevent accidental operation.

The reel capacity will be a minimum of 100' of 0.25" inside diameter dual hydraulic hose. Surfaces where the hose comes in contact with the reel roller will be constructed of either stainless steel, chrome plated steel or plastic.

A Nylatron guide to be provided to aid in the payout and loading of the reel. A ball stop will be provided to prevent the hose from being wound around the reel.

A label will be provided in a readily visible location adjacent to the reel. The label will indicate maximum flow pressure and total length of hose installed on the reel.

A total of two (2) reels will be installed R1, up high.

The reel will be designed for a Hurst low PSI.

### **COUPLING KIT**

A Streamline Technology connection will be provided to connect the hose to the hydraulic tools.

The connection will allow a hydraulic twin line hose to be converted into a single connection.

A total of two (2) female connection fitting(s) will be provided.

### **LOOSE EQUIPMENT**

The following equipment will be furnished with the completed unit:

- One (1) bag of chrome, stainless steel, or cadmium plated screws, nuts, bolts and washers, as used in the construction of the unit.

### **NFPA REQUIRED LOOSE EQUIPMENT, PROVIDED BY FIRE DEPARTMENT**

The following loose equipment as outlined in NFPA 1901, 2009 edition, section 5.8.2 and 5.8.3 will be provided by the fire department. All loose equipment will be installed on the apparatus before placed in emergency service, unless the fire department waives NFPA section 4.21.

- 800 ft (60 m) of 2.50" (65 mm) or larger fire hose.

- 400 ft (120 m) of 1.50" (38 mm), 1.75" (45 mm), or 2.00" (52 mm) fire hose.
- One (1) handline nozzle, 200 gpm (750 L/min) minimum.
- Two (2) handline nozzles, 95 gpm (360 L/min) minimum.
- One (1) playpipe with shutoff and 1.00" (25 mm), 1.125" (29 mm), and 1.25" (32 mm) tips.
- One (1) SCBA complying with NFPA 1981, *Standard on Open-Circuit Self-Contained Breathing Apparatus for Fire and Emergency Services*, for each assigned seating position, but not fewer than four (4), mounted in brackets fastened to the apparatus or stored in containers supplied by the SCBA manufacturer.
- One (1) spare SCBA cylinder for each SCBA carried, each mounted in a bracket fastened to the apparatus or stored in a specially designed storage space(s).
- One (1) first aid kit.
- Four (4) combination spanner wrenches mounted in bracket(s) fastened to the apparatus.
- Two (2) hydrant wrenches mounted in brackets fastened to the apparatus.
- Four (4) ladder belts meeting the requirements of NFPA 1983, *Standard on Fire Service Life Safety Rope and System Components* (if equipped with an aerial device).
- One (1) double female 2.50" (65 mm) adapter with National Hose threads, mounted in a bracket fastened to the apparatus.
- One (1) double male 2.50" (65 mm) adapter with National Hose threads, mounted in a bracket fastened to the apparatus.
- One (1) rubber mallet, for use on suction hose connections, mounted in a bracket fastened to the apparatus.
- Two (2) salvage covers each a minimum size of 12 ft x 14 ft (3.7 m x 4.3 m).
- One (1) traffic vest for each seating position, each vest to comply with ANSI/ISEA 207, *Standard for High Visibility Public Safety Vests*, and have a five-point breakaway feature that includes two (2) at the shoulders, two (2) at the sides, and one (1) at the front.
- Five (5) fluorescent orange traffic cones not less than 28.00" (711 mm) in height, each equipped with a 6.00" (152 mm) retro-reflective white band no more than 4.00" (152 mm) from the top of the cone, and an additional 4.00" (102 mm) retro-reflective white band 2.00" (51 mm) below the 6.00" (152 mm) band.
- Five (5) illuminated warning devices such as highway flares, unless the five (5) fluorescent orange traffic cones have illuminating capabilities.
- One (1) automatic external defibrillator (AED).
- If the supply hose carried does not use sexless couplings, an additional double female adapter and double male adapter, sized to fit the supply hose carried, will be carried mounted in brackets fastened to the apparatus.
- If none of the pump intakes are valved, a hose appliance that is equipped with one or more gated intakes with female swivel connection(s) compatible with the supply hose used on one side and a swivel connection with pump intake threads on the other side will be carried. Any intake

connection larger than 3.00" (75 mm) will include a pressure relief device that meets the requirements of 16.6.6.

- If the apparatus does not have a 2.50" National Hose (NH) intake, an adapter from 2.50" NH female to a pump intake will be carried, mounted in a bracket fastened to the apparatus if not already mounted directly to the intake.
- If the supply hose carried has other than 2.50" National Hose (NH) threads, adapters will be carried to allow feeding the supply hose from a 2.50" NH thread male discharge and to allow the hose to connect to a 2.50" NH female intake, mounted in brackets fastened to the apparatus if not already mounted directly to the discharge or intake.

#### **SOFT SUCTION HOSE PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2009 edition, section 5.7.2 requires a minimum of 20 ft of suction hose or 15 ft of supply hose.

Hose is not on the apparatus as manufactured. The fire department will provide suction or supply hose.

#### **STRAINER PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2009 edition, section 5.7.2.1.1 requires a suction strainer when suction hose is provided.

The strainer is not on the apparatus as manufactured. The fire department will provide the suction strainer.

#### **DRY CHEMICAL EXTINGUISHER PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2009 edition, section 5.8.3 requires one (1) approved dry chemical portable fire extinguisher with a minimum 80-B:C rating mounted in a bracket fastened to the apparatus.

The extinguisher is not on the apparatus as manufactured. The fire department will provide and mount the extinguisher.

#### **WATER EXTINGUISHER PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2009 edition, section 5.8.3 requires one (1) 2.5 gallon or larger water extinguisher mounted in a bracket fastened to the apparatus.

The extinguisher is not on the apparatus as manufactured. The fire department will provide and mount the extinguisher.

#### **FLATHEAD AXE PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2009 edition, Section 5.8.3 requires one (1) flathead axe mounted in a bracket fastened to the apparatus.

The axe is not on the apparatus as manufactured. The fire department will provide and mount the axe.

## **PICKHEAD AXE PROVIDED BY FIRE DEPARTMENT**

NFPA 1901, 2009 edition, Section 5.8.3 requires one (1) pickhead axe mounted in a bracket fastened to the apparatus.

The axe is not on the apparatus as manufactured. The fire department will provide and mount the axe.

## **PAINT - BODY PAINTED TO MATCH CAB**

The exterior custom cab and body painting procedure will consist of a seven (7) step finishing process as follows:

1. **Manual Surface Preparation** - All exposed metal surfaces on the custom cab and body will be thoroughly cleaned and prepared for painting. Imperfections on the exterior surfaces will be removed and sanded to a smooth finish. Exterior seams will be sealed before painting. Exterior surfaces that will not be painted include; chrome plating, polished stainless steel, anodized aluminum and bright aluminum treadplate.
2. **Chemical Cleaning and Pretreatment** - All surfaces will be chemically cleaned to remove dirt, oil, grease, and metal oxides to ensure the subsequent coatings bond well. The aluminum surfaces will be properly cleaned and treated using a high pressure, high temperature 4 step Acid Etch process. The steel and stainless surfaces will be properly cleaned and treated using a high temperature 3 step process specifically designed for steel or stainless. The chemical treatment converts the metal surface to a passive condition to help prevent corrosion. A final pure water rinse will be applied to all metal surfaces.
3. **Surfacer Primer** - The Surfacer Primer will be applied to a chemically treated metal surface to provide a strong corrosion protective basecoat. A minimum thickness of 2 mils of Surfacer Primer is applied to surfaces that require a Critical aesthetic finish. The Surfacer Primer is a two-component high solids urethane that has excellent sanding properties and an extra smooth finish when sanded.
4. **Finish Sanding** - The Surfacer Primer will be sanded with a fine grit abrasive to achieve an ultra-smooth finish. This sanding process is critical to produce the smooth mirror like finish in the topcoat.
5. **Sealer Primer** - The Sealer Primer is applied prior to the Basecoat in all areas that have not been previously primed with the Surfacer Primer. The Sealer Primer is a two-component high solids urethane that goes on smooth and provides excellent gloss hold out when topcoated.
6. **Basecoat Paint** - Two coats of a high performance, two component high solids polyurethane basecoat will be applied. The Basecoat will be applied to a thickness that will achieve the proper color match. The Basecoat will be used in conjunction with a urethane clear coat to provide protection from the environment.
7. **Clear Coat** - Two (2) coats of Clear Coat will be applied over the Basecoat color. The Clear Coat is a two-component high solids urethane that provides superior gloss and durability to the exterior surfaces. Lap style and roll-up doors will be Clear Coated to match the body. Paint warranty for the roll-up doors will be provided by the roll-up door manufacture.

Specifications are written to define cyclic corrosion testing, physical strengths, durability and minimum appearance requirements must be met in order for an exterior paint finish to be considered acceptable as a Pierce quality finish.

Each batch of basecoat color is checked for a proper match before painting of the cab and the body. After the cab and body are painted, the color is verified again to make sure that it matches the color standard. Electronic color measuring equipment is used to compare the color sample to the color standard entered into the computer. Color specifications are used to determine the color match. A Delta E reading is used to determine a good color match within each family color.

All removable items such as brackets, compartment doors, door hinges, and trim will be removed and separately if required, to ensure paint behind all mounted items. Body assemblies that cannot be finish painted after assembly will be finish painted before assembly.

The cab will be two-tone, with the upper section painted white #261 and lower section of the cab and body painted #90 red.

#### **PAINT - ENVIRONMENTAL IMPACT**

Contractor will meet or exceed all current State regulations concerning paint operations. Pollution control will include measures to protect the atmosphere, water and soil. Controls will include the following conditions:

- Topcoats and primers will be chrome and lead free.
- Metal treatment chemicals will be chrome free. The wastewater generated in the metal treatment process will be treated on-site to remove any other heavy metals.
- Particulate emission collection from sanding operations will have a 99.99% efficiency factor.
- Particulate emissions from painting operations will be collected by a dry filter or water wash process. If the dry filter is used, it will have an efficiency rating of 98.00%. Water wash systems will be 99.97% efficient
- Water from water wash booths will be reused. Solids will be removed on a continual basis to keep the water clean.
- Paint wastes are disposed of in an environmentally safe manner.
- Empty metal paint containers will be to recover the metal.
- Solvents used in clean-up operations will be recycled on-site or sent off-site for distillation and returned for reuse.

Additionally, the finished apparatus will not be manufactured with or contain products that have ozone depleting substances. Contractor will, upon demand, present evidence that the manufacturing facility meets the above conditions and that it is in compliance with his State EPA rules and regulations.

## **PAIN T CHASSIS FRAME ASSEMBLY**

The chassis frame assembly will be painted to match the lower job color before the installation of the cab and body, and before installation of the engine and transmission assembly, air brake lines, electrical wire harnesses, etc.

Components that are included with the chassis frame assembly that will be painted not e-coated are:

- Frame rails
- Cross members
- Axles
- Suspensions
- Steering gear
- Battery boxes
- Bumper extension weldment
- Frame extensions
- Body mounting angles
- Rear Body support substructure (front and rear)
- Pump house substructure
- Air tanks
- Fuel tank
- Castings
- Individual piece parts used in chassis and body assembly

Components treated with epoxy E-coat protection prior to paint:

- Two (2) C-channel frame rails

The E-coat process will meet the technical properties shown.

## **COMPARTMENT INTERIOR PAINT**

The compartment interior will be painted with a gray spatter finish for ease of cleaning and to make it easier to touch up scratches and nicks.

## **REFLECTIVE BAND**

A 10.00" white reflective band will be provided across the front of the vehicle and along the sides of the body.

The reflective band provided on the cab face will be below the headlights on the fiberglass.

## **CHEVRON STRIPING, REAR**

There will be alternating chevron striping located on the rear-facing vertical surface of the apparatus. The rear surface, excluding the rear roll up door will be covered.



The colors will be ruby red and lemon yellow reflective.

Each stripe will be 6.00" in width.

This will meet the requirements of NFPA 1901, 2009 edition, which states that 50% of the rear surface will be covered with chevron striping.

### **OUTLINE, REFLECTIVE STRIPE**

A black outline will be applied on the top and the bottom of the reflective band. There will be one (1) set of outline stripes required.

### **REFLECTIVE STRIPE, CAB DOORS**

A 6.00" x 16.00" white reflective stripe will be provided across the interior of each cab door. The stripe will be located approximately 1.00" up from the bottom, on the door panel.

This stripe will meet the NFPA 1901 requirement.

### **BODY STRIPE**

There will be a reflective stripe provided on each side of the body, over the fender.

### **CAB STRIPE**

There will be a reflective stripe on each side of the cab, low and over the fender.

### **LETTERING**

Eighty-one (81) to one hundred (100) reflective lettering, 3.00" high, with outline and shade will be provided.

### **LETTERING**

There will be reflective lettering, 12.00" high, with outline and shade provided. There will be two (2) letters provided.

### **LETTERING**

There will be reflective lettering, 6.00" high, with outline and shade provided. There will be four (4) letters provided.

### **RUST PROOFING/UNDERCOATING**

The apparatus will be properly treated by an authorized Ziebart dealer.

The underside of the apparatus will be undercoated with an asphalt petroleum based material, dark in color.

The undercoating material utilized on the apparatus will be formulated to resist corrosion and deaden unwanted sound or road noise.

Coating texture will appear firm, flexible, and resistant to abrasion. Minimum dry film thickness will be in the range of 8.00 to 12.00 mils.

The material will be applied to the following areas:

Body and cab wheel well fender liners, on the back side only.

Underside of body and cab sheet metal, and structural components.

Underside and vertical sides of all sheet metal compartmentation, including support angles.

Structural support members under running boards, rear platforms, battery boxes, walkways, etc.

Inside surfaces of the pump heat enclosure, (when installed).

### **MANUAL, FIRE APPARATUS PARTS**

Two (2) custom parts manuals for the complete fire apparatus will be provided in hard copy with the completed unit.

The manual will contain the following:

- Job number
- Part numbers with full descriptions
- Table of contents
- Parts section sorted in functional groups reflecting a major system, component, or assembly
- Parts section sorted in Alphabetical order
- Instructions on how to locate a part

The manual will be specifically written for the chassis and body model being purchased. It will not be a generic manual for a multitude of different chassis and bodies.

### **SERVICE PARTS INTERNET SITE**

The service parts information included in this manual is also available on the Pierce website. The website offers additional functions and features not contained in this manual, such as digital photographs and line drawings of select items. The website also features electronic search tools to assist in locating parts quickly.

### **MANUALS, CHASSIS SERVICE**

Two (2) chassis service manuals containing parts and service information on major components will be provided with the completed unit.

The manuals will contain the following sections:

- Job number

- Table of contents
- Troubleshooting
- Front Axle/Suspension
- Brakes
- Engine
- Tires
- Wheels
- Cab
- Electrical, DC
- Air Systems
- Plumbing
- Appendix

The manual will be specifically written for the chassis model being purchased. It will not be a generic manual for a multitude of different chassis and bodies.

**MANUALS, CHASSIS OPERATION**

Two (2) chassis operation manuals will be provided.

**ONE (1) YEAR MATERIAL AND WORKMANSHIP**

A Pierce basic apparatus limited warranty certificate, WA0008, is included with this proposal.

**THREE (3) YEAR MATERIAL AND WORKMANSHIP**

The Pierce custom chassis limited warranty certificate, WA0284, is included with this proposal.

**ENGINE WARRANTY**

A Cummins **five (5) year** limited engine warranty will be provided. A limited warranty certificate, WA0181, is included with this proposal.

**STEERING GEAR WARRANTY**

A Sheppard **three (3) year** limited steering gear warranty shall be provided. A copy of the warranty certificate shall be submitted with the bid package.

**FIFTY (50) YEAR STRUCTURAL INTEGRITY**

The Pierce custom chassis frame and crossmembers limited warranty certificate, WA0038, is included with this proposal.

**FRONT AXLE THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY**

The Pierce TAK-4 suspension limited warranty certificate, WA0050, is included with this proposal.

**REAR AXLE TWO (2) YEAR MATERIAL AND WORKMANSHIP WARRANTY**

A Meritor axle limited warranty certificate, WA0046, is included with this proposal.

**ABS BRAKE SYSTEM THREE (3) YEAR MATERIAL AND WORKMANSHIP WARRANTY**

A Meritor Wabco™ABS brake system limited warranty certificate, WA0232, is included with this proposal.

**TEN (10) YEAR STRUCTURAL INTEGRITY**

The Pierce custom cab limited warranty certificate, WA0012, is included with this proposal.

**TEN (10) YEAR PRO-RATED PAINT AND CORROSION**

A Pierce cab limited pro-rated paint warranty certificate, WA0055, is included with this proposal.

**FIVE (5) YEAR MATERIAL AND WORKMANSHIP**

The Pierce Command Zone electronics limited warranty certificate, WA0014, is included with this proposal.

**COMPARTMENT LIGHT WARRANTY**

The Pierce 12 volt DC LED strip lights limited warranty certificate, WA0203, is included with this proposal.

**TRANSMISSION WARRANTY**

The transmission will have a **five (5) year/unlimited mileage** warranty covering 100 percent parts and labor. The warranty will be provided by Allison Transmission.

Note: The transmission cooler is not covered under any extended warranty you may be getting on your Allison Transmission. Please review your Allison Transmission warranty for coverage limitations.

**TRANSMISSION COOLER WARRANTY**

The transmission cooler will carry a five (5) year parts and labor warranty (exclusive to the transmission cooler). In addition, a collateral damage warranty will also be in effect for the first three (3) years of the warranty coverage and will not exceed \$10,000 per occurrence. A copy of the warranty certificate will be submitted with the bid package.

**WATER TANK WARRANTY**

A UPF poly water tank limited warranty certificate, WA0195, is included with this proposal.

### **TEN (10) YEAR STRUCTURAL INTEGRITY**

The Pierce apparatus body limited warranty certificate, WA0009, is included with this proposal.

### **ROLL UP DOOR MATERIAL AND WORKMANSHIP WARRANTY**

A Gortite roll-up door limited warranty will be provided. The mechanical components of the roll-up door will be warranted against defects in material and workmanship for the lifetime of the vehicle. A **six (6) year** limited warranty will be provided on painted and satin roll up doors.

The limited warranty certificate, WA0190, is included with this proposal.

### **SIX (6) YEAR MATERIAL AND WORKMANSHIP**

A Pierce PUC pump limited warranty certificate, WA0039, is included with this proposal.

### **TEN (10) YEAR PUMP PLUMBING WARRANTY**

The Pierce apparatus plumbing limited warranty certificate, WA0035, is included with this proposal.

### **FOAM SYSTEM WARRANTY**

The Husky 12 foam system limited warranty certificate, WA0231, is included with this proposal.

### **TEN (10) YEAR PRO-RATED PAINT AND CORROSION**

A Pierce body limited pro-rated paint warranty certificate, WA0057, is included with this proposal.

### **ONE (1) YEAR MATERIAL AND WORKMANSHIP**

The Pierce graphics fading and deterioration limited warranty limited warranty certificate, WA0168, is included with this proposal.

### **VEHICLE STABILITY CERTIFICATION**

The fire apparatus manufacturer will provide a certification stating the apparatus complies with NFPA 1901, current edition, section 4.13, Vehicle Stability. The certification will be provided at the time of bid.

### **ENGINE INSTALLATION CERTIFICATION**

The fire apparatus manufacturer will provide a certification, along with a letter from the engine manufacturer stating they approve of the engine installation in the bidder's chassis. The certification will be provided at the time of delivery.

### **POWER STEERING CERTIFICATION**

The fire apparatus manufacturer will provide a certification stating the power steering system as installed meets the requirements of the component supplier. The certification will be provided at the time of bid.

### **CAB INTEGRITY CERTIFICATION**

The fire apparatus manufacturer will provide a cab integrity certification with this proposal. The certification will state that the cab has been tested and certified by an independent third-party test facility. Testing events will be documented with photographs, real-time and high-speed video, vehicle

accelerometers, cart accelerometers, and a laser speed trap. The fire apparatus manufacturer will provide a state-licensed professional engineer to witness and certify all testing events. Testing will meet or exceed the requirements below:

- European Occupant Protection Standard ECE Regulation No.29.
- SAE J2422 Cab Roof Strength Evaluation - Quasi-Static Loading Heavy Trucks.
- SAE J2420 COE Frontal Strength Evaluation - Dynamic Loading Heavy Trucks.
- Roof Crush

The cab will be subjected to a roof crush force of 22,050 lbs. This value meets the ECE 29 criteria and is equivalent to the front axle rating up to a maximum of 10 metric tons.

- Additional Roof Crush

The same cab will be subjected to a roof crush force of 100,000 lbs. This value exceeds the ECE 29 criteria by nearly 4.5 times.

- Side Impact

The same cab will be subjected to dynamic preload where a 13,275 lb moving barrier slams into the side of the cab at 5.5 mph at a force of 13,000 ft-lbs. This test is part of the SAE J2422 test procedure and more closely represents the forces a cab will see in a rollover incident.

- Frontal Impact

The same cab will withstand a frontal impact of 32,600 ft-lbs of force using a moving barrier in accordance with SAE J2420.

- Additional Frontal Impact

The same cab will withstand a frontal impact of 65,200 ft-lbs of force using a moving barrier, (twice the force required by SAE J2420).

The same cab will withstand all tests without any measurable intrusion into the survival space of the occupant area.

### **CAB DOOR DURABILITY CERTIFICATION**

Robust cab doors help protect occupants. Cab doors will survive a 200,000 cycle door slam test where the slamming force exceeds 20 G's of deceleration. The bidder will certify that the sample doors similar to those provided on the apparatus have been tested and have met these criteria without structural damage, latch malfunction, or significant component wear.

### **WINDSHIELD WIPER DURABILITY CERTIFICATION**

Visibility during inclement weather is essential to safe apparatus performance. Windshield wipers will survive a 3 million cycle durability test in accordance with section 6.2 of SAE J198 *Windshield Wiper Systems - Trucks, Buses and Multipurpose Vehicles*. The bidder will certify that the wiper system design has been tested and that the wiper system has met these criteria.

### **ELECTRIC WINDOW DURABILITY CERTIFICATION**

Cab window roll-up systems can cause maintenance problems if not designed for long service life. The window regulator design will complete 30,000 complete up-down cycles and still function normally when finished. The bidder will certify that sample doors and windows similar to those provided on the apparatus have been tested and have met these criteria without malfunction or significant component wear.

### **SEAT BELT ANCHOR STRENGTH**

Seat belt attachment strength is regulated by Federal Motor Vehicle Safety Standards and should be validated through testing. Each seat belt anchor design will withstand 3000 lb of pull on both the lap and shoulder belt in accordance with FMVSS 571.210 Seat Belt Assembly Anchorages. The bidder will certify that each anchor design was pull tested to the required force and met the appropriate criteria.

### **SEAT MOUNTING STRENGTH**

Seat attachment strength is regulated by Federal Motor Vehicle Safety Standards and should be validated through testing. Each seat mounting design will be tested to withstand 20 G's of force in accordance with FMVSS 571.207 Seating Systems. The bidder will certify that each seat mount and cab structure design was pull tested to the required force and met the appropriate criteria.

### **CAB DEFROSTER CERTIFICATION**

Visibility during inclement weather is essential to safe apparatus performance. The defroster system will clear the required windshield zones in accordance with SAE J381 *Windshield Defrosting Systems Test Procedure And Performance Requirements - Trucks, Buses, And Multipurpose Vehicles*. The bidder will certify that the defrost system design has been tested in a cold chamber and passes the SAE J381 criteria.

### **CAB HEATER CERTIFICATION**

Good cab heat performance and regulation provides a more effective working environment for personnel, whether in-transit, or at a scene. The cab heaters will warm the cab 75 F from a cold-soak, within 30 minutes when tested using the coolant supply methods found in SAE J381. The bidder will certify that a substantially similar cab has been tested and has met these criteria.

### **CAB AIR CONDITIONING PERFORMANCE CERTIFICATION**

Good cab air conditioning temperature and air flow performance keeps occupants comfortable, reduces humidity, and provides a climate for recuperation while at the scene. The cab air conditioning system will cool the cab from a heat-soaked condition at 100 degrees Fahrenheit to an average of 67 degrees

Fahrenheit in 30 minutes. The bidder will certify that a substantially similar cab has been tested and has met these criteria.

### **AMP DRAW REPORT**

The bidder will provide, at the time of bid and delivery, an itemized print out of the expected amp draw of the entire vehicle's electrical system.

The manufacturer of the apparatus will provide the following:

- Documentation of the electrical system performance tests.
- A written load analysis, which will include the following:
  - The nameplate rating of the alternator.
  - The alternator rating under the conditions specified per:
    - Applicable NFPA 1901 or 1906 (Current Edition).
  - The minimum continuous load of each component that is specified per:
    - Applicable NFPA 1901 or 1906 (Current Edition).
  - Additional loads that, when added to the minimum continuous load, determine the total connected load.
  - Each individual intermittent load.

All of the above listed items will be provided by the bidder per the applicable NFPA 1901 or 1906 (Current Edition).