450F BACKHOE LOADER TIER 41 HRC LEICESTER, ENGLAND

Ship Weight lbs

LIST PRICE AT DEALER

Standard Equipment:

BOOMS, STICKS AND LINKAGES

17'3" center pivot backhoe
Excavator style boom with hammer rest
Thumb-ready stick w/gripping edges
Boom transport lock w/auto latching
Swing transport lock
Lifting eye
Pilot operated stabilizer controls
198-degree bucket rotation
Single Tilt (ST) Loader
Bucket level indicator
Loader service brace
Return-to-dig, automatic
Self-leveling loader bucket
Transmission neutralizer switch

POWERTRAIN

Cat C4.4 106kW Engine U.S. EPA T4i EMISSIONS COMPLIANT Electronic, turbo, aftercooled with Water separator with indicator light Thermal starting aid system Dry-type axial seal air cleaner w/auto dust ejection, pre-cleaner & filter indicator Engine fan guard On-the-go 4-wheel drive front axle Front driveshaft guard Power steering, w/secondary steering Hydraulically applied multi-plate wet outboard disk brakes Electronic differential lock Separate driveline parking brakes Torque converter Transmission, Auto-shift (5F, 3R) 25 mph/40 kph level ground max speed Spin-on eng & trans oil filters Spin-on clear bowl water/fuel separator Spin-on secondary fuel filter Firestone 15-19.5 12 ply front tires Firestone 21L-24 16 ply rear tires Consolidated engine service points Open-Circuit-Breather system Diesel particulate filter

HYDRAULICS

Load sensing, variable flow closed center system, 50 gpm 5 Function backhoe hydraulics 2 Function loader hydraulics 6-micron bowl & carriage filter O-ring face seal hydraulic fittings Snap-To-Connect hydraulic couplings Caterpillar XT-3 hose Cat "ToughGuard" XT-3 ES hose

Ride Control

ELECTRICAL

12-volt electrical system
150-ampere alternator
Horn and Backup Alarm
Hazard flashers/turn signals
Halogen head lights (4)
Halogen rear flood lights (4)
Stop and taillights
Audible system fault alarm
Key start/stop system
Ext/int 12-volt power receptacles (2)
Two 880 CCA service-free batteries
Battery disconnect switch

OPERATOR ENVIRONMENT

Lighted gauge group: -coolant temp, fuel, tachometer. Interior rearview mirror ROPS canopy 2-inch retractable seat belt Steering wheel assist knob Hand and foot governor Floor mat, coat hook Cell phone mount Two lockable storage areas Drink and lunch box holders Air suspension seat with arm rests Service harness Tilt steering column Rear fender extensions System fault alarm

OTHER STANDARD EQUIPMENT

Hydrostatic power steering
Toolbox, lockable, external
Vandalism locks & lockable hood
Transport tie-down points
Ground line fill, 44 gal fuel tank
Rubber impact strips on radiator guard
2200 lb counterweight
Tire valve stem protection
Stabilizer cylinder rock guards
Flip style, dual-purpose stabilizer pads
CD-ROM Parts & Backhoe Safety Manuals
Operations and Maintenance Manual
Long life coolant, -30C (-20F)

450F BACKHOE LOADER TIER 41 HRC LEICESTER, ENGLAND

Ship Weight lbs

LIST PRICE AT DEALER

ORDERING INSTRUCTIONS

For an explanation of Lane Strategy and ordering instructions please refer to the sales model 'GENERAL' posted in the web price lists.

You must order your machine from Lane 1, Lane 2 or Lane 3.

Your lane selection will determine the range of additional attachments you may order and the service level you will receive.

LANE 1 DISTRIBUTION CENTER ARRANGEMENTS (DCA's)

If no reference number is listed, a Lane 1 configuration is not available.

TO COMPLETE A LANE 1 ORDER your order must at least contain

1: Distribution Center Arrangment (DCA) See above if available

2: 0P-9001 Lane 1 Order

3: Selection from each section of the 'LANE 1 MANDATORY' section

4: Packing references

450F BACKHOE LOADER TIER 4I HRC LEICESTER, ENGLAND

Ship Weight lbs

LIST PRICE AT DEALER

LANE 2/ LANE 3 FACTORY ARRANGEMENTS

If no reference number is listed, a Lane 2/ Lane 3 configuration is not available.

385-6570 \$164,940

MISCELLANEOUS ORDERS

Not available on this model, all miscellaneous orders should be placed using the ANTARES parts ordering system.

TO COMPLETE A LANE 2 OR LANE 3 ORDER

your order must at least contain

1: A Base Machine Reference. See choices above.
2: Either 0P-9002 (Lane 2) or 0P-9003 (Lane 3) order reference
3: Selection from each section of the 'LANE2/LANE3 MANDATORY' Section

4: Packing references.

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER

LANE SELECTION

LANE 2/ LANE 3 FACTORY ARRANGEMENTS

MACHINES ORDERED FROM THIS SECTION WILL BE SOURCED FROM THE FACTORY

Lane 2 and Lane 3 are dependant on factory availability.

If no reference number is listed, Lane 2 or Lane 3 configurations are not available.

0P-9002	LANE 2 ORDER	NC
	Please select for orders not including the items marked 'FOR USE	
	IN LANE 3 ONLY'	
0P-9003	LANE 3 ORDER	NC
	Currently only Wiring, Product Link requires Lane 3 availability.	

BOOMS, STICKS AND LINKAGES

STICKS

Select one

L	387-8234	STICK, STANDARD 0	NC
L	387-8235	STICK. EXTENDIBLE	\$6,290

BACKHOE BUCKETS

Must select

L	326-7717	BUCKET, HOE, (NONE)	NC
		Ship with no backhoe bucket	
		Backhoe Buckets must be ordered from the WT-BHL Price List	
		from Parts Distribution. For further information see the	
		Field Installed Attachments section at the end of this	

price list.

HYDRAULICS

BACKHOE CONTROLS

Select one

L	385-6577	CONTROLS, PILOT, 5 FUNCTION	\$4,355
		actuated by roller switch on RH joystick.	
L	385-6578	CONTROLS, PILOT, 6 FUNCTION	\$5,490
		Boom, stick, bucket, swing and two additional aux sections	
		actuated by roller switches in LH and RH joysticks.	
L	385-6579	CONTROLS, DYNAHOE, 5 FUNCTION	\$1,215
		Controls from left to right are bucket-stick-boom-swing.	
		The right foot pedal operates the auxiliary function such	
		as extendible stick or Combined Function Auxiliary lines.	

JSE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
HYDI	RAULICS (CONT.)		
В	ACKHOE C	ONTROLS (Cont.)		
	385-6580	CONTROLS, DYNAHOE, 6 FUNCTION Controls from left to right are bucket-stick-boom-swing. The right foot pedal normally operates the extendible stick. The left foot pedal normally operates the auxiliary function such as Combined Function Auxiliary lines.	<.	\$2,365
	385-6581	CONTROLS, FORD, 5 FUNCTION		\$2,150
	385-6582	CONTROLS, FORD, 6 FUNCTION Controls from left to right are stick-boom-bucket-swing. The right foot pedal normally operates the extendible stick The left foot pedal normally operates the auxiliary function such as Combined Function Auxiliary lines.	<.	\$3,275
	Distribution. For Attachments s	S must be ordered from the WT-BHL Price List from Parts or further information see the Field Installed ection at the end of this price list.		
•	112-9177	STD STICK TRANSPORT GROUP		NC
1	374-7863	E-STICK TRANSPORT GROUP	0	NC
	OADER HYL Select one	DRAULICS		
	387-8237	HYDRAULICS, LOADER, GP, PILOT	, 5 Function or , 6 Function or unction or	NC
	387-1575	HYDRAULICS, LOADER, MP, PILOT Includes valve section for operating MP style loader bucket Can be used with all loader bucket selections. FOR USE WITH: 112-9177 Bucket, Loader (None) or 270-9163 Bucket, 1.75 CYD GP or 272-1700 Bucket-MP, 1.5 CYD, W/Forl 272-1701 Bucket-MP, 1.5 CYD CANNOT BE USED WITH: 385-6579 Controls, Dynahoe, 385-6580 Controls, Dynahoe,	0 ets. ks or , 5 Function or	\$1,740
	387-8238	385-6581 Controls, Ford, 5 F 385-6582 Controls, Ford, 6 F HYDRAULICS, LOADER, GP, MECH FOR USE WITH: 112-9177 Bucket, Loader (None) or 270-9163 Bucket, 1.75 CYD GP CANNOT BE USED WITH: 385-6577 Controls, Pilot, 5 F 385-6578 Controls, Pilot 6 Fu	unction or unction O unction	NC

450F-005

450F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
HY	DRAULICS (CONT.)		
	LOADER HY	DRAULICS (Cont.)		
L	387-1577	HYDRAULICS, LOADER, MP, MECH Includes valve section for operating MP style loader buck FOR USE WITH: ALL LOADER BUCKET SELECTIONS. CANNOT BE USED WITH: 385-6577 Controls, Pilot, 5 385-6578 Controls, Pilot, 6	kets Function or	\$1,740
OPI	ERATOR ENV	IRONMENT		
	CAB/ CANOR Select one	Pγ		
L	387-1581	CANOPY, ROPS	column,	NC
L	387-1582	CAB, ROPS, DELUXE, W/AC Includes window defroster, front and rear windshield wip system, A/C, heater/pressurizer, left and right side doors coat hook, interior rearview mirror, tilt steering column, air-suspension fabric seat, radio-ready headliner, two into one external power receptacles, system indicators for hy service and hydraulic temp warning, deluxe air suspension and auto-up stabilizers.	per/washer with locks, floor mat, ernal and /draulic filter	\$10,390
	SEAT BELT Select one			
L	206-1747	BELT, SEAT, 2" SUSPENSION	0	NC
L	206-1748	SEAT BELT, 3" SUSPENSION		\$105
INS	TRUCTIONS			
	DECAL PACE Must select	KAGE		
P	391-2134	INSTRUCTIONS, ANSI	pt for	NC
	INSTRUCTIO Must select	NS AND OPERATION MANUALS		
	421-8926	SERIALIZED TECHNICAL MEDIA KIT	equired	NC

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
UJL	IVO.		ius	AT DEALER

NOTE

Optional Attachments - Select if required.

HYDRAULICS

QUICK DISCONNECTS

Р	132-8769	COUPLING, QUICK DISCONNECT	4	\$491 NI
		JXILIARY LINES mbined auxiliary lines if using a thumb.		
L	387-1585	Provides diverter valve and hydraulic 3/4" lines routed to midpoint of stick for use with one-way or two-way flow work tools. Includes hydraulic quick disconnect couplings. REQUIRES: 387-8234 Stick, Standard and 385-6577 Controls, Pilot, 5 function or 385-6578 Controls, Pilot, 6 Function	0	\$3,235
L	387-1586	LINES, ONE-WAY, E-STICK Provides hydraulic 3/4" lines routed to midpoint of stick for use with hammers, compactors and other one-way flow work tools. E-stick retract function operates one-way flow work tools. Includes hydraulic quick disconnect couplings. CAN BE USED WITH ANY BACKHOE CONTROLS REQUIRES: 387-8235 Stick, Extendible ("E")	0	\$3,050
L	387-1587	LINES, COMB AUX, E-STCK, PILOT Provides diverter valve and hydraulic 3/4" lines routed to midpoint of stick for use with one-way or two-way flow work tools. Includes hydraulic quick disconnect couplings. REQUIRES: 387-8235 Stick, Extendible ("E") and 385-6578 Controls, Pilot, 6 Function	0	\$3,275
L	387-1588	Provides diverter valve and hydraulic 3/4" lines routed to midpoint of stick for use with one-way or two-way flow work tools. Includes hydraulic quick disconnect couplings. REQUIRES: 387-8234 Stick, Standard and 385-6579 Controls, Dynahoe, 5 Function or 385-6580 Controls, Dynahoe, 6 Function or 385-6581 Controls, Ford, 5 Function or	0	\$3,235
L	387-1589	385-6582 Controls, Ford, 6 Function LINES,COMB AUX, E-STICK, MECH Provides diverter valve and hydraulic 3/4" lines routed to midpoint of stick for use with one-way or two-way flow work tools. Includes hydraulic quick disconnect couplings. REQUIRES: 387-8235 Stick, Extendible ("E") and 385-6580 Controls, Dynahoe, 6 Function or 385-6582 Controls, Ford 6 Function	0	\$3,275

450F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
ELEC	TRICAL			
P	211-4292	BEACON, MAGNETIC MOUNT	0	\$224 NI
PF	RODUCT LI	NK		
L	331-5489	WIRING, PRODUCT LINK 321 SR FOR USE IN LANE 3 ONLY Provides tracking of machine location, service meter he and diagnostic codes through GPS technology. Available to dealers in licensed countries, to verify if a exists for your territory please contact Caterpillar mark Requires service subscription.	ours license	\$2,169
C	OLD WEAT	HER PACKAGE		
L	422-1418	COLD WEATHER PACKAGE, 120V	freeze ribution	\$625
OTHE	R ATTACH	IMENTS		
BA	ACKHOE B	UCKET STOPS		
P P	303-4603 337-6851	STOPS, BUCKET	3.	\$174 \$557
FLUID	os			
C	OLD WEAT	HER FUEL		
L	396-6505	FUEL, COLD WEATHER		\$68
FIELD	INSTALLE	D ATTACHMENTS		
	DADER BU (AVAILABLE FF	CKETS ROM PARTS DISTRIBUTION		
	270-9163 272-1701	BUCKET-GP, 1.75 CYD 1.75 cu. yd. SAE capacity General Purpose. For use in material. Includes bolt on reversible cutting edges. BUCKET-MP, 1.5 CYD	low-density	
	272-1701	Includes fork mounting brackets. REQUIRES: 387-1575 Hydraulics, Loader, MP BUCKET-MP, 1.5 CYD, W/ FORKS 1.5 cu. yd. SAE capacity Multi-Purpose. Includes bolt of cutting edges. Includes flip-over forks.	on reversible	

USE REF LANE 2 / 3 OPTIONAL Ship Weight LIST PRICE Ibs AT DEALER

FIELD INSTALLED ATTACHMENTS (CONT.)

BACKHOE BUCKETS

AVAILABLE FROM PARTS DISTRIBUTION

278-4499 BUCKET-HD, 18", 6.3 CFT

278-4487 BUCKET-HD, 24", 9.5 CFT

278-4493 BUCKET-HD, 30", 12.4 CFT

275-4026 BUCKET-HD, 36", 15.5 CFT

OPTIONAL ITEMS

AVAILABLE FROM PARTS DISTRIBUTION

132-8769 COUPLING, QUICK DISCONNECT

Includes one additional male and female flat face hydraulic quick disconnect. Compatible with Caterpillar work tools.

FOR USE WITH: All Backhoe work tools.

281-7219 KIT, DEBRIS SCREEN

For open canopy units in hammer operation. Kit includes enclosed

cab rear and corner glass to deflect flying objects.

Reference media number REHS3134

PACKING

Must Select

0G-3274	PACK, ROLL ON/ROLL OFF BY SEA	\$221 NET
	Preparation for shipment by sea. Complete machine.	
0G-3273	CYLOWAX APPLICATOR	\$105 NET
	Preparation for shipment - Silix applicators recommended for	
	shipment by sea.	