



Hall-Mark Fire--3431 NW 27th Ave--Ocala, FL 34475

**KEY WEST FIRE DEPARTMENT**  
1600 N. ROOSEVELT BLVD  
KEY WEST, FL 33040  
DAVID FRAGA

---

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Type:** 3  
**Model:** 453  
**Rev 2** Print Features **11809**

**CATEGORIES:**

- A** Chassis
- B** Body Connection Pass Thru Type
- BH** Chassis Accessories
- BL** Chassis Electrical
- C** Conversion Model
- CB** Module Body Modifications
- D** Module Body Hardware
- E** Paint and Striping
- F** Cabinet Doors, Handles and Hardware
- G** Interior Colors
- H** Interior Cabinets, Streetside
- I** Interior Cabinets, Curbside
- J** Front Wall Cabinets
- K** Interior Accessories and Trim
- L** Cot Mount, and Patient Handling
- M** Warning Systems, Visual
- MN** Warning Systems, Audible
- O** Lights, Non Emergency
- P** Electrical Power Group
- Q** Heat, Ventilation, Air conditioning
- R** Console, Radio, and communications
- T** Oxygen and Suction
- U** Lettering and Graphics
- Z** Other

KEY WEST FIRE DEPARTMENT  
1600 N. ROOSEVELT BLVD  
KEY WEST, FL 33040  
DAVID FRAGA



# Selected Feature List 11809

Year: 2014  
Chassis: Ford Type III, 138"WB, 80"  
Model: 453

Option   Std Qty   Header/Description/Data   Proposal Total

**AB**   **Horton Emergency Vehicles Feature List**

**AC**   **CHASSIS**

AFE   1   1   FORD E-SERIES CHASSIS

AFE36014   0   1   CHASSIS, 2014 FORD 138" E-350 DUAL WHEEL CUTAWAY-GAS

The chassis required to complete the ambulance conversion shall be supplied by Horton.

!!! STOCK CHASSIS.

AJNSPIC0   1   1   CHASSIS INTERIOR COLOR SHALL BE GRAY

AOSPD001   0   1   CHASSIS: FIN

This chassis is eligible for Ford fleet discount incentive.

\$4,800 GPC DISCOUNT

FIN Code: QJ185

**B**   **CHASSIS MODIFICATIONS, HARDWARE AND ACCESSORIES**

BH02A300   1   1   STAINLESS STEEL WHEEL COVERS

Stainless steel wheel covers shall be installed.

BH03A000   1   1   MUD FLAPS: front

Install rubber mud flaps behind each front tire.

**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

<b>BH03B000</b>	1	1	<b>MUD FLAPS: rear</b> Install individual rear mud flaps behind each set of rear wheels.	
<b>BH070000</b>	1	1	<b>REINFORCE REAR BUMPER END CAPS</b> Reinforce end caps of rear bumper for greater impact resistance. <i>A SECTION OF 2" X 2" STEEL ANGLE SHALL BE ATTACHED TO THE BACK SIDE OF THE STD HORTON STEP.</i>	
<b>BH08H000</b>	0	1	<b>RUNNING BOARDS: STAR PUNCHED</b> Install heavy duty aluminum diamond plate running boards and splash shields. Running boards are to be star punched for enhanced drain and foot grip.	
<b>BH110000</b>	1	1	<b>REAR STEP/ BUMPER ASSEMBLY</b> The center section of the rear step bumper shall be constructed of aluminum grip strut and be hinged to assist in patient handling.	
<b>BHSPD006</b>	1	1	<b>MIRROR: OEM</b> The mirror set shall be OEM supplied, and installed by the chassis manufacturer.	
<b>BL070000</b>	1	1	<b>BATTERIES, STANDARD ON TYPE III CHASSIS</b> (2) batteries shall be installed in the specified battery compartment on a pull out tray.	
<b>BL26B000</b>	1	1	<b>BACKUP ALARM RESET</b> Backup alarm to automatically reset to on if alarm was manually canceled using the control panel alarm cut-off switch (FL25) during previous use.	
<b>BL26J000</b>	0	1	<b>REVERSE CAMERA WITH WINDSHIELD MOUNTED MONITOR</b> Install a Voyager VCCS155 backup camera over the rear doors. Install a Voyager AOM562HD 5.6" OR 7" LCD screen in the cab upper windshield area. Wire to activate when the vehicle is placed into reverse. <i>SELECT MONITOR SIZE: (7" not recommended for type 3 vehicles)</i> [ ] 5.6" [ ] 7"	



# Selected Feature List 11809

Year: 2014  
 Chassis: Ford Type III, 138"WB, 80"  
 Model: 453

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

BL32A000	1	1	<b>OEM AM/FM/CD PLAYER SHALL BE PROVIDED BY THE OEM MANUFACTURER</b>  OEM AM/FM/CD player shall be provided by the OEM manufacturer on all Horton supplied chassis.  <i>NOTE: THIS OPTION APPLIES ONLY TO CHASSIS SUPPLIED BY HORTON.</i>	
----------	---	---	---	--

C	CONVERSIONS			
---	-------------	--	--	--

CA450000	0	1	<b>CONVERSION MODEL: 453-3 FORD:</b>  MINIMUM BODY DIMENSIONS: (Exterior) -Height: 89" -Width: 96" -Length: 145" (Interior) -Height: 72" -Aisle: 20" -Width: 20" (from edge of cot in wall position to squad bench riser) -Length: 141" OVERALL DIMENSIONS (Including Chassis, Module and Step): -Height: 110.5" (to top of vent) -Width: 100" -Length: 245"  <i>!!! CUSTOM BODY. INCREASE BODY LENGTH 4.00" TO 149.75". THE ADDITIONAL 4" IS ADDED TO THE STREETSIDE AND CURBSIDE COMPARTMENTS.            !!! DELETE EXTERIOR COMPARTMENT #1</i>	
----------	---	---	---	--

CA450001	1	1	<b>453 STREET SIDE, FRONT:</b>  Clear Door Opening: 16.7" wide x 79.1" high Actual Dimension: 19.4" wide x 82.1" high x 20.3" deep This area shall be accessed through a single outside hinged door. The compartment shall house the vehicle's primary O2 cylinder. The compartment shall be vented to the outside.	
----------	---	---	---	--

tn01aa00	0	1	<b>OXYGEN BOTTLE, RE-LOCATION OF O2 TANK TRACK</b>  The location of the O2 bottle shall be changed per the information listed below.  <i>LOCATE: STREETSIDE REAR COMPARTMENT.</i>	
----------	---	---	---	--

CA450002	1	1	<b>453 STREET SIDE, INTERMEDIATE:</b>  Clear Door Opening: 27.7" wide x 26.3" high Actual Dimension: 33.2" wide x 29.5" high x 20.3" deep This area shall be accessed through a single, outside hinged door.	
----------	---	---	--	--



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Oty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

0	1		<b>COMPARTMENT WIDTH Modify: first, street side</b>	
cb040w00			The width of the standard compartment for this model shall be modified. This is the first street side compartment width modification and shall include affected modifications to the interior cabinet.  <i>Width Modification: INCREASE COMPARTMENT WIDTH AS WIDE AS POSSIBLE FOR DELETION OF SS FORWARD COMPARTMENT.</i>	
CA450004	1	1	<b>453 STREET SIDE, REAR:</b> Clear Door Opening: 27.9" wide x 26.3" high Actual Dimension: 32.5" wide x 29.5" high x 20.3" deep This area shall be accessed through a single outside hinged door.  <i>!!! SINGLE LEFT HINGED EXTERIOR DOOR. !!! DOOR TO OPEN AS WIDE AS POSSIBLE WHILE STILL USING A GAS CYLINDER HOLD OPEN.</i>	
0	1		<b>COMPARTMENT HEIGHT Modify: first, street side</b>	
cb040000			The height of the standard compartment for this model shall be modified. This is the first street side compartment height modification and shall include affected modifications to the interior cabinet.  <i>Height Modification: INCREASE 32.00"</i>	
0	1		<b>COMPARTMENT WIDTH Modify: second, street side</b>	
cb04aw00			The width of the standard compartment for this model shall be modified. This is the second street side compartment width modification and shall include affected modifications to the interior cabinet.  <i>Width Modification: INCREASE 4.00"</i>	
0	2		<b>SHELF FOR LED LIGHTED VERTICAL COMPARTMENT</b>	
dr08l000			A diamond plate adjustable shelf shall be installed in the following location.  <i>LOCATE: INSTALL THE BOTTOM OF THE LOWER SHELF 40" ABOVE THE COMPARTMENT FLOOR. SPACE THE REMAINING SHELF EVENLY ABOVE.</i>	
0	1		<b>DIVIDER FIXED, VERTICAL COMPARTMENT</b>	
dr11a000			Install a 16" deep fixed vertical divider shall be installed in the location listed below. (Divider material is to match the compartment material)  <i>LOCATE: 11.50" FROM RIGHT COMPARTMENT WALL. FABRICATE FROM D/A FINISHED FLAT ALUMINUM. !!! INSTALL ROK BACKBOARD STRAP ON THE LEFT SIDE OF THE DIVIDER TO SECURE THE STAIR CHAIR.</i>	



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
dr11p000	0	1	<b>STAIR CHAIR POCKET, RECESSED</b> A pocket that is 40" high x 10" wide x 1.2" deep shall be recessed into the inner compartment door panel. The pocket shall be installed as close to the bottom and hinged side of door as possible unless otherwise specified.  <i>Locate:</i> LOCATE: DIRECTLY FORWARD OF THE O2 DIVIDER.	
dr150000	0	1	<b>SPECIAL INSTRUCTION, COMPARTMENT</b>  !!! INSTALL THE O2 BOTTE BRACKET ON THE BACK COMPARTMENT WALL, RIGHT SIDE. INSTALL THE BRACKET ON WALL APROX 6" ABOVE THE FLOOR TO ALLOW FOR STORAGE OF "D" BOTTLES UNDERNEATH.	
CA450005	1	1	<b>453 CURB SIDE, REAR:</b> Clear Door Opening: 9.9" wide x 79.1" high Actual Dimension: 10.7" wide x 82.1" high x 20.3" deep This area shall be accessed through a single outside hinged door. This area shall house the vehicle's backboards  !!! COMPARTMENT DOOR TO BE LEFT HINGED ILOS. DOOR TO OPEN AS FAR AS POSSIBLE USING GAS CYLINDER HOLD OPEN.	
cb060w00	0	1	<b>COMPARTMENT WIDTH Modify: first, curbside</b> The width of the standard compartment for this model shall be modified. This is the first curbside compartment width modification and shall include affected modifications to the interior cabinet.  WIDTH MODIFICATION: INCREASE 4.00"	
dr150000	0	1	<b>SPECIAL INSTRUCTION, COMPARTMENT</b>  !!! INSTALL A D/A FINISHED FLAT ALUMINUM BACKBOARD RETENTION BAR 66" ABOVE THE COMPARTMENT FLOOR. ATTACH TO THE LEFT SIDE OF THE COMPARTMENT DOOR FRAME AND BREAK BACK TO THE DIVIDER.	
CA450006	1	1	<b>453 CURBSIDE INTERMEDIATE:</b> Clear Door Opening 24.6" wide x 16.6" high Actual Compartment: 32" wide x 19.5" high x 20.3" deep This area shall be accessed through a single, outside hinged door	
cb060000	0	1	<b>COMPARTMENT HEIGHT MODIFY: first, curbside</b> The height of the standard compartment for this model shall be modified. This is the first curbside compartment height modification and shall include affected modifications of the interior cabinet.  HEIGHT MODIFICATION: INCREASE TO THE BOTTOM OF THE BENCH CUSHION.	



# Selected Feature List 11809

Year: 2014  
 Chassis: Ford Type III, 138"WB, 80"  
 Model: 453

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

**CA450007 1 1 453 CURB SIDE, FRONT:**

Clear Door Opening: upper 16.5" wide x 65" high  
 lower 16.5" wide x 12.6" high  
 Actual Dimensions: upper 21.7" wide x 65" high x 30" deep  
 lower 21.7" wide x 12.6" high x 20.3" deep

This area shall be accessed through two outside hinged doors and from an opening located on the curb side forward wall. The upper area shall be primarily used for storage of customer furnished jump kits, the lower area for storage of two batteries on a rollout tray.

!!! INSTALL ALL ADD-ON ELECTRICAL COMPONENTS IN THE COMPARTMENT SUBFLOOR AREA.

**CAB90000 0 1 LE Package**

This unit will receive aluminum composite cabinetry, LE style insulation package and double bolt tie-down style mounts ilos. See below.

Sales note: You must delete CB09SA00, DH000000 and H.  
 You must add CB09SAA0, DH000001 and H4.

**CAB93AF0 0 1 KKK-A-1822F CERTIFICATION LABEL**

The vehicle shall have weight/payload, electrical load and KKK-A-1822F certification stickers installed in the O2 compartment.

**CB BODY MODIFICATIONS/OPTIONS**

**CB06SX00 0 1 DOUBLE STEP CURBSIDE ENTRY 6" DROP SKIRT**

The curbside skirt, forward of the rear wheel well shall be dropped 6 inches. Two integral ALD steps within the side patient door step well shall be available upon opening the side door for easier and lower access to the patient compartment.

**CB09SAA0 0 1 LE style insulation package**

Install LE style insulation package ILOS.

KEY WEST FIRE DEPARTMENT  
1600 N. ROOSEVELT BLVD  
KEY WEST, FL 33040  
DAVID FRAGA



# Selected Feature List 11809

Year: 2014  
Chassis: Ford Type III, 138"WB, 80"  
Model: 453

---

<u>Option</u>	<u>Std</u>	<u>Oty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

---

**CBSP0001 0 1 SPECIAL INSTRUCTION, BODY MODIFICATIONS**

!!! DELETE DOLPHIN SPRAY TO THE INSIDE OF THE BODY ONLY  
!!! MOUNT WITH DOUBLE-BOLT BODY TIE-DOWN SYSTEM ILOS VI-TECH  
!!! DO NOT FOAM BODY TUBES  
!!! DELETE THE 0.125" FLOOR SOUND BARRIER.  
!!! INSTALL 0.50" COMPOSITE COOSA BOARD SUB-FLOOR ILOS.  
!!! HOPS DELETED

**CBSP0003 0 1 SPECIAL INSTRUCTION, BODY MODIFICATIONS**

!!! REINFORCE THE CEILING AT THE HEAD OF BENCH FOR CARGO NET INSTALLATION.

**CBSP0004 0 1 SPECIAL INSTRUCTION, BODY MODIFICATIONS**

!!! NOTE FRONT FACE LIGHT LAY-OUT.

---

<b>D</b>	<b>MODULE BODY HARDWARE</b>
----------	-----------------------------

---

**DG05C100 0 1 PRIVACY WINDOWS, REAR MODULE BODY ENTRY DOORS**

The rear module entry doors shall have solid windows. The windows shall have dark privacy glass. The windows shall meet FMVSS glazing standards. No films are to be used.

**DG06C200 0 1 PRIVACY WINDOW, SLIDING FOR SIDE ENTRY DOOR**

The side entry door shall have a sliding window. The window shall have dark privacy glass. The window shall meet FMVSS glazing standards. No films are to be used.

**DG080000 1 1 EMERGENCY DOOR RELEASE MECHANISM**

Install standard emergency release knobs on top and bottom of rear module entrance doors.



**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

Option    Std    Oty    Header/Description/Data    Proposal Total

---

- DH000001    0    1    **Double bolt tie-down style body mounts**  
 Install tie down style body mounts.
  
- DH03B000    1    1    **MIRROR STAINLESS STEEL SPLASH SHIELDS**  
 Install #8 mirror stainless splash shields on the lower front face of the body just behind the cab access doors. These splash shields are to be the same height as the diamond plate front corner guards.  
 !!! SEE OL41C000 FOR RUNNING BOARD LIGHTS
  
- DH04B000    0    1    **MODULE BODY FENDERS: rubber**  
 Rubber extruded fenders shall be installed around the rear wheel well opening.
  
- DH050000    0    1    **RUB RAILS, RUBBER**  
 The lower body rub rails shall be rubber ILOS>
  
- DH330000    1    1    **REAR DOOR HOLD OPENS, GRABBER**  
 Install chrome Cast Products "Grabber" style rear door hold opens.  
 (NOTE: HOLD OPENS MUST BE RELOCATED IF TELESCOPIC LIGHTS ARE ORDERED)
  
- DH660000    0    1    **FUEL FILL PLATE**  
 Install a stainless steel plate on the body face below the fuel fill housing.
  
- DL480000    0    1    **ELECTRIC DOOR LOCKS: compartment**  
 Install power activated door locks on all exterior compartment doors. Locks to be activated by a switch at each patient area access door. Locks may be overridden by a door key. A separate lock switch will be located in the front radio console if option DL48D000 (wired to OEM locks) is not selected.
  
- DL48A000    1    1    **ELECTRIC DOOR LOCKS: access doors**  
 Install power activated door locks on all patient area access doors. Locks to be activated by a switch at each patient area door, and controlled with the access door locks. Locks may be overridden by a manual slide lever or by the door key. A separate lock switch will be located in the front radio console if option DL48D000 (wired to OEM locks) is not selected.

**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

<b>DL48B000</b>	0	1	<b>ELECTRIC DOOR SWITCH: concealed</b> Install a concealed switch on the exterior of the vehicle to operate the power door lock circuit. Doors shall be wired to unlock only on this circuit.  <i>LOCATE: UNDER STREETSIDE FORWARD BODY CORNER POST</i>	
-----------------	---	---	--	--

<b>DL48D000</b>	0	1	<b>ELECTRIC DOOR LOCKS WIRED TO OEM SWITCHES</b> The module door locks and compartment locks (if ordered) are to be wired to the chassis door lock switches.	
-----------------	---	---	---	--

<b>DLH40000</b>	0	1	<b>RECESSED LICENSE PLATE BRACKET</b> A Cast Products #LP0002 recessed license plate bracket shall be installed per the attached drawing. The bracket will include lighting in the top to illuminate the license plate.  <i>LOCATE: CENTERED IN REAR RISER</i>	
-----------------	---	---	---	--

<b>DM100000</b>	1	1	<b>REFLECTORS:</b> All patient compartment entry doors shall have red reflectors in the lower corner.	
-----------------	---	---	--	--

<b>DR220000</b>	1	1	<b>RUBBER MATTING IN EXTERIOR COMPARTMENTS</b> Ribbed rubber matting will be installed on the floor and shelves of all exterior compartments.	
-----------------	---	---	--	--

<b>DR23A000</b>	1	1	<b>RUBBER COVERED WALLS IN BACKBOARD COMPARTMENT</b> The interior of the backboard compartment is to be covered with rubber matting to protect equipment stored in this area.	
-----------------	---	---	--	--

<b>E</b>	<b>PAINT AND STRIPING</b>			
----------	---------------------------	--	--	--

<b>ED020000</b>	0	1	<b>CHASSIS PAINT: other color</b> Paint CHASSIS special color  <i>PAIN T COLOR: RED FLNA 3042            WHITE FLNA 40117</i>  <i>PAIN T CHASSIS ROOF WHITE FROM JUST BELOW THE WINDOWS. CHASSIS HOOD TO REMAIN RED.</i>	
-----------------	---	---	---	--

**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

ED050000	0	1	<b>MODULE PAINT: other color</b> Paint MODULE special color  COLOR: RED NUMBER: FLNA 3042  COLOR: WHITE NUMBER: FLNA 40117  !!! PAINT THE BODY RED FROM THE TOP OF THE DRIP RAILS DOWN. ENTIRE DRIP RAILS ARE TO BE RED. !!! PAINT THE ENTIRE MODULE ROOF WHITE FROM THE DRIP RAILS UP.	
----------	---	---	---	--

ED20PS00	1	1	<b>PAINT PANEL: sample</b> A painted test panel shall be prepared with the following paint color and number, to confirm correct paint selection. The panel will be mailed as designated.  COLOR: RED NUMBER: FLNA 3042	
----------	---	---	--	--

ED5E0000	0	1	<b>DIAMONDGRADE CHEVRONS-AROUND REAR DOORS</b> Install Diamondgrade chevron striping on the rear of the body around the rear doors. Install inboard of the corner posts and below the upper driprail.  Colors: RED/GOLD	
----------	---	---	--	--

<b>F INTERIOR CABINET DOORS, HANDLES &amp; HARDWARE</b>				
---	--	--	--	--

FE010000	1	1	<b>FULL HEIGHT PULL HANDLES ON SLIDING PLEXIGLAS DOORS</b> All sliding cabinet doors to have full length pull handles.	
----------	---	---	---	--

FE01FT00	1	1	<b>LATCH, HINGED DOOR: Southco flush stainless steel pull style</b> Install stainless flush mount Southco pull latches on the hinged interior cabinet doors.	
----------	---	---	---	--

FE02A000	1	1	<b>PLEXIGLAS COLOR: light tint</b> All Plexiglas doors to be light tint.	
----------	---	---	---	--

**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

<b>FE060000</b>	1	1	<b>STAINLESS STEEL COUNTER TOPS (STANDARD)</b> Stainless steel pan formed counter tops shall be installed in the patient area.	
-----------------	---	---	---	--

<b>FE08ST00</b>	1	1	<b>INHALATION PANEL (STANDARD):</b> The inhalation panel is to be fabricated from composite material and covered with Formica to match to color selected.  !!! ILOS, INSTALL CONCEPT 3 STYLE INHALATION PANEL WITH INTELLIPLEX. PANEL IS HINGE-DOWN FOR SERVICE ACCESS AND INCLUDES O2 SHUT-OFF VALVE CONTROL. LOCATE PER DRAWING.	
-----------------	---	---	---	--

<b>G INTERIOR COLORS, UPHOLSTERY AND SEATING</b>				
--	--	--	--	--

<b>GF01R000</b>	0	1	<b>INTERIOR COLOR SCHEME: Custom</b> Interior colors are as follows:  FLOOR: LONCOIN FLECKSTONE BLACK ONYX 150 UV RISER: WILSONART FASHION GRAY #D381 WALL: WILSONART FASHION GRAY #D381 CABINET: FASHION GRAY PAINT UPHOLSTERY: GRAYSTONE US425 CHARCOAL COUNTER: STAINLESS STEEL	
-----------------	---	---	--	--

<b>GF02M000</b>	1	1	<b>INSIDE CABINET FINISH: paint</b> The interior of all aluminum cabinets shall have a durable paint finish. The painted surface shall be washable and non-absorbent. See the appropriate Interior Color Scheme option for paint color information.	
-----------------	---	---	--	--

<b>GF02P000</b>	1	1	<b>RISERS:</b> The interior of this vehicle is to contain no wood or wood products. The risers are to be made of reinforced structural composite board covered with Formica per the color description. Formica will not be installed on the risers if stainless steel riser options are selected.	
-----------------	---	---	--	--

KEY WEST FIRE DEPARTMENT  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

Year: 2014  
 Chassis: Ford Type III, 138"WB, 80"  
 Model: 453

Option	Std	Oty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

**GK12C000 0 1 HIGH BACK CHILD SAFETY SEAT**

Delete the standard attendant seat cushion. Install a high back bucket seat with built in child seat restraints. The seat to be adjustable front to rear.

NOTE: NOT AVAILABLE WITH HOPS SYSTEM.

!!! INSTALL WITH AN EVS CBDL SEAT BASE. HINGE DOWN DOOR TO OPEN FACING REAR OF VEHICLE.

**H INTERIOR CABINTRY, STREET SIDE**

**HK010000 1 1 CABINET TRIM**

Install smooth radiused trim on all applicable interior cabinets.

**HK01A000 1 1 STREETSIDE WALL WITHOUT CPR SEAT**

Street side cabinet wall to be per drawing.

NOTE: THIS OPTION DELETES THE TUBULAR AIR BAG FOR THE CPR SEAT.

!!! CUSTOM CABINET WALL "A" PER DRAWING. STANDARD ALUMINUM CONSTRUCTION STYLE CABINETS.

!!! INCLUDE A CENTER DIVIDER IN THE UPPER INHALATION CABINET WITH ONE ADJUSTABLE SHELF ON EACH SIDE. (HK160000)

!!! ALL SHELVES TO HAVE ONLY 1/2" LIP ON THE INBOARD EDGE.

!!! NOTE CONCEPT 3 STYLE INHALATION PANEL PER FE08ST00.

**HK11A000 0 1 DRUG BOX: enclosed**

A separate drug storage box shall be fabricated and installed within the cabinet as designated in the cabinet wall diagram

Locate: CABINET ABOVE ACTION AREA TOWARDS FRONT. INSTALL ON BOTTOM OF SHELF. BOX TO BE 12"W x 6"H ID. INSTALL MEDCO SECURITY LOCK AND SUPPLY THREE KEYS.

**HK160000 0 4 EXTRA SHELF: interior**

Install an additional adjustable shelf.

LOCATE: (1) UPPER INHALATION CABINET. LOCATE ONE ON EACH SIDE OF THE DIVIDER. (ONE STANDARD, ONE EXTRA)  
 (3) ONE SHELF IN EACH CABINET PER DRAWING.

!!! SHELF TO HAVE ONLY 1/2" LIP ON INBOARD EDGE.

KEY WEST FIRE DEPARTMENT  
1600 N. ROOSEVELT BLVD  
KEY WEST, FL 33040  
DAVID FRAGA



# Selected Feature List 11809

Year: 2014  
Chassis: Ford Type III, 138"WB, 80"  
Model: 453

Option   Std   Qty   Header/Description/Data   Proposal Total

## INTERIOR CABINETS AND SQUAD BENCH, CURB SIDE

- IA200000**   1   1   **SQUAD BENCH STORAGE:**  
Storage shall be provided under the bench cushions. The area shall run where possible under the bench. The storage pan shall be fabricated from aluminum and shall be accessed by raising the split cushions.  
*!!! REAR BENCH CUSHION TO BE FIXED.*
- IG09E000**   0   1   **CARGO NET AT HEAD OF BENCH**  
Install a cargo net at the head of the bench. Net to be removeable for cleaning purposes.
- IG10A000**   1   1   **BENCH HOLD OPENS: gas**  
Install gas spring hold opens on squad bench lid.  
*!!! FOR FORWARD CUSHION ONLY*
- IG10Q000**   1   1   **BENCH HOLD-DOWN: paddle latches (Pair)**  
Install recessed paddle latches into the squad bench riser to retain the squad bench lids in the closed position. The latches shall be both passive and positive.  
*!!! FOR FORWARD CUSHION ONLY. REAR CUSHION FIXED.*
- IG15A000**   1   1   **BENCH CUSHION EDGE TRIM:**  
Trim bench cushion edge with protective aluminum trim, to protect horizontal edge of squad bench cushion from tears..
- IG15B000**   1   1   **BENCH BACK CUSHION: full size**  
Delete individual squad bench back cushions. Install full size cushion.

**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Oty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

<b>IK18AA00</b>	<b>1</b>	<b>1</b>	<b>CURBSIDE OVERHEAD CABINET: hinged doors</b>  Storage shall be provided above the squad bench. The storage shall run the full length of the squad bench and shall be accessed through hinged Plexiglas doors that are held in the open position with gas activated rods. The entire cabinet shall be fabricated from aluminum. The cabinet is to be 9" H to meet current K requirements.  <i>!!! STANDARD ALUMINUM CONSTRUCTION STYLE CABINETS.</i>  <i>!!! CABINET TO HAVE (2) HINGED PLEXI DOOR WITH A GAS SHOCK AT EACH END.</i>	
-----------------	----------	----------	---	--

<b>ISP00001</b>	<b>0</b>	<b>1</b>	<b>SPECIAL INSTRUCTION, CURBSIDE CABINETRY</b>  <i>!!! INSTALL SHARPS/WASTE STORAGE AT THE HEAD OF BENCH SIZED FOR (2) 8970 CONTAINERS.</i> <i>!!! TOP TO INCLUDE A HINGE-UP FRAME WITH RED LAMINTE COVERED ALUMINUM SLIDING DOORS.</i> <i>!!! INCLUDE A HORIZONTAL INTERIOR DIVIDER WITH DROP-IN OPENINGS TO HOLD THE CONTAINERS.</i> <i>!!! TOP OF LIFT-UP FRAME TO BE APPROX EVEN WITH THE TOP OF THE BENCH CUSHION.</i>	
-----------------	----------	----------	--	--

<b>J INTERIOR CABINETS, FRONT</b>				
-----------------------------------	--	--	--	--

<b>JAK03000</b>	<b>1</b>	<b>1</b>	<b>FRONT WALL CABINET:</b>  The front wall cabinet shall be arranged per drawing. Additional configuration information may follow.  <i>CABINET WALL FINISH: FASHION GRAY PAINT.</i>	
-----------------	----------	----------	---	--

<b>JE040000</b>	<b>4</b>	<b>4</b>	<b>FRONT WALL DOORS: Plexiglas</b>  Front cabinet wall to have hinged Plexiglas doors, and latch type as designated.  <i>TYPE: PLEXIGLAS</i> <i>LATCH STYLE: SOUTHCO</i>	
-----------------	----------	----------	---	--

<b>JK140000</b>	<b>0</b>	<b>1</b>	<b>CROSSOVER CABINET</b>  An aluminum crossover cabinet is to be installed above the walkthrough/passthrough and is to include a solid hinged door.  <i>!!! FOR INTELLIPIX ELECTRONICS.</i>	
-----------------	----------	----------	---	--



# Selected Feature List 11809

Year: 2014  
 Chassis: Ford Type III, 138"WB, 80"  
 Model: 453

Option   Std   Oty   Header/Description/Data   Proposal Total

<b>K</b>	<b>MODULE INTERIOR ACCESSORIES AND TRIM</b>			
----------	---	--	--	--

- KG02A000   0   2   I.V. HOOKS: Perko**  
 Install Perko I.V. hook where indicated.  
*LOCATE:   SHIP LOOSE*
  
- KG02B000   2   1   IV HANGER, CAST PRODUCTS WITH RUBBER ARM**  
 Cast products recessed IV hangers with rubber arms for attaching solution bags shall be installed in the designated locations.  
*LOCATE:   BENCH SIDE PER DRAWING*
  
- KG09B000   1   1   CEILING GRAB RAIL: standard (2) 2ft rails or (1) 6ft rail anti-microbial**  
 Cabinet wall "A" will have (1) 6' rail over cot as standard.  
 Cabinet wall "B" will have (2) 2' rails, 1-forward and 1-to rear of CPR seat.  
*LOCATE:   (1) 6 FT RAIL ON THE STREETSIDE EDGE OF CENTER CEILING PLATE.*
  
- KG09K000   1   1   PATIENT DOOR GRAB RAILS: angled with anti-microbial coating**  
 All patient access doors to have heavy duty angled stainless steel grab rails with smooth radius corners and flange mounting and anti-microbial coating.
  
- KG110000   1   1   FLOOR TRIM**  
 Trim floor with cove molding at non rolled areas of floor.
  
- KG120000   1   1   CABINET TRIM**  
 Trim all vertical and horizontal edges.
  
- KG16B000   1   1   CEILING MATERIAL, PLATINUM WHITE ALUMINUM COMPOSITE**  
 The standard module ceiling material shall be platinum white aluminum composite.
  
- KSP00001   0   1   SPECIAL INSTRUCTION, INTERIOR ACCESSORIES & TRIM**  
*!!! FABRICATE AND INSTALL A 3 POSITION GLOVE BOX HOLDER IN THE HEADER ABOVE THE REAR DOORS.*



KEY WEST FIRE DEPARTMENT  
1600 N. ROOSEVELT BLVD  
KEY WEST, FL 33040  
DAVID FRAGA



# Selected Feature List 11809

Year: 2014  
Chassis: Ford Type III, 138"WB, 80"  
Model: 453

Option   Std Qty   Header/Description/Data   Proposal Total

---

**L**   **COT MOUNTS AND ACCESSORIES**

---

LG03F000   0   1   **COT MOUNT, SINGLE: Stryker**  
Install Stryker cot mount for single position.  
COT MODEL:   STRYKER  
LOCATE:   CENTER MOUNT

**MM**   **ELECTRICAL EMERGENCY VISUAL WARNING SYSTEMS**

---

MM01A000   0   1   **WIG WAG HEADLIGHTS:**  
Install wig wag headlight flasher.

MM030000   1   1   **WHELEN M SERIES LIGHTING OPTIONS:**

0   1   **M7 SERIES LED, AMBER**  
mm07a000   Whelen M7 series L.E.D. lights shall be installed in the designated locations.  
LOCATION:   CENTERED OVER THE REAR ENTRY DOORS  
LENS COLOR:   CLEAR

0   4   **M7 SERIES LED, RED**  
mm07r000   Whelen M7 series L.E.D. lights shall be installed in the designated locations.  
LOCATION:   (2) CHASSIS INTERSECTION LIGHTS  
              (2) GRILLE LIGHTS  
LENS COLOR:   CLEAR



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	----------------	--------------------------------	-----------------------

0	12	<b>M9 SERIES LED, RED</b>	
mm09r000		Whelen M9 series L.E.D. lights shall be installed in the designated locations.  <i>LOCATION: (2) FRONT FACE, OUTBOARD CORNERS            (2) FRONT FACE, OUTBOARD OF CENTER WHITE FLASHER            (2) STREETSIDE            (2) CURBSIDE            (2) REAR FACE, UPPER OUTBOARD CORNERS            (2) REAR FACE, WINDOW LEVEL</i>  <i>LENS COLOR: CLEAR</i>  <i>!!! PROGRAM AT THE LIGHT HEADS FOR RANDOM FLASH PATTERN.</i>	

0	1	<b>M9 SERIES LED, WHITE WITH CLEAR LENS</b>	
mm09w000		Whelen M9 series L.E.D. lights shall be installed in the designated locations.  <i>LOCATION: CENTER FRONT FACE BELOW CONDENSER PER DRAWING.</i>	

<b>MN</b>	<b>AUDIBLE EMERGENCY WARNING SYSTEMS</b>
-----------	--

MN35EF20	0	1	<b>SIREN, FEDERAL EQ2B</b>	
			Specified siren to be: Federal EQ2B 200 watt electronic with digital output control.	
MN40A000	1	1	<b>SIREN INSTALL:</b>	
			The siren listed above shall be supplied and mounted as defined.  <i>LOCATE: FRONT SECTION OF CONSOLE, FORWARD OF CONTROL PANEL - DRIVER SIDE.</i>	
MN45BA00	1	1	<b>SIREN SPEAKERS, C.P. 3801 FOR FORD E SERIES</b>	
			Cast Products #SAD3801-08E35-1 & #SAP3801-08E35-1 siren speakers will be install in each outboard end of the chassis bumper.	
MN50A000	1	1	<b>SPEAKER INSTALL: bumper</b>	
			Speaker Selections (Bumper Installed)	

<b>O</b>	<b>LIGHTS</b>
----------	---------------

**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

<b>OL09M000</b>	0	1	<b>KKK SIDE BODY MARKER LIGHTS, M6 SERIES L.E.D. (PAIR)</b> Install red Whelen L.E.D. M6 series turn/marker lights on each rear side of the module body. Lights provide module body night time side lighting visibility and turning signal indication.	
-----------------	---	---	---	--

<b>OL34L000</b>	1	1	<b>LED EXTERIOR COMPARTMENT LIGHTING</b> All exterior compartments will be lighted with LED strip lighting. A vertical strip will be installed inside both sides of each compartment. The lights shall be directed toward the back of the compartment.	
-----------------	---	---	---	--

<b>OL350000</b>	0	1	<b>ICC MARKER LIGHTS</b> LED ICC marker lights shall be installed.	
-----------------	---	---	---	--

<b>OL35D000</b>	1	1	<b>ICC MARKER LIGHTS</b> Install standard rolled marker lights along the upper corner post front and rear.  <i>Note: Do not install if lightbar(s) already includes standard marker lights.</i>	
-----------------	---	---	--	--

<b>OM25CW0</b>	0	6	<b>M9 SERIES LED SCENE LIGHT</b> Install Whelen M9 series LED side scene lights.  <i>LOCATE: (2) PER BODY SIDE PER DRAWING            (2) ABOVE REAR ENTRY DOORS AS LOAD LIGHTS</i>	
----------------	---	---	--	--

<b>P</b>	<b>ELECTRICAL POWER GROUP</b>
----------	-------------------------------

<b>PAL00003</b>	0	1	<b>INTELLIPLX MULTIPLEX ELECTRICAL SYSTEM:</b> Install the Intelliplex Multiplex electrical system.	
-----------------	---	---	--	--

<b>PAL00A00</b>	0	1	<b>MODULE DISCONNECT DEFAULT</b> The module disconnect circuit shall default to the "on" position when the battery switch is activated.	
-----------------	---	---	--	--

KEY WEST FIRE DEPARTMENT  
1600 N. ROOSEVELT BLVD  
KEY WEST, FL 33040  
DAVID FRAGA



# Selected Feature List 11809

Year: 2014  
Chassis: Ford Type III, 138"WB, 80"  
Model: 453

---

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

---

**PAL01B00 1 1 BATTERY SWITCH: std. operation**

The "Master" battery switch shall switch battery power "on" and "off" to the ambulance body and conversion added electrical circuits only. All OEM chassis electric's, (headlights, ignition, keep alive) shall remain wired "hot" and have no ability to be switched "off", and provide circuit function as provided by the chassis manufacturer.

NOTE: DO NOT MODIFY OEM BATTERY SWITCH UNLESS STATED BELOW.

**PAL02000 1 1 INVERTER PREWIRE OPTIONS:**

**0 1 INVERTER PREWIRE: 20-1050CUL w/charger, on demand**

pal02h00

Furnish wiring only to the designated electrical equipment location to power a Vanner 20-1050CUL inverter. This inverter uses "On Demand" operation and no switch or wiring for a switch is installed. Charger portion of unit will be wired to shoreline circuit.

Inverter is not included in this option.

Locate: *STREETSIDE #1, LEFT HAND WALL.*

**PAL04E00 0 1 CHARGER/POWER SUPPLY: 80 AMP**

Install an 80 amp battery conditioner with ground fault protection shall be installed in the designated electrical equipment area. Conditioner to be wired to the batteries through the standard shoreline inlet.

LOCATE: *CURBSIDE FORWARD COMPARTMENT, SUBFLOOR AREA*

**PAL30A00 2 4 110V INTERIOR OUTLET**

Two 110V interior outlets are provided as standard on all models. The standard locations are in the inhalation area and the wall over the squad bench. Additional outlets are to be specified as to their location.

LOCATE: (1) FORWARD INHALATION AREA  
(1) REAR INHALATION AREA, UPPER LEFT CORNER  
(1) BENCH OVERHEAD CABINET, FORWARD  
(1) FRONT WALL CABINET, UPPER LEFT CORNER

KEY WEST FIRE DEPARTMENT  
1600 N. ROOSEVELT BLVD  
KEY WEST, FL 33040  
DAVID FRAGA



# Selected Feature List 11809

Year: 2014  
Chassis: Ford Type III, 138"WB, 80"  
Model: 453

---

Option    Std Qty    Header/Description/Data    Proposal Total

---

- PAL31C00    3    6    INTERIOR 12VDC OUTLETS: cigarette lighter type**  
12 volt outlets to use cigarette lighter style connectors.  
LOCATE:    (2) FORWARD INHALATION AREA  
              (1) REAR INHALATION AREA, UPPER LEFT CORNER  
              (2) FRONT WALL CABINET, UPPER LEFT CORNER  
              (1) FRONT WALL CABINET, BELOW CENTER SHELF, LEFT SIDE  
  
CONFIGURE:    BATTERY HOT
  
- PAL38E00    0    1    SHORELINE, KUSSMAUL SUPER AUTO EJECT, 20 AMP NON ARCING**  
Install a 20 amp Kussmaul non-arcing auto ejection shoreline receptacle.  
  
Locate:                            Street side of module body
  
- PAL40000    1    1    EXTRA 12VDC CIRCUIT BREAKER:**  
An extra circuit breaker shall be installed.
  
- PL10A000    1    1    SWITCH PANEL MOUNT:**  
Switch panel to be flush mounted in upper face of console.
  
- PL11A000    0    1    LIGHT PROGRAMMING: side rear scene**  
The side rear scene lights shall be wired to transmission reverse, plus standard mode of operation.
  
- PL11B000    0    1    LIGHT PROGRAMMING: right side scene**  
The right side scene lights shall come "on" when the side patient door is opened.
  
- PL11C000    0    1    LIGHT PROGRAMMING: load light**  
The rear load lights shall be wired to transmission reverse, plus the standard mode of operation.
  
- PL11F000    1    1    PROGRAMMING: AUDIBLE LOW VOLTAGE ALARM**  
Program an audible alarm to activate if the voltage drops below 11.8 volts for 120 seconds.

**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

<b>PL11G000</b>	1	1	<p><b>LIGHT PROGRAMMING: park brake</b></p> <p>A warning shall display on the front console readout, advising to set the Parking Brake, should the modular disconnect switch be "ON" and the transmission placed in "PARK" or "NEUTRAL". It will also advise to Disengage the Parking Brake should the vehicle be placed into gear.</p> <p><i>CONFIGURE: WIRE ALARM TO ACTIVATE WITH RED FLASHER CIRCUIT</i></p>	
<b>PL19A000</b>	1	1	<p><b>REPORT LIGHT</b></p> <p>Report lights shall be located at the action wall to light the counter area. Lighting to be Tecniq for Concept 3.</p> <p><i>LOCATE: ON BOTTOM OF UPPER INHALATION CABINET. CENTER OVER INHALATION PANEL. INCLUDES ON/OFF SWITCH IN THE REAR CONTROL PANEL.</i></p>	
<b>PL22C000</b>	1	1	<p><b>STEP WELL LIGHT:</b></p> <p>Install a 10.5" LED Vista light strip in the standard location on the bench side of the step well. Light to activate with door open.</p>	
<b>PL24T000</b>	0	1	<p><b>LAMP TIMER: programmable</b></p> <p>Install an electronic momentary touch timer switch where specified. The switch will enable time limited operation of the below listed lights, with the battery switch in the off position.</p> <p><i>LOCATE: CURBSIDE FORWARD WALL</i>  <i>LIGHTS CONTROLLED: BENCH DOME LIGHTS ONLY</i>  <i>SET ELAPSED TIME FOR: 15 MINUTES</i></p>	
<b>PL27CA00</b>	0	7	<p><b>PATIENT CEILING DOME LIGHTS: WHELEN LED</b></p> <p>Install Whelen 80C0EHCR LED dome lights in the patient area ceiling per the locations listed below. The lights will have a high/low feature with the switch in the rear control panel.</p> <p><i>LOCATE: PER DRAWING.</i>  <i>#10008603</i></p>	
<b>PL29P000</b>	0	1	<p><b>PREWIRE FOR FUTURE STREAMLIGHT INSTALLATION</b></p> <p>Prewire shall be provided as noted below for future installation of Streamlight charger bases.</p> <p><i>QTY: (1)</i>  <i>LOCATE: INSIDE CLOSE-OUT ABOVE RIGHT FRONT CABINET - AISLE SIDE.</i></p> <p><i>CONFIGURE: BATTERY HOT</i></p>	

**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

<b>PM110000</b>	0	1	<b>LIGHT PROGRAMMING: brake light</b> Lower red flashing lights to operate as brake lights when not in the warning mode.  <i>CONFIGURE: FLASHERS TO OVERRIDE BRAKE LIGHT FEATURE</i> <i>NOTE: FEATURE TO ACTIVATE REGARDLESS OF MODULE DISCONNECT STATUS</i>	
-----------------	---	---	--	--

<b>Q</b>	<b>HEATING, AIR CONDITIONING AND INTERIOR ENVIRONMENT</b>			
----------	---	--	--	--

<b>QH29N000</b>	0	1	<b>PAINT AUXILIARY CONDENSER, FRONT FACE, TO MATCH BODY:</b> Paint the auxiliary condensor mounted on the front face of the body to match the body color. Standard color is white.	
-----------------	---	---	---	--

<b>QH310000</b>	0	1	<b>3-PLY PANEL INTAKE FILTER</b> Install a 3-Ply Panel air intake filter ILOS. (1) 16.75" x 8.75" #10008973 for attendant seat base or above right front cabinet. (2) 13" x 18" #10009296 over #1 compartment or in bottom of linen cabinet. Filters will be behind stainless steel intake grills.	
-----------------	---	---	---	--

<b>QL430000</b>	0	1	<b>NFPA COMPLIANT VENTING-ALUMINUM PAINTED</b> Install an NFPA style venting system to include a 400cfm exhaust vent along with a static vent. Install 9.5" square aluminum covers on both vents per drawings. Covers to be painted body color.	
-----------------	---	---	--	--

<b>QSP00001</b>	0	1	<b>SPECIAL INSTRUCTION, HEAT/AC &amp; INTERIOR ENVIRONMENT</b>  <i>!!! INSTALL A 50,000 BTU PROAIR FREEZE-OUT MAX HEAT/AC SYSTEM MODEL #917.</i>  <i>LOCATE: ABOVE THE FRONT WALL CABINET STORAGE AREA.</i>  <i>!!! REQUIRES FRONT FACE 2-FAN CONDENSER INSTALLED WITH A PAN STYLE BRACKET. LOCATE PER DRAWING.</i>	
-----------------	---	---	---	--

<b>R</b>	<b>CAB CONSOLE AND COMMUNICATIONS</b>			
----------	---------------------------------------	--	--	--

**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

<b>RJ01A000</b>	1	1	<b>ANTENNA COAX 1:</b> An RG 58U coax shall be installed so that the ambulance conversion need not be disassembled.  <i>EXTERIOR TERMINATION: FORWARD CENTER MODULE ROOF</i> <i>INTERIOR TERMINATION: CAB CONSOLE</i>	
<b>RJ01B000</b>	0	1	<b>ANTENNA COAX 2:</b> Install additional antenna coax and accesses.  <i>EXTERIOR TERMINATION: MODULE ROOF PER DRAWING</i> <i>INTERIOR TERMINATION: BEHIND INHALATION PANEL</i>	
<b>RJ01C000</b>	0	1	<b>ANTENNA COAX 3:</b> Install additional antenna coax and accesses.  <i>EXTERIOR TERMINATION: REAR CENTER MODULE ROOF</i> <i>INTERIOR TERMINATION: BEHIND INHALATION PANEL</i>	
<b>RJ05A000</b>	1	1	<b>FRONT CONSOLE:</b> A console shall be fabricated to match the OEM dashboard material, color and texture. Room shall be provided on the face of the console for installation of radio and siren controls.  <i>Console #:</i>	
<b>RJ05C000</b>	0	1	<b>CONSOLE EXTENSION:</b> A box for mounting radio heads and storage maps, books, or binders will be attached to the standard engine cover console. Standard box includes (3) 2.5 storage sections, and 8.5 faceplate for radio mounting.  <i>!!! INCLUDES ADJUSTABLE DIVIDERS.</i>	
<b>RJ08A000</b>	0	2	<b>RADIO POWER/GROUND:</b> Install three 6 gauge cables to positive and ground studs for radio power. Wire one constant hot, one ignition hot and one ground.  <i>LOCATE: INSIDE CAB CONSOLE.</i> <i>BEHIND INHALATION PANEL.</i>  <i>CONFIGURE: BATTERY SWITCHED, BATTERY HOT AND GROUND</i>	

<b>T</b>	<b>OXYGEN AND SUCTION</b>
----------	---------------------------



**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

Option    Std    Oty    Header/Description/Data    Proposal Total

---

- TN002000    1    1    OXYGEN BOTTLE MOUNT, VERTICAL TRACK FOR QRM-V**  
 Vertical track for mounting of a QRM-V O2 bottle mount shall be welded on the back wall of the compartment in the right hand corner. The O2 bottle mount is adjustable for "M" or "H" size tanks.  
*LOCATE:    STREETSIDE REAR COMPARTMENT, BACK WALL, RIGHT SIDE.*
- TN01MW00    1    1    OXYGEN BOTTLE, CYLINDER BRACKET: Zico**  
 Zico QRM-V oxygen bracket shall be installed.  
*LOCATE:            STREETSIDE REAR*  
*TANK SIZE:    "M"*  
  
*!!!    INSTALL THE BRACKET ON WALL APROX 6" ABOVE THE FLOOR TO ALLOW FOR STORAGE OF "D" BOTTLES UNDERNEATH.*
- TN020000    0    1    OXYGEN ACCESS:**  
 A clear Plexiglas door shall be provided in the patient area wall for access to the oxygen cylinder valve. The door shall be hinged so that it swings into the oxygen cylinder storage compartment. The opening shall be trimmed with anodized aluminum edging. O.D. dimension of the access is 7" wide x 11" high.  
*LOCATE:    STREETSIDE REAR WALL PER DRAWING.*  
  
*!!!    NOTE CONCEPT STYLE O2 ACCESS CLEAR DOOR OPENING IS    5.75" X 5.75"*
- TN030000    2    2    OXYGEN OUTLETS, STANDARD**  
 Two oxygen outlets shall be provided as standard and shall be located in the inhalation panel.
- TN03A000    0    1    OXYGEN OUTLET: additional**  
 Install additional oxygen outlet(s).  
*LOCATE:    CURBSIDE WALL PER DRAWING.*
- TN04A000    1    1    ADAPTER TYPE: Ohio Diamond II**  
 Oxygen outlets to be Ohio Diamond II.
- TN060000    1    1    OXYGEN WRENCH:**  
 Install oxygen wrench in oxygen compartment. Mount secure so not left hanging. Mount with length of chain or cable so not removable.

**KEY WEST FIRE DEPARTMENT**  
 1600 N. ROOSEVELT BLVD  
 KEY WEST, FL 33040  
 DAVID FRAGA



# Selected Feature List 11809

**Year:** 2014  
**Chassis:** Ford Type III, 138"WB, 80"  
**Model:** 453

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

<b>TN08B100</b>	0	2	<b>D BOTTLE MOUNT: QR-D-2 SINGLE, STRAPLESS</b> Install a Zico QR-D-2 Quic-release strapless d-cylinder oxygen bracket.  <i>Locate: SIDE OF FRONT WALL CABINET</i>	
-----------------	---	---	---	--

<b>TSP00001</b>	0	1	<b>SPECIAL INSTRUCTION, OXYGEN &amp; SUCTION</b>  <i>!!! INSTALL A IMPACT 324 ASPRIATOR IN THE INHALATION AREA. LOCATE ON CUSTOMER INSPECTION ON FIRST VEHICLE.</i>	
-----------------	---	---	---	--

<b>U</b>	<b>LETTERING</b>			
----------	------------------	--	--	--

<b>UP010000</b>	0	1	<b>LETTERING:</b> Lettering to be included.  <i>!!! EXACT CONFIGURATION TBD AT PRE-BUILD.</i>	
-----------------	---	---	--	--

<b>UP020000</b>	0	1	<b>LETTERING:</b> No lettering included.	
-----------------	---	---	---	--

<b>UP180000</b>	1	1	<b>DOOR REFLECTORS</b> Install 2" x 12" strips of red Scotchlite at the top of each entry door placed horizontally.	
-----------------	---	---	--	--

<b>UP200000</b>	0	1	<b>SPECIAL LETTERING:</b> Instructions and/or description requiring special consideration.  <i>!!! INSTALL WHITE VINYL OVERALL HEIGHT STICKERS ON INSIDE OF DRIVER SIDE WINDSHIELD.</i>	
-----------------	---	---	--	--

<b>Y00</b>	0	1	<b>PRICE ADJUSTMENT: discount</b> Price discount, and or consideration.  <i>MULTIPLE VEHICLE DISCOUNT: \$1500</i>	
------------	---	---	--	--

<b>Z00</b>	0	1	  <i>PRICE INCLUDES (2) FACTORY INSPECTION TRIPS FOR UP TO (3) PEOPLE.</i>	
------------	---	---	--	--

KEY WEST FIRE DEPARTMENT  
1600 N. ROOSEVELT BLVD  
KEY WEST, FL 33040  
DAVID FRAGA



# Selected Feature List 11809

Year: 2014  
Chassis: Ford Type III, 138"WB, 80"  
Model: 453

Option   Std   Qty   Header/Description/Data   Proposal Total

---

Z02      0      1      **Factory Pickup and Transportation**  
Allowance for vehicle pickup, transportation and drivers fee.  
F.O.B. KEY WEST, FL

Z03      0      1      **Dealer Prep. and Dealer Delivery**  
Allowance for vehicle preparation and delivery.

Z04      0      1      **Fuel, Tags, Etc.**  
Allowance for fuel, tags and administrative.  
  
!!! MAINTAIN MINIMUM FUEL LOAD UNTIL FINAL DELEIVERY.

Z06      0      1      **STATE CONTRACT:**  
This vehicle is subject to state contract pricing.  
FLORIDA SHERIFFS ASSOCIATION CONTRACT # 11-10-1202 1/2% FEE

**Total Configured Cost**      \$130,597.00

Authorized Department Signature(s): \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_