



# Fire Apparatus Quotation for: KEY WEST FIRE DEPARTMENT



Quotation Number: 84669 Rev: 7

Unit Description: IAVA-COMM

Quote Description: Initial Attack, Aluminum, Commerical

Salesperson: RWILSON

Salescode	Extended Description	Qty	
TIRE OPTIONS			
1060-0117	RWC AirGuard LED tire pressure monitoring valve stem caps (6) for single rear axle applications.	1	
TESTING COMPLIANCE STANDARD			
1001-0068	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition except for the occupant detection system with display and vehicle data recorder which are not available on the Ford chassis. Equipment allowance exception also applies.	1	
3090-0002	OAH. Unit has no overall height restrictions.	1	
3090-0004	OAL. Unit has no overall length restrictions.	1	
3340-1137-12A	Equipment allowance on the apparatus shall be 1500 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1	
3340-1140	Hosebed hoseload allowance on the apparatus shall be 500 lbs.	1	
CHASSIS PREP			
1020-0023	Commercial Chassis Preperation for the Ford Super Duty Series.	1	
1020-0024	Ember Seperator - Ford.	1	
ENGINES & TRANSMISSIONS			
1200-0025	Speed maximum 75 MPH.	1	
1200-0216	FORD F550 6.8L V10 Gasoline Engine	1	
CHASSIS OPTIONS			
1680-0012	Tow eyes rear frame painted black.	1	
1680-0078	Tow hooks front OEM. Not available with extended E-ONE installed front bumper. Tow hooks are OEM supplied with chassis.	1	

Salescode	Extended Description	Qty	
CAB			
1500-0047	Ford Commercial Super Duty Cab (aluminum) and Chassis 2 door F550 4X2.	1	
CAB BADGE PACKAGE			
1610-0000	Cab and body to have applicable E-ONE logos.	1	
CAB DOOR OPTIONS			
1550-0227	Reflective striping shall be installed on commercial cab doors, visible when the door is open, meeting NFPA requirement of 96 sq. in. coverage for each door.	1	
MISC EXTERIOR CAB OPTIONS			
1675-0120	Unleaded fuel only label.	1	
1675-0202	Mounting plate for battery charger receptacle, indicator, air inlet, etc (if applicable). Plate to be removable brushed stainless steel.	1	
SEATS			
1685-0012	Seating capacity tag of two occupants.	1	
MISC INTERIOR CAB OPTIONS			
1685-0009	Chain for ignition key	1	
1685-0450	Center control console painted black Zolatone. Locate in cab between driver and officer. Includes area for NFPA siren, electrical, and in-cab controls (as applicable) switching.	1	
CAB ELECTRICAL OPTIONS			
1750-0024-062-04	Auto-Eject receptacle inlet 20 amp located driver side front compartment face with a Yellow cover.	1	
1750-0343	Battery charger E-ONE LPC 20. 120 volt inlet, 20 amp output.	1	
1750-0526	Dome Lts Red/White Incandescent. Package includes two lights mounted in the front of the cab. White light wire through door and light assembly mounted switch. Red light through light assembly mounted switch.	1	
RESCUE BODY REAR			
3096-0058	8" Tailboard Bolt-On With Bracing Rescue.	1	
BODY COMPT LEFT SIDE			
3100-0287	Driver side body with 19.5" wide forward and 31" wide rearward compartmentation. Includes (1) 40" wide compartment over the wheel well.	1	
BODY COMPT RIGHT SIDE			
3120-0455	Officer side body with 19.5" wide forward and 31" wide rearward	1	

Salescode	Extended Description	Qty	
BODY COMPT RIGHT SIDE			
	compartmentation. Includes (1) 40" wide compartment over the wheel well.		
BODY COMPT REAR			
3110-0159	Full Height Rear Compartment with smooth plate panels for mini pumper. Compartment width will be 44" wide.	1	
DOORS			
3300-0017-004	Door roll up short (up to 45") with satin finish ROM. Location(s): L2.	1	
3300-0017-016	Door roll up short (up to 45") with satin finish ROM. Location(s): R2.	1	
3300-0017-027	Door roll up short (up to 45") with satin finish ROM. Location(s): B1.	1	
3300-0019-003	Door roll up tall (greater than 45") with satin finish ROM. Location(s): L1.	1	
3300-0019-005	Door roll up tall (greater than 45") with satin finish ROM. Location(s): L3.	1	
3300-0019-015	Door roll up tall (greater than 45") with satin finish ROM. Location(s): R1.	1	
3300-0019-017	Door roll up tall (greater than 45") with satin finish ROM. Location(s): R3.	1	
SHELVES			
3370-0052-003	Adjustable shelf (J-Style) for non-transverse compartments 16" or greater in depth. Location: L1.	1	
3370-0052-005	Adjustable shelf (J-Style) for non-transverse compartments 16" or greater in depth. Location: L3.	1	
3370-0052-015	Adjustable shelf (J-Style) for non-transverse compartments 16" or greater in depth. Location: R1.	1	
3370-0052-017	Adjustable shelf (J-Style) for non-transverse compartments 16" or greater in depth. Location: R3.	1	
3370-0054-003	Tracks for adjustable shelf and/or adjustable tray in compartments 16" or greater in depth. Location: L1.	1	
3370-0054-005	Tracks for adjustable shelf and/or adjustable tray in compartments 16" or greater in depth. Location: L3.	1	
3370-0054-015	Tracks for adjustable shelf and/or adjustable tray in compartments 16" or greater in depth. Location: R1.	1	
3370-0054-017	Tracks for adjustable shelf and/or adjustable tray in compartments 16" or greater in depth. Location: R3.	1	
TRAYS / TOOLBOARDS			
3380-0076-003	Tray, floor mounted roll-out with gas spring. 500 lbs. capacity. Location: L1.	1	
3380-0076-017	Tray, floor mounted roll-out with gas spring. 500 lbs. capacity. Location: R3.	1	
COVERS			

Salescode	Extended Description	Qty	
<b>COVERS</b>			
3305-0007-000-13	Vinyl Black hose bed cover with attached rear flap(s).	1	
3305-0008-000-13	Vinyl Black crosslay cover with attached side flaps.	1	
<b>PUMP MODULE</b>			
3130-0012	Upper SM pump module with double stacked double crosslays and diamond plate storage pan.	1	
3130-0167	Pump module to be 76" wide (side to side). Includes upper, lower, crosswalk, speedlay and tranverse module(s) if applicable.	1	
3130-0409	Pump module. Includes 31" wide pump panel opening and running boards.	1	
<b>PUMP PANELS</b>			
3134-0006	The single gauge panel on the driver's side of the side mount module is to be hinged downward. Includes two (2) cable hold opens, and latches.	1	
3134-0011	Officer side pump panel to be vertical hinged on forward extrusion. Panel(s) to be secured in the closed position with push button latches. Upper panel to be held open with gas shock.	1	
3134-0016	Stainless steel driver and officer side pump panels.	1	
<b>MISC PUMP PANEL OPTIONS</b>			
4460-0003	Pump panel tags color coded per NFPA compliance.	1	
<b>PUMP MODULE OPTIONS</b>			
3136-0011	P-Rubber in flex joint(s) between pump module and/or body modules.	1	
3136-0058	E-ONE logo mounted one each side on pump module/preconnect panels. Logos to be sized as applicable to available space on panels.	1	
<b>WATER TANK</b>			
4010-0099	Fill tower(s) to be located offset to officer side of water tank.	1	
4010-0253	300 gallon "R" water tank. UPF Poly III blue fill tower.	1	
<b>TANK PLUMBING</b>			
4450-0010	2" tank fill Akron manual valve.	1	
4450-0119	3" tank to pump Akron manual valve w/4" tank connection.	1	
<b>LADDER STORAGE / RACKS</b>			
3365-0049	Brand of ladders capable of being carried on unit to be Alco-Lite.	1	
3365-0262	Double Hard Suction Storage Rack for 8' hard suction hoses. Driver side compartment top. Includes spring hold downs with scuff plates (as applicable)	1	

Salescode	Extended Description	Qty	
<b>LADDER STORAGE / RACKS</b>			
3365-0898	Ladder storage officer side compartment top. Includes boot at forward compartment top and a hold-down for (1) 24' 3-section PEL3 and (1) 10' roof ladder.	1	
<b>HANDRAILS / STEPS</b>			
3330-0277	Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on driver side rear of the body. (staggered stepped as applicable with tailboard depth) for NFPA hosebed access and handrail mounted on driver side upper hosebed side (as applicable).	1	
3330-0279-062	Innovative Controls dual lighted LED folding step. Location: driver side front compartment face. Each location requires a minimum of (1) handrail per NFPA.	3	
<b>MISC BODY OPTIONS</b>			
3340-0004	Hosebed above the booster tank. Includes forward hosebed and tower(s) cover plate work (as applicable). Hosebed adjustable divider extrusion rearward of the furthest tower is to run full width of the hosebed (as is practical with other hosebed mounted equipment).	1	
3340-0015	Diamond plate single axle wheel well. Includes bolt-on composite wheel well liners and aluminum trim fenderettes.	1	
3340-0035	Divider Long. To run full length of hose bed (front to rear).	1	
3340-0093	Mud flaps, rear, black with E-ONE logo.	1	
3340-0110	The rear of each hose bed divider to have a hand hold cut-out(s).	1	
3340-0145	Rub rail for the body and pump area module(s).	1	
3340-0544	Body mainframe and hosebed side assemblies for a 70" high body	1	
3340-0671	Recessed fuel fill driver side wheel well supplied by Ford.	1	
<b>SCBA BOTTLE STORAGE</b>			
3320-0093	SCBA bottle storage. (3) Fire Shopp style SCBA bottle storage with hinged brushed stainless steel doors with push-button latches. (2) officer side and (1) driver side in the forward wheel well area.	1	
3320-0100	Strap, loop style to retain SCBA bottle(s). Locate one per bottle in each exterior body storage compartment.	1	
<b>PUMPS</b>			
4005-0035	Rating 1000 GPM	1	
4005-0216	Hale MG Pump 500/1000 GPM single stage. Requires primer option.	1	
<b>PUMP CERTIFICATION</b>			

Salescode	Extended Description	Qty	
PUMP CERTIFICATION			
4475-0000	Pump certification 750-2250 GPM	1	
PUMP OPTIONS			
4015-0016	Thermal relief valve, Hale TRVL-120.	1	
4015-0053-198	Steamers to be Flush + 1". Location: driver's side.	1	
4015-0053-199	Steamers to be Flush + 1". Location: officer's side.	1	
4015-0073	Manual operated master pump drain. The master drain shall be clearly marked and placed in accessible location below running board on driver side (or area directly to rear of panel if no room below panel).	1	
4015-0210	Pump cooler with Innovative Control 1/4 turn valve with "T" handle and label.	1	
4015-0238	Hale electric primer (oil-less).	1	
INTAKES			
4440-0005	2.5" Left Intake Akron Manual Valve.	1	
4440-0006	2.5" Right intake Akron manual valve.	1	
INTAKE OPTIONS			
4445-0048	Intake pressure relief valve, Task Force Tips.	1	
DISCHARGES AND PRECONNECTS			
4415-0012-654	1.5" Crosslay with Akron manual valve. Location: crosslay 1 & 2.	2	
4415-0014-581	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 1.	1	
4415-0016-584	2.5" Right Pump Panel Discharge Akron Manual Valve. Location: right side discharge 2.	1	
4415-0164-583	2.5" Right Panel Discharge Akron Manual Valve w/30 Degree Chrome Droop. Location: right side discharge 1.	1	
DISCHARGE OPTIONS			
4417-0176	Innovative Controls 3/4" bleeder/drain valve include lift lever with ergonomic grip.	5	
4417-0185	Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel.	1	
PRESSURE GOVERNORS			
4465-0017	FRC PumpBoss pressure governor PBA400. Includes engine monitor gauges.	1	
GAUGES			

Salescode	Extended Description	Qty	
<b>GAUGES</b>			
4435-0083	Innovative Controls 10 LED SL series water tank level gauge. On pump panel.	1	
4435-0246	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel.	5	
4435-0247	4" Innovative Controls stainless steel case master pressure gauges with bezel. Intake 30-0-400, and discharge 0-400.	1	
<b>ELECTRICAL SYSTEMS</b>			
5010-0036	V-MUX Electrical system for pumper / tanker / rescue.	1	
5010-0059-B13	VFD Text display for V-MUX electrical system. Location: center console.	1	
5010-0094	Nanoprotech corrosion inhibiting spray coating to be applied on all exposed electrical connections.	1	
<b>LIGHT BARS</b>			
5300-0160	Light bar Federal Signal JetSolaris 60" LED. Red Solaris reflectors with center traffic clearing light. NFPA compliant, does not require 2 addl side facing bars. Location: Centered on the front cab roof.	1	
<b>WARNING LIGHT PACKAGES</b>			
5550-0193-538	Federal Signal QuadraFlare LED lower level warning light package. Includes (6) QL64XF-R LED light heads with bezels and (4) IMPAXX LED model IPX302-4 light heads. Locate side facing lights: at forward most position, in rear wheel well offset to front, and side facing at rear of body in rubrail if equipped.	1	
<b>WARNING LIGHTS</b>			
5600-0034-479-08	Federal model SY12FS Sentry (PR) with driver red, officer amber domes. Location: rear upper body on aerial style brackets.	1	
5600-0105-B13	Hazard (door ajar) light 2" LED. Location: center console.	1	
<b>SIRENS</b>			
5500-0009	Federal PA300 electronic siren recessed mounted.	1	
5500-0024-B13	The primary electronic siren control is to be located center console.	1	
<b>SPEAKERS</b>			
5510-0029-209	Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: driver side front bumper.	1	
<b>DOT LIGHTING</b>			
5150-0017	License plate light LED with chrome housing located at the rear of the body.	1	
5150-0032	Bracket license plate at rear of body.	1	

Salescode	Extended Description	Qty	
DOT LIGHTING			
5150-0059	Federal Signal QuadraFlare LED vertical mount tail lights. Includes LED stop/tail, arrow turn and back-up lights with vertical Cast 3 housing and weatherproof connectors.	1	
5150-0125	Marker light TeqNiq .75" LED body package. Commercial light rescue or initial attack vehicle bodies.	1	
LIGHTS - COMPARTMENT, STEP & GROUND			
5380-0011	Compartment light package LED for small bodies.	1	
5380-0200	Ground light package EON LED - small.	1	
LIGHTS - DECK AND SCENE			
5390-0007	Deck/scene light circuit wiring through chassis reverse. Requires rear deck or scene light.	1	
5390-0048-457	Whelen 600 series gradient Super LED scene lights (PR) with weatherproof connectors. Switch in cab (driver and officer side lights switched separately). Locate (1) each side of body rear facing up high.	1	
5390-0076	Hose bed light Truck-Lite LED model 81380. Locate at front of hose bed. Switched with work light switch in cab.	1	
5390-0102	Crosslay light Truck-Lite LED model 81380. Locate to rear of crosslay (SM) and forward of crosslay (TM as applicable). Switched with work light switch in cab.	1	
LIGHTS - NON-WARNING			
5400-0150	Pump panel LED light package for side mount. Includes (6) Tecniq EON lights with S/S housings located (3) ea side. Includes S/S light shields (as applicable with intermedialte steps).	1	
5400-0151	Pump compartment light EON LED. Wired to work light.	1	
MISC ELECTRICAL			
5110-0017	Back-up alarm 97 dB.	1	
5110-0111	All 12 Volt electrical components and Multiplex box will be located in recessed box at rear between frame rails.	1	
HOSE / NOZZLES			
7700-0004	Hard suction hose 6" X 10'. Smooth bore, black rubber hard suction hose for heavy duty service. Built with a spiral wire helix, and nylon fabric reinforcement piles. Tube and cover are taut, black rubber that is age and abrasion resistant.	2	
GROUND LADDERS			
7800-0017	Alco-Lite PEL3-24 extension ladder.	1	



Salescode	Extended Description	Qty	
GROUND LADDERS			
7800-0032	Alco-Lite FL-10, 10' folding ladder w/safety shoes.	1	
MISC LOOSE EQUIPMENT			
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1	
EXTERIOR PAINT			
8100-0089	All applicable pump/pre-connect application modules are to have a sanded finish (not painted job color). Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color.	1	
8100-0116	Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels.	1	
8100-0182-000-2G	Paint Body - Small - For Pumpers, Rear Mounts, S/A Tankers/Wetsides and Rescues. Sikkens paint. Color: PQ Ford Race Red-Sikkens FA11:PQ.	1	
STRIPING			
8300-0001	NFPA required reflective striping to be dealer/customer applied.	1	
8300-0042	White rubrail scotchlite insert.	1	
8300-0084-000-72	Chevron "A" style 6" printed sheet Scotchlite striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Yellow/Red.	1	
WARRANTY / STANDARD & EXTENDED			
9100-0000	Standard 1 Year Warranty.	1	
9100-0004	10 Year/100,000 Mile Structural Warranty for Alum Cab / Body - Statement of Warranty.	1	
9100-0019	10 Year Limited Paint and Perforation Warranty - For Sikkens Paint.	1	
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS			
9300-0009	Manuals, Operator and Service in digital format.	1	
Dealer Supplied Equipment			