

Cale Web Terminal (CWT)

TECHNICAL SPECIFICATIONS

Dimensions, Weight & Materials

Dimensions (H x W x D):

61.22 inches (1555 mm) x 16.42 inches (417 mm) x 15.35 inches (390 mm)

Construction:

304 stainless steel

Cash Vault:

0.16 inches (4 mm) sheet metal with side-drilling protection

Cash Vault Door:

0.24 inches (6 mm) hardened steel, 4-way and 6-way drilling protected locking latches

Cash Vault Locks:

Abloy Exec.

Optional:

Electronic locks, Patented Cale technology with central administration that features mechanical and electronic opening mechanisms

Weight:

229 pounds (104 kg)

Paint:

Powder coated with anti-graffiti treatment

Standard Color:

Black*

**Custom colors and wraps also available*

Compliance with EN 12414, CE, FCC, Electrical safety
Designed and produced according to ISO 9001 and ISO



Electrical Data

Mains operation:
230 V/115 V AC
Battery operation:
12 V DC**
Solar operation:
12 V, 10.5 W***

Operating Temperature

Solar 0 to 140 °F (-15 to 60 °C)
Mains with heater -31 to 140 °F (-35 to 60 °C)
Relative humidity Up to 97%

** Period of operation will depend on ticket purchase volumes

*** Operation time on battery depends on the size and position of the solar panel and geographical location

All measurements in inches

Operation

Function buttons

Touch technology:

4 software-controlled buttons below the display
Separate "Accept" and "Reject" buttons
Alphanumeric keyboard with up to 48 buttons
Piezo keypad and buttons*

*Only available for the monochrome and color displays.
Keypad not available for color displays.

CPU System & Display

Graphical Display:

Monochrome, 6.6 inches
Color Display, 7 inches
Color Touch Screen Display, 9 inches
Supports multiple languages

Application & Data Memory:

SD card, up to 4 GB

Near Field Communication

NFC:

Contactless card or RFID tag for Electronic Lock Access and Cale Online Permit Account services

Communication

GPRS, 3G, LAN Supported
4G Supported

Types of data:

Transactions, blacklists, rates, parameters, SW, OS, Firmware, statistics, alarms, etc.

Miscellaneous

Buzzer:

Supported

Audio:

Multi-language audio support with pre-recorded messages or sounds at the touch of a button

Motion Sensor Light Bar:

Supported; lights up to the door

Central Administration

Software:

Cale WebOffice back office system
Hosted Software as a Service (SaaS) Solution

Coin System

Coin verifier:

Industry standard for up to 16 coins/tokens, three switch controlled, reprogrammable, tolerance ranges

Coin slot:

Mechanical coin slot shutter with inductive loop

Escrow volume:

1.8 fl. oz (US), 12.3 fl. oz (UK) (0.35 liters) approximately

Coin box volume:

155.5 fl. oz (US), 161.9 fl. oz (UK) (4.6 liters) approximately with presence sensor. SW controlled overflow protection. Closed cash-collection system supported

Ticket Printer

Printer type:

Thermo-electric

Graphics:

Supported

Orientation:

Landscape and Portrait

Width Of Paper Supply Roll:

2.24 inches (57 mm)

Black mark:

Supported

Ticket Length:

2.95 inches - 5.90 inches (75-150 mm)

No. Of Tickets:

Up to 3,000 per roll for 4" tickets

Paper Thickness:

55 - 110 g/m²

Paper loading:

Automatic

"Take Ticket" Sensor:

Standard

Payment

Magnetic stripe (Magstripe) cards Insertion reader for track2 with various online processing services
Contactless Mifare DESFire smart card support Also used for Electronic Lock Access and Cale Online Permit Account services

Bank Note Reader

Complete transport:

1.7-2.5 seconds cycle

Note insertion:

Four-way

Validation rate:

96% or higher

Escrow:

Single bill

Refund voucher supported:

Yes

Bill width range MSM version:

2.4 inches - 3.1 inches

SM version:

2.6 inches - 2.8 inches
(67 or 71 mm)

Cassette sizes:**MSM version:**

300, 500, or 1,000 notes

SM version:

400, 600 or 1,500 notes



About Cale

From the moment Cale was founded in 1955, we have offered innovative and efficient parking solutions. We specialize in creating technology for parking pay stations and meters, mobile payment systems, transaction handling and centralized software that seamlessly integrates with your parking operations. As a world-leading brand within the parking industry, our products and subsidiaries can be found in more than 40 countries around the world.

Cale is certified according to ISO 9001 and ISO 14001. We are also certified according to PCI standards and follow the International Standard on Assurance Engagements (ISAE) No. 3402.

Cale's priority is to engage in continuous product development. Therefore, we reserve the right to alter product specifications and designs without prior notice.

Pay stations and meters are available in a variety of configurations. Please note that some functions listed here are optional.

Cale America

13190 56th Court, Suite 401

Clearwater, FL 33760

United States

Phone: 727-724-1800 (press option 3)

Email: sales@caleamerica.com

Web: caleamerica.com



CALE

Stay ahead